



## SAFETY DATA SHEET (Aerosol) Silver King

### SECTION 1: Identification: Product identifier and chemical identity

#### Product identifier

**Product name** (Aerosol) Silver King

**Product No.** A53-7

#### Relevant identified uses of the substance or mixture and uses advised against

**Application** Car maintenance product. - Paint.

**Uses advised against** For professional use only. This product is not recommended for any industrial, professional or consumer use other than the Identified uses above.

#### Details of the supplier of the safety data sheet

**Supplier** Autosmart Australia  
11 Darrambal Close  
Rathmines  
NSW 2283  
Australia  
[www.autosmartaustralia.com.au](http://www.autosmartaustralia.com.au)  
Tel: 02 49 75 14 88 (Mon to Fri, 08:00 - 16:00 AEST) (General Information. Transport Information. Mild Medical Information)  
[autosmart@autosmartaustralia.com.au](mailto:autosmart@autosmartaustralia.com.au)

**Contact Person** Mr. Russell Butler

**Manufacturer** Autosmart International Ltd..  
Lynn Lane  
Shenstone, nr Lichfield  
Staffordshire WS14 0DH  
Great Britain  
[www.autosmartinternational.com](http://www.autosmartinternational.com)  
Tel: +44 (0) 1543 481616 (09:00 - 17:00)  
Fax: +44 (0) 1543 481549 (09:00 - 17:00)  
[info@autosmartinternational.com](mailto:info@autosmartinternational.com)

#### Emergency telephone number

**Emergency telephone** Emergency No: +44 7808 971321 (24hrs) (Autosmart International, UK)  
General Information. Transport Information. Mild medical Information:-  
Tel: 02 49 75 14 88 (Mon to Fri, 08:00 - 16:00 AEST)

**National emergency telephone number** Poison Information Hotline: 13 11 26

### SECTION 2: Hazard(s) identification

#### Classification of the substance or mixture

**Physical hazards** Aerosol 1 - H222, H229 Press. Gas, Compressed - H280

**Health hazards** Eye Irrit. 2A - H319 STOT SE 3 - H336

**(Aerosol) Silver King****Environmental hazards** Aquatic Chronic 3 - H412**Label elements****Pictogram****Signal word**

Danger

**Hazard statements**

H229 Pressurised container: may burst if heated  
 H280 Contains gas under pressure; may explode if heated.  
 H319 Causes serious eye irritation.  
 H336 May cause drowsiness or dizziness.  
 H412 Harmful to aquatic life with long lasting effects.

**Precautionary statements**

P210 Keep away from heat/ sparks/ open flames/ hot surfaces. - No smoking.  
 P211 Do not spray on an open flame or other ignition source.  
 P251 Pressurized container: Do not pierce or burn, even after use.  
 P280 Wear protective gloves.  
 P284 Wear respiratory protection.  
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

**Supplemental label information**

EUH066 Repeated exposure may cause skin dryness or cracking.  
 For professional users only.

**Contains**

ACETONE, BUTYL ACETATE -norm, METHYL ETHYL KETONE, SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM.; LOW BOILING POINT NAPHTHA

**Other hazards**

This product does not contain any substances classified as PBT or vPvB.

**SECTION 3: Composition and information on ingredients****Mixtures**

<b>ACETONE</b>	<b>30&lt;60%</b>
CAS number: 67-64-1	
Substance with a Community workplace exposure limit.	
<b>Classification</b>	
Flam. Liq. 2 - H225	
Eye Irrit. 2A - H319	
STOT SE 3 - H336	
<b>PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS</b>	<b>30&lt;60%</b>
CAS number: 68476-85-7	
Substance with a Community workplace exposure limit.	
<b>Classification</b>	
Flam. Gas 1 - H220	
Press. Gas, Liquefied - H280	

**(Aerosol) Silver King**

<b>BUTYL ACETATE -norm</b>	<b>5&lt;10%</b>
CAS number: 123-86-4	
<b>Classification</b> Flam. Liq. 3 - H226 STOT SE 3 - H336	
<b>METHYL ETHYL KETONE</b>	<b>5&lt;10%</b>
CAS number: 78-93-3	
<b>Classification</b> Flam. Liq. 2 - H225 Eye Irrit. 2A - H319 STOT SE 3 - H336	
<b>2-METHOXY-1-METHYLETHYL ACETATE</b>	<b>2&lt;3%</b>
CAS number: 108-65-6	
<b>Classification</b> Flam. Liq. 3 - H226	
<b>SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM.; LOW BOILING POINT NAPHTHA</b>	<b>2&lt;3%</b>
CAS number: 64742-95-6	
<b>Classification</b> Flam. Liq. 3 - H226 STOT SE 3 - H335, H336 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411	
<b>1-METHOXY-2-PROPANOL</b>	<b>0.5&lt;0.7%</b>
CAS number: 107-98-2	
Substance with National workplace exposure limits.	
<b>Classification</b> Flam. Liq. 3 - H226 STOT SE 3 - H336	

The full text for all hazard statements is displayed in Section 16.

#### **SECTION 4: First aid measures**

##### **Description of first aid measures**

###### **General information**

Keep affected person away from heat, sparks and flames.

###### **Inhalation**

Move affected person to fresh air at once. Get medical attention if any discomfort continues. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. If breathing stops, provide artificial respiration. Keep affected person warm and at rest. Get medical attention immediately.

## (Aerosol) Silver King

<b>Ingestion</b>	Remove affected person from source of contamination. Rinse mouth thoroughly with water. DO NOT induce vomiting. Get medical attention immediately.
<b>Skin Contact</b>	Remove affected person from source of contamination. Wash skin thoroughly with soap and water. Get medical attention if any discomfort continues.
<b>Eye contact</b>	Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

### Most important symptoms and effects, both acute and delayed

<b>General information</b>	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
<b>Inhalation</b>	In case of overexposure, organic solvents may depress the central nervous system causing dizziness and intoxication, and at very high concentrations unconsciousness and death.
<b>Ingestion</b>	May cause discomfort if swallowed. Dizziness. Nausea, vomiting. Fumes from the stomach contents may be inhaled, resulting in the same symptoms as inhalation.
<b>Skin contact</b>	Prolonged contact may cause redness, irritation and dry skin.
<b>Eye contact</b>	May cause temporary eye irritation. Prolonged contact may cause redness and/or tearing.

### Indication of any immediate medical attention and special treatment needed

<b>Notes for the doctor</b>	No specific recommendations. If in doubt, get medical attention promptly.
-----------------------------	---

## SECTION 5: Firefighting measures

### Extinguishing media

<b>Suitable extinguishing media</b>	Extinguish with the following media: Powder. Alcohol-resistant foam. Carbon dioxide or dry powder. Dry chemicals, sand, dolomite etc. Cool aerosol containers exposed to heat with water spray and remove container, if no risk is involved.
-------------------------------------	--

### Special hazards arising from the substance or mixture

<b>Specific hazards</b>	Containers can burst violently or explode when heated, due to excessive pressure build-up. Fire creates: Carbon dioxide (CO <sub>2</sub> ). Carbon monoxide (CO). Nitrous gases (NO <sub>x</sub> ). Containers can burst violently or explode when heated, due to excessive pressure build-up. The product is highly flammable.
<b>Hazardous combustion products</b>	Oxides of carbon. Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.
<b>Advice for firefighters</b>	
<b>Protective actions during firefighting</b>	Ventilate closed spaces before entering them. Move containers from fire area if it can be done without risk. Use water to keep fire exposed containers cool and disperse vapours. Do not scatter spilled material with more water than needed to fight the fire. Risk of re-ignition after fire has been extinguished. Control run-off water by containing and keeping it out of sewers and watercourses. Containers close to fire should be removed or cooled with water. Be aware of danger of explosion. Fight advanced or massive fires from safe distance or protected location.
<b>Special protective equipment for firefighters</b>	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

## SECTION 6: Accidental release measures

### Personal precautions, protective equipment and emergency procedures

<b>Personal precautions</b>	For personal protection, see Section 8.
-----------------------------	---

## (Aerosol) Silver King

### Environmental precautions

**Environmental precautions** Do not discharge into drains or watercourses or onto the ground. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body.

### Methods and material for containment and cleaning up

**Methods for cleaning up** Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Absorb in vermiculite, dry sand or earth and place into containers. Collect and place in suitable waste disposal containers and seal securely. Label the containers containing waste and contaminated materials and remove from the area as soon as possible.

### Reference to other sections

**Reference to other sections** See Section 11 for additional information on health hazards. For personal protection, see Section 8. For waste disposal, see Section 13.

## SECTION 7: Handling and storage, including how the chemical may be safely used

### Precautions for safe handling

**Usage precautions** Keep away from heat, sparks and open flame. Avoid spilling. Avoid contact with skin and eyes. Provide adequate ventilation. Avoid inhalation of vapours. Use approved respirator if air contamination is above an acceptable level. Read and follow manufacturer's recommendations. During application and drying, solvent vapours will be emitted. Vapours may accumulate on the floor and in low-lying areas. Eliminate all sources of ignition. Static electricity and formation of sparks must be prevented.

### Conditions for safe storage, including any incompatibilities

**Storage precautions** Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C. Keep away from heat, sparks and open flame. Pressurised container: Must not be exposed to temperatures above 50°C. Store in closed original container at temperatures between 5°C and 30°C. Keep container dry.

**Storage class** Miscellaneous hazardous material storage.

### Specific end use(s)

**Specific end use(s)** The identified uses for this product are detailed in Section 1.2.

## SECTION 8: Exposure controls and personal protection

### Control parameters

#### Occupational exposure limits

##### **ACETONE**

Long-term exposure limit (8-hour TWA): NOHSC 500 ppm 1185 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): NOHSC 1000 ppm 2375 mg/m<sup>3</sup>

##### **PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS**

Long-term exposure limit (8-hour TWA): 1000 ppm 1800 mg/m<sup>3</sup>

Carc. 1B

##### **BUTYL ACETATE -norm**

Long-term exposure limit (8-hour TWA): 150 ppm 713 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): 200 ppm 950 mg/m<sup>3</sup>

##### **METHYL ETHYL KETONE**

Long-term exposure limit (8-hour TWA): 150 ppm 445 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): 300 ppm 890 mg/m<sup>3</sup>

## (Aerosol) Silver King

### 2-METHOXY-1-METHYLETHYL ACETATE

Long-term exposure limit (8-hour TWA): NOHSC 50 ppm 274 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): NOHSC 100 ppm 548 mg/m<sup>3</sup>

### 1-METHOXY-2-PROPANOL

Long-term exposure limit (8-hour TWA): 100 ppm 369 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): 150 ppm 553 mg/m<sup>3</sup>

NOHSC = The National Occupational Health and Safety Commission.

Carc. 1B = Presumed to have carcinogenic potential for humans.

### SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM.; LOW BOILING POINT NAPHTHA (CAS: 64742-95-6)

**Ingredient comments** No exposure limits known for ingredient(s).

#### Exposure controls

##### Protective equipment



##### Appropriate engineering controls

Avoid inhalation of vapours. Observe any occupational exposure limits for the product or ingredients. No specific ventilation requirements. This product must not be handled in a confined space without adequate ventilation.

##### Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Chemical splash goggles.

##### Hand protection

Wear protective gloves. The most suitable glove should be chosen in consultation with the glove supplier/manufacture, who can provide information about the breakthrough time of the glove material. Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. Neoprene. Nitrile rubber. Polyethylene. Polyvinyl chloride (PVC). It should be noted that liquid may penetrate the gloves. Frequent changes are recommended.

##### Other skin and body protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

##### Hygiene measures

Provide eyewash station. Do not smoke in work area. When using do not eat, drink or smoke. Wash hands at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Wash promptly if skin becomes contaminated.

##### Respiratory protection

No specific recommendations. Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit. Use chemical cartridge protection with appropriate cartridge. If ventilation is inadequate, suitable respiratory protection must be worn. Wear a respirator fitted with the following cartridge: Combination filter, type A2/P3.

## SECTION 9: Physical and chemical properties

### Information on basic physical and chemical properties

<b>Appearance</b>	Aerosol. Liquid.
<b>Colour</b>	Silver.
<b>Odour</b>	Acetone. Ketonic.
<b>Odour threshold</b>	Not available.

**(Aerosol) Silver King**

<b>pH</b>	Not applicable.
<b>Melting point</b>	Not determined.
<b>Initial boiling point and range</b>	-40 ~ -2°C @ 1013 hPa
<b>Flash point</b>	-60°C CC (Closed cup).
<b>Evaporation rate</b>	Not available.
<b>Flammability Limit - Lower(%)</b>	Lower flammable/explosive limit: 1.4 % Upper flammable/explosive limit: 10.9 %
<b>Vapour pressure</b>	590 - 1760 kPa @ °C
<b>Vapour density</b>	~ 1.5 @ 15°C
<b>Relative density</b>	~ 0.510 @ 15°C
<b>Solubility Value (g/100g H<sub>2</sub>O 20°C)</b>	Soluble in the following materials: Organic solvents. Insoluble in water.
<b>Partition coefficient</b>	log Pow: 2.3 - 2.8
<b>Auto-ignition temperature</b>	365°C
<b>Decomposition Temperature</b>	Not available.
<b>Viscosity</b>	Not determined.
<b>Oxidising properties</b>	Not applicable.
<b>Comments</b>	Information declared as "Not available" or "Not applicable" is not considered to be relevant to the implementation of the proper control measures. Information given is applicable to the major ingredient.
<b>Volatile organic compound</b>	This product contains a maximum VOC content of 639 g/litre.

**SECTION 10: Stability and reactivity**

<b>Reactivity</b>	There are no known reactivity hazards associated with this product.
<b>Stability</b>	Stable at normal ambient temperatures and when used as recommended. Avoid the following conditions: Heat, sparks, flames. Shocks and physical damage.
<b>Possibility of hazardous reactions</b>	Not applicable. Will not polymerise.
<b>Conditions to avoid</b>	Avoid exposing aerosol containers to high temperatures or direct sunlight. Avoid heat, flames and other sources of ignition.
<b>Materials to avoid</b>	Strong alkalis. Strong acids. Strong oxidising agents.
<b>Hazardous decomposition products</b>	Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO <sub>2</sub> ). Nitrous gases (NO <sub>x</sub> ).

**SECTION 11: Toxicological information****Information on toxicological effects**

<b>Other health effects</b>	There is no evidence that the product can cause cancer.
<b><u>Skin corrosion/irritation</u></b>	
<b>Human skin model test</b>	Scientifically unjustified.

**(Aerosol) Silver King**

<b>Extreme pH</b>	Scientifically unjustified.
<b>General information</b>	Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.
<b>Inhalation</b>	Vapours may cause headache, fatigue, dizziness and nausea. Vapour may affect central nervous system. Symptoms following overexposure may include the following: Headache. Nausea, vomiting. Intoxication. May cause discomfort. Gas or vapour in high concentrations may irritate the respiratory system. Symptoms following overexposure may include the following: Headache. Fatigue. Nausea, vomiting. Vapour may irritate respiratory system/lungs.
<b>Ingestion</b>	May cause stomach pain or vomiting. Gastrointestinal symptoms, including upset stomach. May cause discomfort if swallowed. No harmful effects expected from quantities likely to be ingested by accident.
<b>Skin Contact</b>	May cause defatting of the skin but is not an irritant.
<b>Eye contact</b>	Vapour or spray in the eyes may cause irritation and smarting.
<b>Acute and chronic health hazards</b>	Because of the product's quantity and composition, the health hazard is regarded as low.
<b>Route of entry</b>	Inhalation Ingestion. Skin and/or eye contact
<b>Medical Symptoms</b>	No specific symptoms noted, but this chemical may still have adverse health impact, either in general or on certain individuals.
<b>Medical considerations</b>	Skin disorders and allergies.

**Toxicological information on ingredients.****BUTYL ACETATE -norm**

**Other health effects**                      There is no evidence that the product can cause cancer.

**SECTION 12: Ecological Information**

**Ecotoxicity**                                      The product components are not classified as environmentally hazardous. However, large or frequent spills may have hazardous effects on the environment.

**Ecological information on ingredients.****BUTYL ACETATE -norm**

**Ecotoxicity**                                      The product components are not classified as environmentally hazardous. However, large or frequent spills may have hazardous effects on the environment.

**Acute toxicity - fish**                              Not determined.

**Acute toxicity - aquatic invertebrates**                              Not determined.

**Acute toxicity - aquatic plants**                              Not determined.

**Acute toxicity - microorganisms**                              Not determined.

**Acute toxicity - terrestrial**                              Not determined.

**Persistence and degradability**

**Persistence and degradability**                              Volatile substances are degraded in the atmosphere within a few days.

**(Aerosol) Silver King****Ecological information on ingredients.****BUTYL ACETATE -norm****Persistence and degradability**

Volatile substances are degraded in the atmosphere within a few days.

**Bioaccumulative potential****Bioaccumulative Potential**

Bioaccumulation is unlikely to be significant because of the low water-solubility of this product.

**Partition coefficient**

log Pow: 2.3 - 2.8

**Ecological information on ingredients.****BUTYL ACETATE -norm****Bioaccumulative Potential**

Bioaccumulation is unlikely to be significant because of the low water-solubility of this product.

**Mobility in soil****Mobility**

The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces. The product is insoluble in water.

**Ecological information on ingredients.****BUTYL ACETATE -norm****Mobility**

The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces.

**Results of PBT and vPvB assessment****Results of PBT and vPvB assessment**

This product does not contain any substances classified as PBT or vPvB.

**Other adverse effects****Other adverse effects**

Not applicable.

**SECTION 13: Disposal considerations****Waste treatment methods****General information**

Do not puncture or incinerate, even when empty. Empty aerosols should be recycled where facilities exist. Full or part full aerosols should be disposed of as hazardous waste in accordance with local authority requirements.

**Disposal methods**

Empty containers must not be punctured or incinerated because of the risk of an explosion. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Avoid the spillage or runoff entering drains, sewers or watercourses. Packaging: Reuse or recycle products wherever possible.

**SECTION 14: Transport information****UN number****UN No. (ADG)**

1950

**UN No. (IMDG)**

1950

**UN No. (ICAO)**

1950

**UN proper shipping name**

**(Aerosol) Silver King****Proper shipping name (ADG)** AEROSOLS**Proper shipping name (IMDG)** AEROSOLS**Proper shipping name (ICAO)** AEROSOLS**Transport hazard class(es)****ADG class** 2.1**ADG label** 2.1**IMDG class** 2.1**ICAO class/division** 2.1**Transport labels****Packing group**

Not applicable.

**Environmental hazards****Environmentally hazardous substance/marine pollutant**

No.

**Special precautions for user****EmS** F-D, S-U**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** Not applicable.**SECTION 15: Regulatory information****Safety, health and environmental regulations/legislation specific for the substance or mixture****Schedule (SUSMP)** Schedule 5. Caution.**Inventories****Australia - AICS**

All the ingredients are listed or exempt.

**SECTION 16: Any other relevant information****General information** This product has been manufactured under ISO 9001 and ISO 14001 Quality and Environmental Management Systems.**Revision comments** NOTE: Lines within the margin indicate significant changes from the previous revision.**Issued by** Prepared by Autosmart International Ltd, Lynn Lane, Shenstone, Lichfield, Staffordshire, WS14 0DH, Great Britain.  
www.autosmartinternational.com  
rbutler@autosmart.co.uk  
Tel +44 (0)1543 481616**Revision date** 21/06/2016

## (Aerosol) Silver King

<b>Revision</b>	8
<b>Supersedes date</b>	24/09/2015
<b>SDS No.</b>	10539
<b>SDS status</b>	Approved.
<b>Hazard statements in full</b>	H220 Extremely flammable gas. H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour. H229 Pressurised container: may burst if heated H280 Contains gas under pressure; may explode if heated. H304 May be fatal if swallowed and enters airways. H319 Causes serious eye irritation. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.