



## SAFETY DATA SHEET (Aerosol) White Gloss

According to Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice, February 2016

### SECTION 1: Identification: Product identifier and chemical identity

#### Product identifier

**Product name** (Aerosol) White Gloss

#### Relevant identified uses of the substance or mixture and uses advised against

**Application** Car maintenance product. Paint.

**Uses advised against** For professional use only. This product is not recommended for any industrial, professional or consumer use other than the Identified uses above.

#### Details of the supplier of the safety data sheet

**Supplier** Autosmart Australia  
11 Darrambal Close  
Rathmines  
NSW 2283  
Australia  
www.autosmartaustralia.com.au  
Tel: 02 49 75 14 88 (Mon to Fri, 08:00 - 16:00 AEST) (General Information. Transport Information. Mild Medical Information)  
autosmart@autosmartaustralia.com.au

**Contact Person** Mr. Russell Butler

**Manufacturer** Autosmart International Ltd..  
Lynn Lane  
Shenstone, nr Lichfield  
Staffordshire WS14 0DH  
Great Britain  
www.autosmartinternational.com  
Tel: +44 (0) 1543 481616 (09:00 - 17:00)  
Fax: +44 (0) 1543 481549 (09:00 - 17:00)  
info@autosmartinternational.com

#### Emergency telephone number

**Emergency telephone** Emergency No: +44 7808 971321 (24hrs) (Autosmart International, UK)  
General Information. Transport Information. Mild medical Information:-  
Tel: 02 49 75 14 88 (Mon to Fri, 08:00 - 16:00 AEST)

**National emergency telephone number** Poison Information Hotline: 13 11 26

### SECTION 2: Hazard(s) identification

#### Classification of the substance or mixture

**Physical hazards** Aerosol 1 - H222, H229 Press. Gas, Compressed - H280


**Health hazards** Eye Irrit. 2A - H319 STOT SE 3 - H336 STOT RE 1 - H372

**(Aerosol) White Gloss**

**Environmental hazards** Aquatic Chronic 3 - H412

**Human health** Extensive use of the product in areas with inadequate ventilation may result in the accumulation of hazardous vapour concentrations. May cause discomfort. Symptoms following overexposure may include the following: Headache. Dizziness. Nausea, vomiting. Irritation of nose, throat and airway.

**Physicochemical** Aerosol containers can explode when heated, due to excessive pressure build-up. The product is extremely flammable. When sprayed on a naked flame or any incandescent material the aerosol vapours can be ignited.

**Label elements****Hazard pictograms****Signal word**

DANGER

**Hazard statements**

H222 Extremely flammable aerosol.  
 H229 Pressurised container: may burst if heated.  
 H280 Contains gas under pressure; may explode if heated.  
 H319 Causes serious eye irritation.  
 H336 May cause drowsiness or dizziness.  
 H372 Causes damage to organs through prolonged or repeated exposure.  
 H412 Harmful to aquatic life with long lasting effects.

**Precautionary statements**

P210 Keep away from heat/ sparks/ open flames/ hot surfaces. - No smoking.  
 P211 Do not spray on an open flame or other ignition source.  
 P251 Pressurized container: Do not pierce or burn, even after use.  
 P271 Use only outdoors or in a well-ventilated area.  
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.  
 P501 Dispose of contents/ container in accordance with national regulations.  
 P102 Keep out of reach of children.  
 P260 Do not breathe vapour/ spray.

**Supplemental label information**

AUH066 Repeated exposure may cause skin dryness or cracking.  
 For professional users only.

**Contains**

ACETONE, Naphtha (petroleum), hydrodesulfurized heavy

**Other hazards**

This product does not contain any substances classified as PBT (persistent, bioaccumulative and toxic) or vPvB (very persistent and very bioaccumulative).

**SECTION 3: Composition and information on ingredients****Mixtures**

**(Aerosol) White Gloss**

<p><b>ACETONE</b> <span style="float: right;"><b>30&lt;60%</b></span></p> <p>CAS number: 67-64-1</p> <p>Substance with a Community workplace exposure limit.</p>
<p><b>Classification</b></p> <p>Flam. Liq. 2 - H225</p> <p>Eye Irrit. 2A - H319</p> <p>STOT SE 3 - H336</p>
<p><b>PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS</b> <span style="float: right;"><b>20&lt;30%</b></span></p> <p>CAS number: 68476-85-7</p> <p>Substance with a Community workplace exposure limit.</p>
<p><b>Classification</b></p> <p>Flam. Gas 1 - H220</p> <p>Press. Gas, Liquefied - H280</p>
<p><b>Naphtha (petroleum), hydrodesulfurized heavy</b> <span style="float: right;"><b>20&lt;30%</b></span></p> <p>CAS number: 64742-82-1</p>
<p><b>Classification</b></p> <p>Flam. Liq. 3 - H226</p> <p>STOT SE 3 - H336</p> <p>Asp. Tox. 1 - H304</p> <p>Aquatic Chronic 2 - H411</p>
<p><b>XYLENE</b> <span style="float: right;"><b>3&lt;5%</b></span></p> <p>CAS number: 1330-20-7</p> <p>Substance with a Community workplace exposure limit.</p>
<p><b>Classification</b></p> <p>Flam. Liq. 3 - H226</p> <p>Acute Tox. 4 - H312</p> <p>Acute Tox. 4 - H332</p> <p>Skin Irrit. 2 - H315</p>
<p><b>ETHYLBENZENE</b> <span style="float: right;"><b>0.7&lt;1.0%</b></span></p> <p>CAS number: 100-41-4</p> <p>Substance with a Community workplace exposure limit.</p>
<p><b>Classification</b></p> <p>Flam. Liq. 2 - H225</p> <p>Acute Tox. 4 - H332</p>

**(Aerosol) White Gloss**

<b>Cobalt Carboxylate</b>	<b>0.7&lt;1.0%</b>
CAS number: 13586-82-8	
<b>Classification</b>	
Acute Tox. 4 - H302	
Skin Irrit. 2 - H315	
Skin Sens. 1 - H317	
Aquatic Chronic 2 - H411	
<b>ETHYL METHYL KETOXIME</b>	<b>0.7&lt;1.0%</b>
CAS number: 96-29-7	
<b>Classification</b>	
Acute Tox. 4 - H312	
Eye Dam. 1 - H318	
Skin Sens. 1 - H317	
Carc. 2 - H351	
<b>Naphtha (petroleum), hydrotreated heavy</b>	<b>0.7&lt;1.0%</b>
CAS number: 64742-48-9	
<b>Classification</b>	
Flam. Liq. 3 - H226	
STOT SE 3 - H336	
Asp. Tox. 1 - H304	

The full text for all hazard statements is displayed in Section 16.

#### **SECTION 4: First aid measures**

##### **Description of first aid measures**

<b>General information</b>	Get medical attention immediately. Show this Safety Data Sheet to the medical personnel.
<b>Inhalation</b>	Remove affected person from source of contamination. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Maintain an open airway. Loosen tight clothing such as collar, tie or belt. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Place unconscious person on their side in the recovery position and ensure breathing can take place.
<b>Ingestion</b>	Rinse mouth thoroughly with water. Remove any dentures. Give a few small glasses of water or milk to drink. Stop if the affected person feels sick as vomiting may be dangerous. Do not induce vomiting unless under the direction of medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Place unconscious person on their side in the recovery position and ensure breathing can take place. Maintain an open airway. Loosen tight clothing such as collar, tie or belt.
<b>Skin Contact</b>	Rinse with water.
<b>Eye contact</b>	Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 10 minutes.

## (Aerosol) White Gloss

**Protection of first aiders** First aid personnel should wear appropriate protective equipment during any rescue. Wash contaminated clothing thoroughly with water before removing it from the affected person, or wear gloves. It may be dangerous for first aid personnel to carry out mouth-to-mouth resuscitation.

### Most important symptoms and effects, both acute and delayed

**General information** See Section 11 for additional information on health hazards. The severity of the symptoms described will vary dependent on the concentration and the length of exposure.

**Inhalation** A single exposure may cause the following adverse effects: Headache. Nausea, vomiting. Central nervous system depression. Drowsiness, dizziness, disorientation, vertigo. Narcotic effect. During application and drying, solvent vapours will be emitted. Vapours in high concentrations are narcotic.

**Ingestion** Due to the physical nature of this product, it is unlikely that ingestion will occur.

**Skin contact** Repeated exposure may cause skin dryness or cracking. Discoloration of the skin.

**Eye contact** Irritating to eyes.

### Indication of any immediate medical attention and special treatment needed

**Notes for the doctor** Treat symptomatically.

## SECTION 5: Firefighting measures

### Extinguishing media

**Suitable extinguishing media** The product is flammable. Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire-extinguishing media suitable for the surrounding fire.

**Unsuitable extinguishing media** Do not use water jet as an extinguisher, as this will spread the fire.

### Special hazards arising from the substance or mixture

**Specific hazards** Containers can burst violently or explode when heated, due to excessive pressure build-up. If aerosol cans are ruptured, care should be taken due to the rapid escape of the pressurised contents and propellant.

**Hazardous combustion products** Hydrocarbons. Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>).

### Advice for firefighters

**Protective actions during firefighting** Avoid breathing fire gases or vapours. Evacuate area. Keep upwind to avoid inhalation of gases, vapours, fumes and smoke. Ventilate closed spaces before entering them. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapours and protect men stopping the leak. Avoid discharge to the aquatic environment. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.

**Special protective equipment for firefighters** Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing conforming to Australia/New Zealand Standards AS/NZS 4967 (for clothing) AS/NZS 1801 (for helmets), AS/NZS 4821 (for protective boots), AS/NZS 1801 (for protective gloves) will provide a basic level of protection for chemical incidents.

**Hazchem Code** 2(Y)

## SECTION 6: Accidental release measures

### Personal precautions, protective equipment and emergency procedures

## (Aerosol) White Gloss

### **Personal precautions**

No action shall be taken without appropriate training or involving any personal risk. Keep unnecessary and unprotected personnel away from the spillage. Wear protective clothing as described in Section 8 of this safety data sheet. Follow precautions for safe handling described in this safety data sheet. Wash thoroughly after dealing with a spillage. Ensure procedures and training for emergency decontamination and disposal are in place. Do not touch or walk into spilled material. Evacuate area. Risk of explosion. Provide adequate ventilation. No smoking, sparks, flames or other sources of ignition near spillage. Promptly remove any clothing that becomes contaminated. Avoid inhalation of dust and vapours. Use suitable respiratory protection if ventilation is inadequate.

### **Environmental precautions**

#### **Environmental precautions**

Avoid discharge into drains or watercourses or onto the ground. Avoid discharge to the aquatic environment. Large Spillages: Inform the relevant authorities if environmental pollution occurs (sewers, waterways, soil or air).

### **Methods and material for containment and cleaning up**

#### **Methods for cleaning up**

Wear protective clothing as described in Section 8 of this safety data sheet. Clear up spills immediately and dispose of waste safely. Eliminate all ignition sources if safe to do so. No smoking, sparks, flames or other sources of ignition near spillage. Do not allow material to enter confined spaces, due to the risk of explosion. Approach the spillage from upwind. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage. Dangerous for the environment. Do not empty into drains. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

### **Reference to other sections**

#### **Reference to other sections**

For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

## **SECTION 7: Handling and storage, including how the chemical may be safely used**

### **Precautions for safe handling**

#### **Usage precautions**

Keep out of the reach of children. Read and follow manufacturer's recommendations. Wear protective clothing as described in Section 8 of this safety data sheet. Keep away from food, drink and animal feeding stuffs. Avoid exposing aerosol containers to high temperatures or direct sunlight. The product is flammable. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid discharge to the aquatic environment. Do not handle until all safety precautions have been read and understood. Do not handle broken packages without protective equipment. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Spray will evaporate and cool rapidly and may cause frostbite or cold burns if in contact with skin. Avoid contact with eyes. Avoid inhalation of vapours and spray/mists.

#### **Advice on general occupational hygiene**

Wash promptly if skin becomes contaminated. Take off contaminated clothing and wash before reuse. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Wash at the end of each work shift and before eating, smoking and using the toilet. Change work clothing daily before leaving workplace.

### **Conditions for safe storage, including any incompatibilities**

#### **Storage precautions**

Store in accordance with local regulations. Keep away from oxidising materials, heat and flames. Keep only in the original container. Keep container tightly closed, in a cool, well ventilated place. Keep containers upright. Protect containers from damage. Protect from sunlight. Do not store near heat sources or expose to high temperatures. Do not expose to temperatures exceeding 50 °C/ 122 °F. Bund storage facilities to prevent soil and water pollution in the event of spillage. The storage area floor should be leak-tight, jointless and not absorbent.

## (Aerosol) White Gloss

**Storage class** Miscellaneous hazardous material storage.

**Specific end use(s)**

**Specific end use(s)** The identified uses for this product are detailed in Section 1.

### SECTION 8: Exposure controls and personal protection

**Control parameters**

**Occupational exposure limits**

**ACETONE**

Long-term exposure limit (8-hour TWA): NOHSC 500 ppm 1185 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): NOHSC 1000 ppm 2375 mg/m<sup>3</sup>

**PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS**

Long-term exposure limit (8-hour TWA): 1000 ppm 1800 mg/m<sup>3</sup>

**XYLENE**

Long-term exposure limit (8-hour TWA): NOHSC 80 ppm 350 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): NOHSC 150 ppm 655 mg/m<sup>3</sup>

**ETHYLBENZENE**

Long-term exposure limit (8-hour TWA): NOHSC 100 ppm 434 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): NOHSC 125 ppm 543 mg/m<sup>3</sup>

NOHSC = The National Occupational Health and Safety Commission.

**Naphtha (petroleum), hydrodesulfurized heavy (CAS: 64742-82-1)**

**Ingredient comments** No exposure limits known for ingredient(s).

**Naphtha (petroleum), hydrotreated heavy (CAS: 64742-48-9)**

**Ingredient comments** No exposure limits known for ingredient(s).

**Exposure controls**

**Protective equipment**



**Appropriate engineering controls**

Provide adequate ventilation. Personal, workplace environment or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Use process enclosures, local exhaust ventilation or other engineering controls as the primary means to minimise worker exposure. Personal protective equipment should only be used if worker exposure cannot be controlled adequately by the engineering control measures. Ensure control measures are regularly inspected and maintained. Ensure operatives are trained to minimise exposure.

**Eye/face protection**

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Personal protective equipment for eye and face protection should comply with Australia/New Zealand Standard AS/NZS 1337. Wear tight-fitting, chemical splash goggles or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

## (Aerosol) White Gloss

### Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. The breakthrough time for any glove material may be different for different glove manufacturers. To protect hands from chemicals, gloves should comply with Australia/New Zealand Standard AS/NZS 2161. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. Frequent changes are recommended. The choice of protective gloves depends upon the chemicals being handled, and the conditions of work and use. When used with mixtures, the protection time of gloves cannot be accurately estimated. Gloves made from the following material may provide suitable chemical protection: Nitrile rubber. Thickness: >0.2mm The selected gloves should have a breakthrough time of at least 0.5 hours. Glove thickness is not necessarily a good measure of glove resistance as the permeation rate will depend on the exact glove composition. Repeated exposure to chemicals will degrade the ability of the glove to provide resistance to chemicals. Specific work environments and material handling practices may vary, therefore safety procedures should be developed for each intended application. Use thin cotton gloves inside natural rubber gloves if there is an allergy risk to natural rubber.

### Other skin and body protection

Appropriate footwear and additional protective clothing complying with an approved standard should be worn if a risk assessment indicates skin contamination is possible.

### Hygiene measures

Provide eyewash station and safety shower. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Clean equipment and the work area every day. Good personal hygiene procedures should be implemented. Wash at the end of each work shift and before eating, smoking and using the toilet. When using do not eat, drink or smoke. Preventive industrial medical examinations should be carried out. Warn cleaning personnel of any hazardous properties of the product.

### Respiratory protection

Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible. Ensure all respiratory protective equipment is suitable for its intended use and complies with Australia/New Zealand Standard AS/NZS 1716. Check that the respirator fits tightly and the filter is changed regularly. Gas and combination filter cartridges should comply with Australia/New Zealand Standard AS/NZS 1716. Full face mask respirators with replaceable filter cartridges should comply with Australia/New Zealand Standard AS/NZS 1716. Half mask and quarter mask respirators with replaceable filter cartridges should comply with Australia/New Zealand Standard AS/NZS 1716.

### Environmental exposure controls

Keep container tightly sealed when not in use. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## SECTION 9: Physical and chemical properties

### Information on basic physical and chemical properties

Appearance	Aerosol. Liquid.
Colour	White.
Odour	Organic solvents.
Odour threshold	Not available.
pH	Not applicable.
Melting point	Not determined.
Initial boiling point and range	-40 ~ -2°C @ 1013 hPa



**(Aerosol) White Gloss**

<b>Flash point</b>	-60°C Closed cup.
<b>Evaporation rate</b>	Not available.
<b>Flammability Limit - Lower(%)</b>	Lower flammable/explosive limit: 1.4 % Upper flammable/explosive limit: 10.9 %
<b>Vapour pressure</b>	590 - 1760 kPa @ °C
<b>Vapour density</b>	~ 1.5 @ 15°C
<b>Relative density</b>	~ 0.510 @ 15°C
<b>Solubility(ies)</b>	Soluble in the following materials: Organic solvents. Insoluble in water.
<b>Partition coefficient</b>	log Pow: 2.3 - 2.8
<b>Auto-ignition temperature</b>	365°C
<b>Decomposition Temperature</b>	Not available.
<b>Viscosity</b>	Not determined.
<b>Oxidising properties</b>	Not applicable.
<b>Comments</b>	Information declared as "Not available" or "Not applicable" is not considered to be relevant to the implementation of the proper control measures. Information given is applicable to the major ingredient.
<b>Volatile organic compound</b>	This product contains a maximum VOC content of 635 g/litre.

**SECTION 10: Stability and reactivity**

<b>Reactivity</b>	There are no known reactivity hazards associated with this product.
<b>Stability</b>	Stable at normal ambient temperatures and when used as recommended. Stable under the prescribed storage conditions.
<b>Possibility of hazardous reactions</b>	The following materials may react strongly with the product: Oxidising agents.
<b>Conditions to avoid</b>	Avoid exposing aerosol containers to high temperatures or direct sunlight. Pressurised container: may burst if heated
<b>Materials to avoid</b>	No specific material or group of materials is likely to react with the product to produce a hazardous situation.
<b>Hazardous decomposition products</b>	Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours.

**SECTION 11: Toxicological information****Information on toxicological effects****Acute toxicity - oral**

**Notes (oral LD<sub>50</sub>)** Based on available data the classification criteria are not met.

**Acute toxicity - dermal**

**Notes (dermal LD<sub>50</sub>)** Based on available data the classification criteria are not met.

**ATE dermal (mg/kg)** 22,448.98

**Acute toxicity - inhalation**

**Notes (inhalation LC<sub>50</sub>)** Based on available data the classification criteria are not met.

**(Aerosol) White Gloss**

<b>ATE inhalation (dusts/mists mg/l)</b>	30.61
<b><u>Skin corrosion/irritation</u></b>	
<b>Animal data</b>	Repeated exposure may cause skin dryness or cracking.
<b><u>Serious eye damage/irritation</u></b>	
<b>Serious eye damage/irritation</b>	Causes serious eye irritation.
<b><u>Respiratory sensitisation</u></b>	
<b>Respiratory sensitisation</b>	Based on available data the classification criteria are not met.
<b><u>Skin sensitisation</u></b>	
<b>Skin sensitisation</b>	Based on available data the classification criteria are not met.
<b><u>Germ cell mutagenicity</u></b>	
<b>Genotoxicity - in vitro</b>	Based on available data the classification criteria are not met.
<b><u>Carcinogenicity</u></b>	
<b>Carcinogenicity</b>	Based on available data the classification criteria are not met.
<b>IARC carcinogenicity</b>	Contains a substance which may be potentially carcinogenic. IARC Group 3 Not classifiable as to its carcinogenicity to humans.
<b><u>Reproductive toxicity</u></b>	
<b>Reproductive toxicity - fertility</b>	Based on available data the classification criteria are not met.
<b>Reproductive toxicity - development</b>	Based on available data the classification criteria are not met.
<b><u>Specific target organ toxicity - single exposure</u></b>	
<b>STOT - single exposure</b>	STOT SE 3 - H336 May cause drowsiness or dizziness.
<b>Target organs</b>	Central nervous system
<b><u>Specific target organ toxicity - repeated exposure</u></b>	
<b>STOT - repeated exposure</b>	STOT RE 1 - H372
<b><u>Aspiration hazard</u></b>	
<b>Aspiration hazard</b>	Based on available data the classification criteria are not met.
<b>General information</b>	
	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
<b>Inhalation</b>	
	A single exposure may cause the following adverse effects: Headache. Nausea, vomiting. Central nervous system depression. Drowsiness, dizziness, disorientation, vertigo. Narcotic effect. During application and drying, solvent vapours will be emitted. Vapours in high concentrations are narcotic.
<b>Ingestion</b>	
	Due to the physical nature of this product, it is unlikely that ingestion will occur.
<b>Skin Contact</b>	
	Repeated exposure may cause skin dryness or cracking. Discoloration of the skin.
<b>Eye contact</b>	
	Irritating to eyes.
<b>Acute and chronic health hazards</b>	
	Because of the product's quantity and composition, the health hazard is regarded as low.
<b>Route of exposure</b>	
	Ingestion Inhalation Skin and/or eye contact
<b>Target Organs</b>	
	Central nervous system

**(Aerosol) White Gloss****Toxicological information on ingredients.****ACETONE****Acute toxicity - oral**

**Acute toxicity oral (LD<sub>50</sub> mg/kg)** 5,800.0

**Species** Rat

**Acute toxicity - dermal**

**Acute toxicity dermal (LD<sub>50</sub> mg/kg)** 20,000.0

**Species** Rabbit

**PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS****Skin corrosion/irritation**

**Human skin model test** Scientifically unjustified.

**Extreme pH** Scientifically unjustified.

**Germ cell mutagenicity**

**Genotoxicity - in vivo** This substance has no evidence of mutagenic properties.

**Reproductive toxicity**

**Reproductive toxicity - fertility** Does not contain any substances known to be toxic to reproduction.

**Specific target organ toxicity - single exposure**

**STOT - single exposure** Not classified as a specific target organ toxicant after a single exposure.

**Target organs** Central nervous system

**Specific target organ toxicity - repeated exposure**

**STOT - repeated exposure** Not classified as a specific target organ toxicant after repeated exposure.

**Target organs** Central nervous system

**Aspiration hazard**

**Aspiration hazard** Based on available data the classification criteria are not met.

**General information**

Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.

**Inhalation**

Vapours may cause headache, fatigue, dizziness and nausea. Vapour may affect central nervous system. Symptoms following overexposure may include the following: Headache. Nausea, vomiting. Intoxication. May cause discomfort. Vapour may irritate respiratory system/lungs.

**Ingestion**

May cause stomach pain or vomiting. Gastrointestinal symptoms, including upset stomach. May cause discomfort if swallowed. No harmful effects expected from quantities likely to be ingested by accident.

**Skin Contact**

May cause defatting of the skin but is not an irritant.

**Eye contact**

Vapour or spray in the eyes may cause irritation and smarting.

**(Aerosol) White Gloss**

**Acute and chronic health hazards** Because of the product's quantity and composition, the health hazard is regarded as low.

**Route of exposure** Inhalation Ingestion. Skin and/or eye contact

**Naphtha (petroleum), hydrodesulfurized heavy**

**Other health effects** There is no evidence that the product can cause cancer.

**XYLENE****Acute toxicity - oral**

**Acute toxicity oral (LD<sub>50</sub> mg/kg)** 4,300.0

**Species** Rat

**Notes (oral LD<sub>50</sub>)** Based on available data the classification criteria are not met.

**Acute toxicity - dermal**

**Acute toxicity dermal (LD<sub>50</sub> mg/kg)** 2,000.0

**Species** Rabbit

**Notes (dermal LD<sub>50</sub>)** Acute Tox. 4 - H312 Harmful in contact with skin.

**ATE dermal (mg/kg)** 1,100.0

**Acute toxicity - inhalation**

**Notes (inhalation LC<sub>50</sub>)** Acute Tox. 4 - H332 Harmful if inhaled.

**ATE inhalation (dusts/mists mg/l)** 1.5

**Skin corrosion/irritation**

**Animal data** Irritating.

**Serious eye damage/irritation**

**Serious eye damage/irritation** Based on available data the classification criteria are not met.

**Respiratory sensitisation**

**Respiratory sensitisation** Based on available data the classification criteria are not met.

**Skin sensitisation**

**Skin sensitisation** Based on available data the classification criteria are not met.

**Germ cell mutagenicity**

**Genotoxicity - in vitro** Based on available data the classification criteria are not met.

**Genotoxicity - in vivo** Not available.

**Carcinogenicity**

**Carcinogenicity** Based on available data the classification criteria are not met.

**IARC carcinogenicity** IARC Group 3 Not classifiable as to its carcinogenicity to humans.

**Reproductive toxicity**

**(Aerosol) White Gloss**

<b>Reproductive toxicity - fertility</b>	Based on available data the classification criteria are not met.
<b>Reproductive toxicity - development</b>	Based on available data the classification criteria are not met.
<b><u>Specific target organ toxicity - single exposure</u></b>	
<b>STOT - single exposure</b>	Not classified as a specific target organ toxicant after a single exposure.
<b><u>Specific target organ toxicity - repeated exposure</u></b>	
<b>STOT - repeated exposure</b>	Not classified as a specific target organ toxicant after repeated exposure.
<b>Target organs</b>	Respiratory system, lungs
<b><u>Aspiration hazard</u></b>	
<b>Aspiration hazard</b>	Based on available data the classification criteria are not met.
<b><u>General information</u></b>	
<b>General information</b>	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
<b>Inhalation</b>	A single exposure may cause the following adverse effects: Headache. Exhaustion and weakness.
<b>Ingestion</b>	May cause irritation.
<b>Skin Contact</b>	Redness. Irritating to skin.
<b>Eye contact</b>	No specific symptoms known.
<b>Route of exposure</b>	Ingestion Inhalation Skin and/or eye contact
<b>Target Organs</b>	No specific target organs known.

**Cobalt Carboxylate****Acute toxicity - oral**

**ATE oral (mg/kg)** 500.0

**Naphtha (petroleum), hydrotreated heavy****Acute toxicity - oral**

**Acute toxicity oral (LD<sub>50</sub> mg/kg)** 5,000.0

**Species** Rat

**Acute toxicity - dermal**

**Acute toxicity dermal (LD<sub>50</sub> mg/kg)** 5,000.0

**Species** Rabbit

**SECTION 12: Ecological information**

**Ecotoxicity** No negative effects on the aquatic environment are known. The product components are not classified as environmentally hazardous. However, large or frequent spills may have hazardous effects on the environment.

**Ecological information on ingredients.**

**(Aerosol) White Gloss****ACETONE**

**Ecotoxicity** The product components are not classified as environmentally hazardous. However, large or frequent spills may have hazardous effects on the environment.

**PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS**

**Ecotoxicity** The product components are not classified as environmentally hazardous. However, large or frequent spills may have hazardous effects on the environment.

**Naphtha (petroleum), hydrodesulfurized heavy**

**Ecotoxicity** The product contains a substance which is toxic to aquatic organisms and which may cause long-term adverse effects in the aquatic environment.

**XYLENE**

**Ecotoxicity** The product components are not classified as environmentally hazardous. However, large or frequent spills may have hazardous effects on the environment.

**Naphtha (petroleum), hydrotreated heavy**

**Ecotoxicity** The product is not expected to be toxic to aquatic organisms.

**Toxicity** Aquatic Chronic 3 - H412 Harmful to aquatic life with long lasting effects.

**Acute aquatic toxicity**

**Acute toxicity - fish** Not determined.

**Acute toxicity - aquatic invertebrates** Not determined.

**Acute toxicity - aquatic plants** Not determined.

**Acute toxicity - microorganisms** Not determined.

**Acute toxicity - terrestrial** Not determined.

**Ecological information on ingredients.****PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS****Acute aquatic toxicity**

**Acute toxicity - fish** Not determined.

**Acute toxicity - aquatic invertebrates** Not determined.

**Acute toxicity - aquatic plants** Not determined.

**Acute toxicity - microorganisms** Not determined.

**Acute toxicity - terrestrial** Not determined.

**XYLENE****Acute aquatic toxicity**

**(Aerosol) White Gloss**

**Acute toxicity - fish** LC50, 96 hours: 4.2 mg/l, Oncorhynchus mykiss (Rainbow trout)

**Acute toxicity - aquatic invertebrates** EC<sub>50</sub>, 48 hours: > 2.93 mg/l, Daphnia magna

**Chronic aquatic toxicity**

**Chronic toxicity - fish early life stage** NOEC, : 3.3 mg/l, Menidia peninsulae (Tidewater silverside)

**Chronic toxicity - aquatic invertebrates** NOEC, : 6.8 mg/l, Daphnia magna

**Persistence and degradability**

**Persistence and degradability** The degradability of the product is not known.

**Ecological information on ingredients.****ACETONE**

**Persistence and degradability**

Volatile substances are degraded in the atmosphere within a few days.

**PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS**

**Persistence and degradability**

Volatile substances are degraded in the atmosphere within a few days.

**Naphtha (petroleum), hydrodesulfurized heavy**

**Persistence and degradability**

Volatile substances are degraded in the atmosphere within a few days.

**XYLENE**

**Persistence and degradability**

Volatile substances are degraded in the atmosphere within a few days.

**Naphtha (petroleum), hydrotreated heavy**

**Persistence and degradability**

Volatile substances are degraded in the atmosphere within a few days.

**Bioaccumulative potential**

**Bioaccumulative Potential** No data available on bioaccumulation.

**Partition coefficient** log Pow: 2.3 - 2.8

**Ecological information on ingredients.****ACETONE**

**Bioaccumulative Potential** The product does not contain any substances expected to be bioaccumulating.

**PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS**

**Bioaccumulative Potential** Bioaccumulation is unlikely to be significant because of the low water-solubility of this product.

**(Aerosol) White Gloss**

**Partition coefficient** log Pow: ~ 2.3 - 2.8

**Naphtha (petroleum), hydrodesulfurized heavy**

**Bioaccumulative Potential** Bioaccumulation is unlikely to be significant because of the low water-solubility of this product.

**XYLENE**

**Bioaccumulative Potential** The product contains potentially bioaccumulating substances.

**Partition coefficient** log Pow: ~ 3.12

**Naphtha (petroleum), hydrotreated heavy**

**Bioaccumulative Potential** The product does not contain any substances expected to be bioaccumulating.

**Mobility in soil**

**Mobility** The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces.

**Ecological information on ingredients.****ACETONE**

**Mobility** The product contains volatile organic compounds (VOCs) which have a photochemical ozone creation potential.

**PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS**

**Mobility** The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces.

**Naphtha (petroleum), hydrodesulfurized heavy**

**Mobility** The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces.

**XYLENE**

**Mobility** The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces.

**Naphtha (petroleum), hydrotreated heavy**

**Mobility** The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces.

**Other adverse effects**

**Other adverse effects** None known.

**Ecological information on ingredients.****PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS**

**Other adverse effects** None known.

**SECTION 13: Disposal considerations**



## (Aerosol) White Gloss

### Waste treatment methods

#### General information

The generation of waste should be minimised or avoided wherever possible. Reuse or recycle products wherever possible. This material and its container must be disposed of in a safe way. Disposal of this product, process solutions, residues and by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements. When handling waste, the safety precautions applying to handling of the product should be considered. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out. Empty containers or liners may retain some product residues and hence be potentially hazardous.

#### Disposal methods

Dispose of surplus products and those that cannot be recycled via a licensed waste disposal contractor. Waste, residues, empty containers, discarded work clothes and contaminated cleaning materials should be collected in designated containers, labelled with their contents. Waste packaging should be collected for reuse or recycling. Incineration or landfill should only be considered when recycling is not feasible.

### SECTION 14: Transport information

#### General

For limited quantity packaging/limited load information, consult the relevant modal documentation using the data shown in this section.

#### UN number

UN No. (ADG) 1950

UN No. (IMDG) 1950

UN No. (ICAO) 1950

#### UN proper shipping name

Proper shipping name (ADG) AEROSOLS

Proper shipping name (IMDG) AEROSOLS

Proper shipping name (ICAO) AEROSOLS

#### Transport hazard class(es)

ADG class 2.1

ADG classification code 5F

ADG label 2.1

IMDG class 2.1

ICAO class/division 2.1

#### Transport labels



#### Packing group

ADG packing group None

IMDG packing group None

ICAO packing group None

#### Environmental hazards

## (Aerosol) White Gloss

### Environmentally hazardous substance/marine pollutant

No.

### Special precautions for user

Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**EmS** F-D, S-U

**Hazchem Code** 2(Y)

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** Not applicable.

### SECTION 15: Regulatory information

#### Safety, health and environmental regulations/legislation specific for the substance or mixture

**Guidance** Workplace Exposure Limits EH40.  
Safety Data Sheets for Substances and Preparations.

**Schedule (SUSMP)** Schedule 5. Caution.

### Inventories

#### **Australia - AICS**

All the ingredients are listed or exempt.

### SECTION 16: Any other relevant information

**Training advice** Read and follow manufacturer's recommendations. Only trained personnel should use this material.

**Revision comments** NOTE: Lines within the margin indicate significant changes from the previous revision. This is the first issue.

**Issued by** Prepared by Autosmart International Ltd, Lynn Lane, Shenstone, Lichfield, Staffordshire, WS14 0DH, Great Britain.  
www.autosmartinternational.com  
rbutler@autosmart.co.uk  
Tel +44 (0)1543 481616

**Revision date** 13/05/2021

**Revision** 5

**Supersedes date** 27/06/2016

**SDS No.** 11131

**SDS status** Approved.

## (Aerosol) White Gloss

### Hazard statements in full

H220 Extremely flammable gas.  
H225 Highly flammable liquid and vapour.  
H226 Flammable liquid and vapour.  
H229 Pressurised container: may burst if heated.  
H280 Contains gas under pressure; may explode if heated.  
H302 Harmful if swallowed.  
H304 May be fatal if swallowed and enters airways.  
H312 Harmful in contact with skin.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H318 Causes serious eye damage.  
H319 Causes serious eye irritation.  
H332 Harmful if inhaled.  
H336 May cause drowsiness or dizziness.  
H351 Suspected of causing cancer.  
H372 Causes damage to organs through prolonged or repeated exposure.  
H411 Toxic to aquatic life with long lasting effects.  
H412 Harmful to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.