

### SECTION 1: Product identifier

#### 1.1. GHS Product identifier

Product form : Mixture  
Trade name : (Aerosol) Zinc Galva  
Product code : 003498000007

#### 1.2. Other means of identification

Synonyms : AZGA001D

#### 1.3. Recommended use of the chemical and restrictions on use

Recommended use : Spraying paint (spray can)  
Restrictions on use : For professional use only

#### 1.4. Details of manufacturer or importer

Autosmart Australia  
11 Darrambal Close  
Rathmines NSW 2283 NSW  
Australia  
T 02 49 75 14 88 (Mon to Fri, 08:00 - 16:00 AEST)  
[autosmart@autosmartaustralia.com.au](mailto:autosmart@autosmartaustralia.com.au) - [www.autosmartaustralia.com.au](http://www.autosmartaustralia.com.au)

#### 1.5. Emergency phone number

Emergency number : NCEC - For Chemical Emergency Support ONLY (spill, leak, fire, exposure or accident),  
Call NCEC at 18000 74234 (toll free 24Hrs) - when calling please quote "AUTOSMART 29003-NCEC"  
Local number +61 2 8 014 4558  
General Information. Transport Information. Mild medical Information:-  
Tel: 02 49 75 14 88 (Mon to Fri, 08:00 - 16:00 AEST)

### SECTION 2: Hazard identification


#### 2.1. Classification of the hazardous chemical

##### Classification according to the model Work Health and Safety Regulations (WHS Regulations)

Aerosol, Category 1	H222;H229
Gases under pressure : Compressed gas	H280
Skin corrosion/irritation, Category 2	H315
Serious eye damage/eye irritation, Category 2A	H319
Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336

#### 2.2. GHS Label elements, including precautionary statements

Hazard pictograms (GHS AU) :



Signal word (GHS AU) : Danger  
Contains : n-butyl acetate (5.41 %); Acetone (25.8 %)  
Hazard statements (GHS AU) : H222 - Extremely flammable aerosol  
H229 - Pressurised container: May burst if heated  
H280 - Contains gas under pressure; may explode if heated  
H315 - Causes skin irritation

# (Aerosol) Zinc Galva

## Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

Precautionary statements (GHS AU)	: H319 - Causes serious eye irritation H336 - May cause drowsiness or dizziness P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 - Do not spray on an open flame or other ignition source. P251 - Do not pierce or burn, even after use. P261 - Avoid breathing vapours, spray. P271 - Use only outdoors or in a well-ventilated area. P280 - Wear protective gloves, eye protection. P302+P352 - IF ON SKIN: Wash with plenty of water. P332+P313 - If skin irritation occurs: Get medical advice, medical attention. P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P312 - Call a POISON CENTER, a doctor if you feel unwell. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337+P313 - If eye irritation persists: Get medical advice, medical attention. P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C, 122 °F.
Additional hazard statements (GHS AU)	: AUH066 - Repeated exposure may cause skin dryness or cracking.

### 2.3. Other hazards which do not result in classification

No additional information available

## SECTION 3: Composition and information on ingredients

Name	CAS-No.	%	Classification according to the model Work Health and Safety Regulations (WHS Regulations)
Petroleum gases, liquefied (Contains < 0.1% 1,3-butadiene)	68476-85-7	35	Flam. Gas 1A, H220 Press. Gas (Comp.), H280 Flam. Liq. 1, H224
Acetone	67-64-1	25.8	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
n-butyl acetate	123-86-4	5.41	Flam. Liq. 2, H225 STOT SE 3, H336
Aluminium powder (stabilised)	7429-90-5	2.85	Flam. Sol. 1, H228 Water-react. 2, H261 STOT RE 2, H373
1-methoxypropan-2-ol	107-98-2	2.308057315	Flam. Liq. 3, H226 STOT SE 3, H336
Ethylbenzene	100-41-4	1.725	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Inhalation:vapour), H332 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT RE 2, H373 Asp. Tox. 1, H304
Other substances (not contributing to the classification of this product)	-	26.91	-

## SECTION 4: First aid measures

### 4.1. Description of necessary first-aid measures

First-aid measures general : Call a poison center or a doctor if you feel unwell.

# (Aerosol) Zinc Galva

## Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

### 4.2. Symptoms caused by exposure

Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after inhalation	: Although no appropriate human or animal health effects data are known to exist, this material is expected to be an inhalation hazard.
Symptoms/effects after skin contact	: Irritation.
Symptoms/effects after eye contact	: Eye irritation.
Symptoms/effects after ingestion	: None under normal conditions.

### 4.3. Medical attention and special treatment

Other medical advice or treatment	: Treat symptomatically.
-----------------------------------	--------------------------

## SECTION 5: Fire-fighting measures

### 5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

### 5.2. Specific hazards arising from the chemical

Fire hazard	: Extremely flammable aerosol.
Explosion hazard	: Pressurised container: May burst if heated.
General measures	: Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material damage.

### 5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material damage.
------------------	--

#### 6.1.1. For non-emergency personnel

Protective equipment	: Wear recommended personal protective equipment.
Emergency procedures	: Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

#### 6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	: Evacuate unnecessary personnel. Stop leak if safe to do so.

### 6.2. Environmental precautions

Avoid release to the environment.

# (Aerosol) Zinc Galva

## Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

### 6.3. Methods and materials for containment and cleaning up

- For containment : Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak without risks if possible.
- Methods for cleaning up : Mechanically recover the product.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

- Additional hazards when processed : Not expected to present a significant hazard under anticipated conditions of normal use.
- Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes. Wear personal protective equipment.
- Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Keep in a cool, well-ventilated place away from heat.
- Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Store in a well-ventilated place. Keep container tightly closed.
- Packaging materials : Store always product in container of same material as original container.

## SECTION 8: Exposure controls and personal protection

### 8.1. Control parameters - exposure standards

n-butyl acetate (123-86-4)	
Australia - Occupational Exposure Limits	
Local name	n-Butyl acetate
OES TWA	713 mg/m <sup>3</sup>
	150 ppm
OES STEL	950 mg/m <sup>3</sup>
	200 ppm
Regulatory reference	Workplace exposure standards for airborne contaminants (2022)
Acetone (67-64-1)	
Australia - Occupational Exposure Limits	
Local name	Acetone
OES TWA	1185 mg/m <sup>3</sup>
	500 ppm
OES STEL	2375 mg/m <sup>3</sup>
	1000 ppm
Regulatory reference	Workplace exposure standards for airborne contaminants (2022)
1-methoxypropan-2-ol (107-98-2)	
Australia - Occupational Exposure Limits	
Local name	Propylene glycol monomethyl ether (1-Methoxypropan-2-ol)
OES TWA	369 mg/m <sup>3</sup>

# (Aerosol) Zinc Galva

## Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

1-methoxypropan-2-ol (107-98-2)	
	100 ppm
OES STEL	553 mg/m <sup>3</sup>
	150 ppm
Regulatory reference	Workplace exposure standards for airborne contaminants (2022)
Aluminium powder (stabilised) (7429-90-5)	
Australia - Occupational Exposure Limits	
Local name	Aluminium
OES TWA	10 mg/m <sup>3</sup> metal dust 5 mg/m <sup>3</sup> welding fumes (as Al) 2 mg/m <sup>3</sup> alkyls (NOC) (as Al) 5 mg/m <sup>3</sup> pyro powders (as Al) 2 mg/m <sup>3</sup> soluble salts (as Al)
Regulatory reference	Workplace exposure standards for airborne contaminants (2022)
Ethylbenzene (100-41-4)	
Australia - Occupational Exposure Limits	
Local name	Ethyl benzene
OES TWA	434 mg/m <sup>3</sup>
	100 ppm
OES STEL	543 mg/m <sup>3</sup>
	125 ppm
Regulatory reference	Workplace exposure standards for airborne contaminants (2022)
Petroleum gases, liquefied (Contains < 0.1% 1,3-butadiene) (68476-85-7)	
Australia - Occupational Exposure Limits	
Local name	LPG (liquefied petroleum gas)
OES TWA	1800 mg/m <sup>3</sup>
	1000 ppm
Remark (AU)	Carcinogenicity Category 1B - Presumed to have a carcinogenic potential for humans. The classification of a substance into this category is based largely on animal evidence where there is sufficient evidence to demonstrate carcinogenicity in animals or where there is limited evidence of carcinogenicity in humans and animals.
Regulatory reference	Workplace exposure standards for airborne contaminants (2022)

### 8.2. Monitoring methods

No additional information available

### 8.3. Engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

### 8.4. Individual protection measures, such as personal protective equipment (PPE)

Personal protective equipment : Wear recommended personal protective equipment.  
Materials for protective clothing : The following Australian and New Zealand Standards will provide general advice regarding safety clothing and equipment: Industrial Clothing: AS2919.  
Hand protection : Protective gloves. The following Australian and New Zealand Standards will provide general advice regarding safety clothing and equipment: Protective Gloves: AS 2161.

# (Aerosol) Zinc Galva

## Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

- Eye protection : Safety glasses. The following Australian and New Zealand Standards will provide general advice regarding safety clothing and equipment: Industrial Eye Protection: AS1336 and AS/NZS 1337.
- Skin and body protection : Wear suitable protective clothing
- Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment. The following Australian and New Zealand Standards will provide general advice regarding safety clothing and equipment: Respiratory equipment: AS/NZS 1715.

### Personal protective equipment symbol(s)



- Environmental exposure controls : Avoid release to the environment.

## SECTION 9: Physical and chemical properties

- Physical state : Liquid
- Appearance : Aerosol.
- Colour : Silver
- Odour : Odourless.
- Odour threshold : No data available
- pH : Not relevant - substance/mixture is non-soluble (in water).
- pH solution : No data available
- Relative evaporation rate (butylacetate=1) : No data available
- Melting point / Freezing point : Melting point: Not applicable
- Boiling point : No data available
- Flash point : < -40 °C
- Auto-ignition temperature : No data available
- Flammability : No data available
- Vapour pressure : No data available
- Relative density : No data available
- Density : No data available
- Solubility : No data available
- Partition coefficient n-octanol/water (Log Pow) : No data available
- Viscosity, kinematic : < 20.5 mm<sup>2</sup>/s
- Explosive properties : Pressurised container: May burst if heated.
- Explosive limits : No data available
- Minimum ignition energy : No data available
- VOC content : 619 g/l
- Fat solubility : No data available

## SECTION 10: Stability and reactivity

- Reactivity : Extremely flammable aerosol. Pressurised container: May burst if heated.
- Chemical stability : No additional information available
- Possibility of hazardous reactions : No additional information available
- Conditions to avoid : Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.
- Incompatible materials : No additional information available
- Hazardous decomposition products : No additional information available

## SECTION 11: Toxicological information

- Acute toxicity (oral) : Not classified
- Acute toxicity (dermal) : Not classified
- Acute toxicity (inhalation) : Not classified

### Acetone (67-64-1)

LD50 oral rat	5800 mg/kg bodyweight Animal: rat, Animal sex: female
---------------	---

# (Aerosol) Zinc Galva

## Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

<b>Acetone (67-64-1)</b>	
LC50 Inhalation - Rat	76 mg/l air Animal: rat, Animal sex: female, 95% CL: 65,2 - 88,4
<b>1-methoxypropan-2-ol (107-98-2)</b>	
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: EU Method B.3 (Acute Toxicity (Dermal))
<b>Aluminium powder (stabilised) (7429-90-5)</b>	
LD50 oral rat	> 15900 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LC50 Inhalation - Rat	> 0.888 mg/l air Animal: rat, Animal sex: male, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), Remarks on results: other:
Skin corrosion/irritation	: Causes skin irritation. pH: Not relevant - substance/mixture is non-soluble (in water).
Serious eye damage/irritation	: Causes serious eye irritation. pH: Not relevant - substance/mixture is non-soluble (in water).
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: May cause drowsiness or dizziness.
<b>n-butyl acetate (123-86-4)</b>	
STOT-single exposure	May cause drowsiness or dizziness.
<b>Acetone (67-64-1)</b>	
STOT-single exposure	May cause drowsiness or dizziness.
<b>1-methoxypropan-2-ol (107-98-2)</b>	
STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified
<b>1-methoxypropan-2-ol (107-98-2)</b>	
LOAEL (oral, rat, 90 days)	2757 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)
NOAEL (oral, rat, 90 days)	919 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)
NOAEL (dermal, rat/rabbit, 90 days)	> 1000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)
<b>Aluminium powder (stabilised) (7429-90-5)</b>	
LOAEC (inhalation, rat, dust/mist/fume, 90 days)	0.05 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)
NOAEL (subchronic, oral, animal/male, 90 days)	1034 mg/kg bodyweight Animal: dog, Animal sex: male, Guideline: OECD Guideline 409 (Repeated Dose 90-Day Oral Toxicity Study in Non-Rodents)
NOAEL (subchronic, oral, animal/female, 90 days)	1087 mg/kg bodyweight Animal: dog, Animal sex: female, Guideline: OECD Guideline 409 (Repeated Dose 90-Day Oral Toxicity Study in Non-Rodents)
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
<b>Ethylbenzene (100-41-4)</b>	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
<b>Petroleum gases, liquefied (Contains &lt; 0.1% 1,3-butadiene) (68476-85-7)</b>	
LOAEC (inhalation, rat, gas, 90 days)	12000 ppm Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test), Guideline: other:

# (Aerosol) Zinc Galva

## Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

Aspiration hazard : Not classified.

<b>(Aerosol) Zinc Galva</b>	
Vaporizer	Aerosol
Not able to form a pool	Yes
Viscosity, kinematic	< 20.5 mm <sup>2</sup> /s
<b>1-methoxypropan-2-ol (107-98-2)</b>	
Viscosity, kinematic	1.848 mm <sup>2</sup> /s
<b>Ethylbenzene (100-41-4)</b>	
Viscosity, kinematic	0.6 mm <sup>2</sup> /s Temp.: 'other:' Parameter: 'kinematic viscosity (in mm <sup>2</sup> /s)' Remarks on result: 'other:'

## SECTION 12: Ecological information

According to the National Code of Practice for the Preparation of Material Safety Data Sheets, Environmental classification information is not mandatory. Information relevant for GHS classification is available on request

### 12.1. Ecotoxicity

Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified

<b>n-butyl acetate (123-86-4)</b>	
EC50 - Other aquatic organisms [1]	32 mg/l Test organisms (species): Artemia salina
<b>Acetone (67-64-1)</b>	
LOEC (chronic)	> 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	≥ 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
<b>1-methoxypropan-2-ol (107-98-2)</b>	
EC50 - Other aquatic organisms [1]	2954 mg/l Test organisms (species): other aquatic crustacea:
<b>Petroleum gases, liquefied (Contains &lt; 0.1% 1,3-butadiene) (68476-85-7)</b>	
LC50 - Fish [1]	0.362 mg/l
EC50 - Crustacea [1]	0.018 mg/l
ErC50 algae	7.6 mg/l Source: ECOTOX
Partition coefficient n-octanol/water (Log Pow)	≤ 2.8 Source: IUCLID

### 12.2. Persistence and degradability

<b>(Aerosol) Zinc Galva</b>	
Persistence and degradability	Not rapidly degradable
<b>n-butyl acetate (123-86-4)</b>	
Persistence and degradability	Not rapidly degradable
<b>Acetone (67-64-1)</b>	
Persistence and degradability	Not rapidly degradable



# (Aerosol) Zinc Galva

## Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

1-methoxypropan-2-ol (107-98-2)	
Persistence and degradability	Not rapidly degradable
Aluminium powder (stabilised) (7429-90-5)	
Persistence and degradability	Not rapidly degradable
Ethylbenzene (100-41-4)	
Persistence and degradability	Not rapidly degradable
Petroleum gases, liquefied (Contains < 0.1% 1,3-butadiene) (68476-85-7)	
Persistence and degradability	Not rapidly degradable

### 12.3. Bioaccumulative potential

Petroleum gases, liquefied (Contains < 0.1% 1,3-butadiene) (68476-85-7)	
Partition coefficient n-octanol/water (Log Pow)	≤ 2.8 Source: IUCLID

### 12.4. Mobility in soil

Petroleum gases, liquefied (Contains < 0.1% 1,3-butadiene) (68476-85-7)	
Partition coefficient n-octanol/water (Log Pow)	≤ 2.8 Source: IUCLID

### 12.5. Other adverse effects

Ozone : Not classified  
Other adverse effects : No additional information available

(Aerosol) Zinc Galva	
Fluorinated greenhouse gases	False
n-butyl acetate (123-86-4)	
Fluorinated greenhouse gases	False
Acetone (67-64-1)	
Fluorinated greenhouse gases	False
1-methoxypropan-2-ol (107-98-2)	
Fluorinated greenhouse gases	False
Aluminium powder (stabilised) (7429-90-5)	
Fluorinated greenhouse gases	False
Ethylbenzene (100-41-4)	
Fluorinated greenhouse gases	False
Petroleum gases, liquefied (Contains < 0.1% 1,3-butadiene) (68476-85-7)	
Fluorinated greenhouse gases	False

## SECTION 13: Disposal considerations

Regional waste regulation : Disposal must be done according to official regulations.  
Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.  
Sewage disposal recommendations : Disposal must be done according to official regulations.  
Product/Packaging disposal recommendations : Disposal must be done according to official regulations.  
Additional information : Do not re-use empty containers.




# (Aerosol) Zinc Galva

## Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

### SECTION 14: Transport information

In accordance with ADG / IMDG / IATA

ADG	IMDG	IATA
<b>14.1. UN number</b>		
1950	1950	1950
<b>14.2. UN Proper Shipping Name</b>		
AEROSOLS	AEROSOLS	Aerosols, flammable
<b>Transport document description</b>		
Not applicable	UN 1950 AEROSOLS, 2.1	UN 1950 Aerosols, flammable, 2.1
<b>14.3. Transport hazard class(es)</b>		
2.1	2.1	2.1
		
<b>14.4. Packing group</b>		
Not applicable	Not applicable	Not applicable
<b>14.5. Environmental hazards</b>		
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No

### 14.6. Special precautions for user

Specific storage requirement : No data available  
Shock sensitivity : No data available

### 14.7. Additional information

Other information : No supplementary information available

#### Transport by road and rail

UN-No. (ADG) : 1950  
Special provision (ADG) : 63, 190, 277, 327, 344, 381  
Limited quantities (ADG) : 1I  
Packing instructions (ADG) : P207, LP200  
Special packing provisions (ADG) : PP87, L2

#### Transport by sea

UN-No. (IMDG) : 1950  
Special provisions (IMDG) : 63, 190, 277, 327, 344, 381, 959  
Limited quantities (IMDG) : SP277  
Excepted quantities (IMDG) : E0  
Packing instructions (IMDG) : P207, LP200  
Special packing provisions (IMDG) : PP87, L2  
EmS-No. (Fire) : F-D - FIRE SCHEDULE Delta - FLAMMABLE GASES  
EmS-No. (Spillage) : S-U - SPILLAGE SCHEDULE Uniform - GASES (FLAMMABLE, TOXIC OR CORROSIVE)  
Stowage category (IMDG) : None  
Stowage and handling (IMDG) : SW1, SW22  
Segregation (IMDG) : SG69

#### Air transport

UN-No. (IATA) : 1950  
PCA Excepted quantities (IATA) : E0  
PCA Limited quantities (IATA) : Y203  
PCA limited quantity max net quantity (IATA) : 30kgG

# (Aerosol) Zinc Galva

## Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

PCA packing instructions (IATA)	: 203
PCA max net quantity (IATA)	: 75kg
CAO packing instructions (IATA)	: 203
CAO max net quantity (IATA)	: 150kg
Special provisions (IATA)	: A145, A167, A802
ERG code (IATA)	: 10L

### 14.8. Hazchem or Emergency Action Code

Hazchem Code : Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations specific for the product in question

No additional information available

### 15.2. International agreements

No additional information available

## SECTION 16: Other information

### Classification

Aerosol 1	H222;H229
Press. Gas (Comp.)	H280
Skin Irrit. 2	H315
Eye Irrit. 2A	H319
STOT SE 3	H336

### Full text of H-statements

Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Inhalation:vapour)	Acute toxicity (inhalation:vapour) Category 4
Aerosol 1	Aerosol, Category 1
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation, Category 2A
Flam. Gas 1A	Flammable gases, Category 1A
Flam. Liq. 1	Flammable liquids, Category 1
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Flam. Sol. 1	Flammable solids, Category 1
Press. Gas (Comp.)	Gases under pressure : Compressed gas
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis
Water-react. 2	Substances and Mixtures which, in contact with water, emit flammable gases, Category 2
H220	Extremely flammable gas
H224	Extremely flammable liquid and vapour

# (Aerosol) Zinc Galva

## Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

Full text of H-statements	
H225	Highly flammable liquid and vapour
H226	Flammable liquid and vapour
H228	Flammable solid
H261	In contact with water releases flammable gases
H280	Contains gas under pressure; may explode if heated
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H319	Causes serious eye irritation
H332	Harmful if inhaled
H336	May cause drowsiness or dizziness
H373	May cause damage to organs through prolonged or repeated exposure

Safety Data Sheet (SDS), Australia

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.