

### SECTION 1: Product identifier

#### 1.1. GHS Product identifier

Product form : Mixture  
Trade name : (Aerosol) Gloss Black  
Product code : 003498000051

#### 1.2. Other means of identification

Synonyms : AGL001D

#### 1.3. Recommended use of the chemical and restrictions on use

Recommended use : Spraying paint (spray can)  
Restrictions on use : For professional use only

#### 1.4. Details of manufacturer or importer

Autosmart Australia  
11 Darrambal Close  
Rathmines NSW 2283 NSW  
Australia  
T 02 49 75 14 88 (Mon to Fri, 08:00 - 16:00 AEST)  
[autosmart@autosmartaustralia.com.au](mailto:autosmart@autosmartaustralia.com.au) - [www.autosmartaustralia.com.au](http://www.autosmartaustralia.com.au)

#### 1.5. Emergency phone number

Emergency number : NCEC - For Chemical Emergency Support ONLY (spill, leak, fire, exposure or accident),  
Call NCEC at 18000 74234 (toll free 24Hrs) - when calling please quote "AUTOSMART 29003-NCEC"  
Local number +61 2 8 014 4558  
General Information. Transport Information. Mild medical Information:-  
Tel: 02 49 75 14 88 (Mon to Fri, 08:00 - 16:00 AEST)

### SECTION 2: Hazard identification


#### 2.1. Classification of the hazardous chemical

##### Classification according to the model Work Health and Safety Regulations (WHS Regulations)

Aerosol, Category 1	H222;H229
Gases under pressure : Compressed gas	H280
Serious eye damage/eye irritation, Category 2A	H319
Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336

#### 2.2. GHS Label elements, including precautionary statements

Hazard pictograms (GHS AU) :



Signal word (GHS AU) : Danger  
Contains : n-butyl acetate (2.7957215 – 6.98930375 %); Butanone (2.7957215 – 6.98930375 %); 2-methoxy-1-methylethyl acetate (2.7957215 – 6.98930375 %); Acetone (36.35 %)  
Hazard statements (GHS AU) : H222 - Extremely flammable aerosol  
H229 - Pressurised container: May burst if heated  
H280 - Contains gas under pressure; may explode if heated  
H319 - Causes serious eye irritation  
H336 - May cause drowsiness or dizziness

# (Aerosol) Gloss Black

## Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

Precautionary statements (GHS AU)	: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 - Do not spray on an open flame or other ignition source. P251 - Do not pierce or burn, even after use. P261 - Avoid breathing vapours, spray. P271 - Use only outdoors or in a well-ventilated area. P280 - Wear protective gloves, eye protection. P264 - Wash contaminated skin thoroughly after handling. P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P312 - Call a POISON CENTER, a doctor if you feel unwell. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337+P313 - If eye irritation persists: Get medical advice, medical attention. P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C, 122 °F.
Additional hazard statements (GHS AU)	: AUH066 - Repeated exposure may cause skin dryness or cracking.

### 2.3. Other hazards which do not result in classification

No additional information available

## SECTION 3: Composition and information on ingredients

Name	CAS-No.	%	Classification according to the model Work Health and Safety Regulations (WHS Regulations)
Acetone	67-64-1	36.35	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
Petroleum gases, liquefied (Contains < 0.1% 1,3-butadiene)	68476-85-7	30.1	Flam. Gas 1A, H220 Press. Gas (Comp.), H280 Flam. Liq. 1, H224
n-butyl acetate	123-86-4	2.7957215 – 6.98930375	Flam. Liq. 2, H225 STOT SE 3, H336
Butanone	78-93-3	2.7957215 – 6.98930375	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
2-methoxy-1-methylethyl acetate	108-65-6	2.7957215 – 6.98930375	Flam. Liq. 3, H226 STOT SE 3, H336
2-methoxy-1-methylethyl acetate	108-65-6	5.576565923 5	Flam. Liq. 3, H226
1-methoxypropan-2-ol	107-98-2	0.698930375 – 2.7957215	Flam. Liq. 3, H226 STOT SE 3, H336
Other substances (not contributing to the classification of this product)	-	76.24 – 90.91	-

## SECTION 4: First aid measures

### 4.1. Description of necessary first-aid measures

First-aid measures general	: Call a poison center or a doctor if you feel unwell.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

# (Aerosol) Gloss Black

## Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

### 4.2. Symptoms caused by exposure

Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after inhalation	: Although no appropriate human or animal health effects data are known to exist, this material is expected to be an inhalation hazard.
Symptoms/effects after skin contact	: None under normal conditions.
Symptoms/effects after eye contact	: Eye irritation.
Symptoms/effects after ingestion	: None under normal conditions.

### 4.3. Medical attention and special treatment

Other medical advice or treatment	: Treat symptomatically.
-----------------------------------	--------------------------

## SECTION 5: Fire-fighting measures

### 5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

### 5.2. Specific hazards arising from the chemical

Fire hazard	: Extremely flammable aerosol.
Explosion hazard	: Pressurised container: May burst if heated.
General measures	: Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material damage.

### 5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material damage.
------------------	--

#### 6.1.1. For non-emergency personnel

Protective equipment	: Wear recommended personal protective equipment.
Emergency procedures	: Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

#### 6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	: Evacuate unnecessary personnel. Stop leak if safe to do so.

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and materials for containment and cleaning up

For containment	: Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak without risks if possible.
Methods for cleaning up	: Mechanically recover the product.

# (Aerosol) Gloss Black

## Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Additional hazards when processed	: Not expected to present a significant hazard under anticipated conditions of normal use.
Precautions for safe handling	: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes. Wear personal protective equipment.
Hygiene measures	: Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

#### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Keep in a cool, well-ventilated place away from heat.
Storage conditions	: Protect from sunlight. Store in a well-ventilated place. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Keep container tightly closed.
Packaging materials	: Store always product in container of same material as original container.

### SECTION 8: Exposure controls and personal protection

#### 8.1. Control parameters - exposure standards

n-butyl acetate (123-86-4)	
Australia - Occupational Exposure Limits	
Local name	n-Butyl acetate
OES TWA	713 mg/m <sup>3</sup>
	150 ppm
OES STEL	950 mg/m <sup>3</sup>
	200 ppm
Regulatory reference	Workplace exposure standards for airborne contaminants (2022)
Butanone (78-93-3)	
Australia - Occupational Exposure Limits	
Local name	Methyl ethyl ketone (MEK; 2-Butanone)
OES TWA	445 mg/m <sup>3</sup>
	150 ppm
OES STEL	890 mg/m <sup>3</sup>
	300 ppm
Regulatory reference	Workplace exposure standards for airborne contaminants (2022)
2-methoxy-1-methylethyl acetate (108-65-6)	
Australia - Occupational Exposure Limits	
Local name	1-Methoxy-2-propanol acetate
OES TWA	274 mg/m <sup>3</sup>
	50 ppm
OES STEL	548 mg/m <sup>3</sup>
	100 ppm
Remark (AU)	Sk - Absorption through the skin may be a significant source of exposure.
Regulatory reference	Workplace exposure standards for airborne contaminants (2022)

# (Aerosol) Gloss Black

## Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

1-methoxypropan-2-ol (107-98-2)	
<b>Australia - Occupational Exposure Limits</b>	
Local name	Propylene glycol monomethyl ether (1-Methoxypropan-2-ol)
OES TWA	369 mg/m <sup>3</sup>
	100 ppm
OES STEL	553 mg/m <sup>3</sup>
	150 ppm
Regulatory reference	Workplace exposure standards for airborne contaminants (2022)
2-methoxy-1-methylethyl acetate (108-65-6)	
<b>Australia - Occupational Exposure Limits</b>	
Local name	1-Methoxy-2-propanol acetate
OES TWA	274 mg/m <sup>3</sup>
	50 ppm
OES STEL	548 mg/m <sup>3</sup>
	100 ppm
Remark (AU)	Sk - Absorption through the skin may be a significant source of exposure.
Regulatory reference	Workplace exposure standards for airborne contaminants (2022)
Acetone (67-64-1)	
<b>Australia - Occupational Exposure Limits</b>	
Local name	Acetone
OES TWA	1185 mg/m <sup>3</sup>
	500 ppm
OES STEL	2375 mg/m <sup>3</sup>
	1000 ppm
Regulatory reference	Workplace exposure standards for airborne contaminants (2022)
Petroleum gases, liquefied (Contains < 0.1% 1,3-butadiene) (68476-85-7)	
<b>Australia - Occupational Exposure Limits</b>	
Local name	LPG (liquefied petroleum gas)
OES TWA	1800 mg/m <sup>3</sup>
	1000 ppm
Remark (AU)	Carcinogenicity Category 1B - Presumed to have a carcinogenic potential for humans. The classification of a substance into this category is based largely on animal evidence where there is sufficient evidence to demonstrate carcinogenicity in animals or where there is limited evidence of carcinogenicity in humans and animals.
Regulatory reference	Workplace exposure standards for airborne contaminants (2022)

### 8.2. Monitoring methods

No additional information available

### 8.3. Engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

### 8.4. Individual protection measures, such as personal protective equipment (PPE)

Personal protective equipment : Wear recommended personal protective equipment.

# (Aerosol) Gloss Black

## Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

Materials for protective clothing	: The following Australian and New Zealand Standards will provide general advice regarding safety clothing and equipment: Industrial Clothing: AS2919.
Hand protection	: Protective gloves. The following Australian and New Zealand Standards will provide general advice regarding safety clothing and equipment: Protective Gloves: AS 2161.
Eye protection	: Safety glasses. The following Australian and New Zealand Standards will provide general advice regarding safety clothing and equipment: Industrial Eye Protection: AS1336 and AS/NZS 1337.
Skin and body protection	: Wear suitable protective clothing
Respiratory protection	: In case of insufficient ventilation, wear suitable respiratory equipment. The following Australian and New Zealand Standards will provide general advice regarding safety clothing and equipment: Respiratory equipment: AS/NZS 1715.

### Personal protective equipment symbol(s)



Environmental exposure controls	: Avoid release to the environment.
---------------------------------	-------------------------------------

## SECTION 9: Physical and chemical properties

Physical state	: Liquid
Appearance	: No data available
Colour	: Colourless.
Odour	: Odourless.
Odour threshold	: No data available
pH	: No data available
pH solution	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point / Freezing point	: Melting point: Not applicable
Boiling point	: No data available
Flash point	: < -40 °C
Auto-ignition temperature	: No data available
Flammability	: No data available
Vapour pressure	: No data available
Relative density	: No data available
Density	: No data available
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: < 20.5 mm <sup>2</sup> /s
Explosive properties	: Pressurised container: May burst if heated.
Explosive limits	: No data available
Minimum ignition energy	: No data available
VOC content	: 655 g/l
Fat solubility	: No data available

## SECTION 10: Stability and reactivity

Reactivity	: Extremely flammable aerosol. Pressurised container: May burst if heated.
Chemical stability	: No additional information available
Possibility of hazardous reactions	: No additional information available
Conditions to avoid	: Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.
Incompatible materials	: No additional information available
Hazardous decomposition products	: No additional information available

## SECTION 11: Toxicological information

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified

# (Aerosol) Gloss Black

## Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

Acute toxicity (inhalation) : Not classified

<b>2-methoxy-1-methylethyl acetate (108-65-6)</b>	
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Remarks on results: other:
<b>1-methoxypropan-2-ol (107-98-2)</b>	
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: EU Method B.3 (Acute Toxicity (Dermal))
<b>2-methoxy-1-methylethyl acetate (108-65-6)</b>	
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Remarks on results: other:
<b>Acetone (67-64-1)</b>	
LD50 oral rat	5800 mg/kg bodyweight Animal: rat, Animal sex: female
LC50 Inhalation - Rat	76 mg/l air Animal: rat, Animal sex: female, 95% CL: 65,2 - 88,4
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: May cause drowsiness or dizziness.
<b>n-butyl acetate (123-86-4)</b>	
STOT-single exposure	May cause drowsiness or dizziness.
<b>Butanone (78-93-3)</b>	
STOT-single exposure	May cause drowsiness or dizziness.
<b>2-methoxy-1-methylethyl acetate (108-65-6)</b>	
STOT-single exposure	May cause drowsiness or dizziness.
<b>1-methoxypropan-2-ol (107-98-2)</b>	
STOT-single exposure	May cause drowsiness or dizziness.
<b>Acetone (67-64-1)</b>	
STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified
<b>2-methoxy-1-methylethyl acetate (108-65-6)</b>	
NOAEL (dermal, rat/rabbit, 90 days)	> 1000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)
<b>1-methoxypropan-2-ol (107-98-2)</b>	
LOAEL (oral, rat, 90 days)	2757 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)
NOAEL (oral, rat, 90 days)	919 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)
NOAEL (dermal, rat/rabbit, 90 days)	> 1000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)
<b>2-methoxy-1-methylethyl acetate (108-65-6)</b>	
NOAEL (dermal, rat/rabbit, 90 days)	> 1000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)

# (Aerosol) Gloss Black

## Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

Petroleum gases, liquefied (Contains < 0.1% 1,3-butadiene) (68476-85-7)	
LOAEC (inhalation, rat, gas, 90 days)	12000 ppm Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test), Guideline: other:

Aspiration hazard : Not classified

(Aerosol) Gloss Black	
Vaporizer	Aerosol
Not able to form a pool	Yes
Viscosity, kinematic	< 20.5 mm <sup>2</sup> /s

1-methoxypropan-2-ol (107-98-2)	
Viscosity, kinematic	1.848 mm <sup>2</sup> /s

## SECTION 12: Ecological information

According to the National Code of Practice for the Preparation of Material Safety Data Sheets, Environmental classification information is not mandatory. Information relevant for GHS classification is available on request

### 12.1. Ecotoxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Not classified

n-butyl acetate (123-86-4)	
EC50 - Other aquatic organisms [1]	32 mg/l Test organisms (species): Artemia salina

Butanone (78-93-3)	
LC50 - Fish [1]	2993 mg/l Test organisms (species): Pimephales promelas
EC50 - Crustacea [1]	308 mg/l Test organisms (species): Daphnia magna

2-methoxy-1-methylethyl acetate (108-65-6)	
LC50 - Fish [1]	> 100 mg/l Test organisms (species): Oryzias latipes
EC50 - Crustacea [1]	> 500 mg/l Test organisms (species): Daphnia magna
NOEC (chronic)	≥ 100 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	47.5 mg/l Test organisms (species): Oryzias latipes Duration: '14 d'

1-methoxypropan-2-ol (107-98-2)	
EC50 - Other aquatic organisms [1]	2954 mg/l Test organisms (species): other aquatic crustacea:

2-methoxy-1-methylethyl acetate (108-65-6)	
LC50 - Fish [1]	> 100 mg/l Test organisms (species): Oryzias latipes
EC50 - Crustacea [1]	> 500 mg/l Test organisms (species): Daphnia magna
NOEC (chronic)	≥ 100 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	47.5 mg/l Test organisms (species): Oryzias latipes Duration: '14 d'

Acetone (67-64-1)	
LOEC (chronic)	> 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	≥ 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'



# (Aerosol) Gloss Black

## Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

Petroleum gases, liquefied (Contains < 0.1% 1,3-butadiene) (68476-85-7)	
LC50 - Fish [1]	0.362 mg/l
EC50 - Crustacea [1]	0.018 mg/l
ErC50 algae	7.6 mg/l Source: ECOTOX
Partition coefficient n-octanol/water (Log Pow)	≤ 2.8 Source: IUCLID

### 12.2. Persistence and degradability

(Aerosol) Gloss Black	
Persistence and degradability	Not rapidly degradable
n-butyl acetate (123-86-4)	
Persistence and degradability	Not rapidly degradable
Butanone (78-93-3)	
Persistence and degradability	Not rapidly degradable
2-methoxy-1-methylethyl acetate (108-65-6)	
Persistence and degradability	Not rapidly degradable
1-methoxypropan-2-ol (107-98-2)	
Persistence and degradability	Not rapidly degradable
2-methoxy-1-methylethyl acetate (108-65-6)	
Persistence and degradability	Not rapidly degradable
Acetone (67-64-1)	
Persistence and degradability	Not rapidly degradable
Petroleum gases, liquefied (Contains < 0.1% 1,3-butadiene) (68476-85-7)	
Persistence and degradability	Not rapidly degradable

### 12.3. Bioaccumulative potential

Petroleum gases, liquefied (Contains < 0.1% 1,3-butadiene) (68476-85-7)	
Partition coefficient n-octanol/water (Log Pow)	≤ 2.8 Source: IUCLID

### 12.4. Mobility in soil

Petroleum gases, liquefied (Contains < 0.1% 1,3-butadiene) (68476-85-7)	
Partition coefficient n-octanol/water (Log Pow)	≤ 2.8 Source: IUCLID

### 12.5. Other adverse effects

Ozone : Not classified  
Other adverse effects : No additional information available

(Aerosol) Gloss Black	
Fluorinated greenhouse gases	False
n-butyl acetate (123-86-4)	
Fluorinated greenhouse gases	False
Butanone (78-93-3)	
Fluorinated greenhouse gases	False

# (Aerosol) Gloss Black

## Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations




2-methoxy-1-methylethyl acetate (108-65-6)	
Fluorinated greenhouse gases	False
1-methoxypropan-2-ol (107-98-2)	
Fluorinated greenhouse gases	False
2-methoxy-1-methylethyl acetate (108-65-6)	
Fluorinated greenhouse gases	False
Acetone (67-64-1)	
Fluorinated greenhouse gases	False
Petroleum gases, liquefied (Contains < 0.1% 1,3-butadiene) (68476-85-7)	
Fluorinated greenhouse gases	False

### SECTION 13: Disposal considerations

Regional waste regulation	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: Disposal must be done according to official regulations.
Additional information	: Do not re-use empty containers.

### SECTION 14: Transport information

In accordance with ADG / IMDG / IATA

ADG	IMDG	IATA
<b>14.1. UN number</b>		
1950	1950	1950
<b>14.2. UN Proper Shipping Name</b>		
AEROSOLS	AEROSOLS	Aerosols, flammable
<b>Transport document description</b>		
Not applicable	UN 1950 AEROSOLS, 2.1	UN 1950 Aerosols, flammable, 2.1
<b>14.3. Transport hazard class(es)</b>		
2.1	2.1	2.1
		
<b>14.4. Packing group</b>		
Not applicable	Not applicable	Not applicable
<b>14.5. Environmental hazards</b>		
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No

### 14.6. Special precautions for user

Specific storage requirement	: No data available
Shock sensitivity	: No data available

# (Aerosol) Gloss Black

## Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

### 14.7. Additional information

Other information : No supplementary information available

#### Transport by road and rail

UN-No. (ADG) : 1950  
Special provision (ADG) : 63, 190, 277, 327, 344, 381  
Limited quantities (ADG) : 1I  
Excepted quantities (ADG) : E0  
Packing instructions (ADG) : P207, LP200  
Special packing provisions (ADG) : PP87, L2

#### Transport by sea

UN-No. (IMDG) : 1950  
Special provisions (IMDG) : 63, 190, 277, 327, 344, 381, 959  
Limited quantities (IMDG) : SP277  
Excepted quantities (IMDG) : E0  
Packing instructions (IMDG) : P207, LP200  
Special packing provisions (IMDG) : PP87, L2  
EmS-No. (Fire) : F-D - FIRE SCHEDULE Delta - FLAMMABLE GASES  
EmS-No. (Spillage) : S-U - SPILLAGE SCHEDULE Uniform - GASES (FLAMMABLE, TOXIC OR CORROSIVE)  
Stowage category (IMDG) : None  
Stowage and handling (IMDG) : SW1, SW22  
Segregation (IMDG) : SG69

#### Air transport

UN-No. (IATA) : 1950  
PCA Excepted quantities (IATA) : E0  
PCA Limited quantities (IATA) : Y203  
PCA limited quantity max net quantity (IATA) : 30kgG  
PCA packing instructions (IATA) : 203  
PCA max net quantity (IATA) : 75kg  
CAO packing instructions (IATA) : 203  
CAO max net quantity (IATA) : 150kg  
Special provisions (IATA) : A145, A167, A802  
ERG code (IATA) : 10L

### 14.8. Hazchem or Emergency Action Code

Hazchem Code : Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations specific for the product in question

No additional information available

### 15.2. International agreements

No additional information available

## SECTION 16: Other information

### Classification

Aerosol 1	H222;H229
Press. Gas (Comp.)	H280
Eye Irrit. 2A	H319
STOT SE 3	H336

# (Aerosol) Gloss Black

## Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

Full text of H-statements	
Aerosol 1	Aerosol, Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation, Category 2A
Flam. Gas 1A	Flammable gases, Category 1A
Flam. Liq. 1	Flammable liquids, Category 1
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Press. Gas (Comp.)	Gases under pressure : Compressed gas
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis
H220	Extremely flammable gas
H224	Extremely flammable liquid and vapour
H225	Highly flammable liquid and vapour
H226	Flammable liquid and vapour
H280	Contains gas under pressure; may explode if heated
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness

Safety Data Sheet (SDS), Australia

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.