



MATERIAL SAFETY DATA SHEET
(Aerosol) Express Wax

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Name (Aerosol) Express Wax
Product No. A83-9
Proper Shipping Name AEROSOLS

1.2. Relevant identified uses of the substance or mixture and uses advised against

Application: Car maintenance product. - Paint protector
Uses Advised Against For professional use only. This product is not recommended for any industrial, professional or consumer use other than the Identified uses above.

1.3. Details of the supplier of the safety data sheet

Supplier Autosmart Australia
11 Darrambal Close
Rathmines
NSW 2283
Australia
www.autosmartinternational.com
Tel: 02 49 75 14 88 (Mon to Fri, 08:00 - 16:00 AEST) (General Information. Transport Information. Mild Medical Information)
autosmart@autosmartaustralia.com.au
Contact Person Mr. Russell Butler

1.4. Emergency telephone number

Emergency No: +44 7808 971321 (24hrs) (Autosmart International, UK)
General Information. Transport Information. Mild medical Information:-
Tel: 02 49 75 14 88 (Mon to Fri, 08:00 - 16:00 AEST)

SECTION 2: HAZARDS IDENTIFICATION

Risk Phrases

R12 Extremely flammable.
R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R66 Repeated exposure may cause skin dryness or cracking.
R67 Vapours may cause drowsiness and dizziness.

Safety Phrases

A1 Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.
A2 Do not spray on a naked flame or any incandescent material.
S2 Keep out of the reach of children.
S9 Keep container in a well-ventilated place.
S16 Keep away from sources of ignition - No smoking.
S23 Do not breathe vapour/spray.
S37 Wear suitable gloves.
S38 In case of insufficient ventilation, wear suitable respiratory equipment.

2.1. Classification of the substance or mixture

Human health

When working extensively on big surfaces in small and badly ventilated rooms, vapours may develop in concentrations which may cause malaise such as headache, dizziness, nausea and irritation of the respiratory system.

(Aerosol) Express Wax**Physical and Chemical Hazards**

Aerosol containers can explode when heated, due to excessive pressure build-up. The product is extremely flammable, and explosive vapour/air mixtures may be formed even at normal room temperatures. When sprayed on a naked flame or any incandescent material the aerosol vapours can be ignited.

2.2. Label elements**Labelling**

Extremely flammable

Risk Phrases

R12	Extremely flammable.
R52/53	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R66	Repeated exposure may cause skin dryness or cracking.
R67	Vapours may cause drowsiness and dizziness.

Safety Phrases

A1	Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.
A2	Do not spray on a naked flame or any incandescent material.
S2	Keep out of the reach of children.
S9	Keep container in a well-ventilated place.
S16	Keep away from sources of ignition - No smoking.
S23	Do not breathe vapour/spray.
S37	Wear suitable gloves.
S38	In case of insufficient ventilation, wear suitable respiratory equipment.

2.3. Other hazards

This product does not contain any PBT or vPvB Substances.

Statement Of Hazardous Nature

HAZARDOUS SUBSTANCE (According to criteria of NOHSC). DANGEROUS GOODS (According to ADG Code).

ADR Class	Class 2: Gases
ADR Pack Group	#
UN No. Road	1950
Emergency Action Code	2(Y)

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**3.2. Mixtures**

BUTANE	30-60%
CAS-No.: 106-97-8	EC No.: 203-448-7
Classification (EC 1272/2008) Flam. Gas 1 - H220	Classification (67/548) F+;R12
Solvent naphtha (petroleum), medium aliph.	20-30%
CAS-No.: 64742-88-7	EC No.: 265-191-7
	Registration Number: 01-2119458049-33-xxxx
Classification (EC 1272/2008) Flam. Liq. 3 - H226 EUH066 STOT SE 3 - H336 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411	Classification (67/548) Xn;R65. N;R51/53. R10,R66,R67.

(Aerosol) Express Wax

Anhydrous Aluminium Silicate		0.2-0.5%
CAS-No.: 92704-41-1	EC No.: 296-473-8	
Classification (EC 1272/2008) Not classified.	Classification (67/548) Not classified.	
STODDARD SOLVENT; LOW BOILING POINT NAPHTHA - UNSPECIFIED		0.2-0.5%
CAS-No.: 8052-41-3	EC No.: 232-489-3	
Classification (EC 1272/2008) Asp. Tox. 1 - H304	Classification (67/548) Xn;R65.	
PARAFFIN WAX		0.1-0.2%
CAS-No.: 8002-74-2	EC No.: 232-315-6	
Substance with a Community workplace exposure limit.		
Classification (EC 1272/2008) Not classified.	Classification (67/548) Not classified.	

The Full Text for all R-Phrases and Hazard Statements is Displayed in Section 16.

SECTION 4: FIRST AID MEASURES

Susdp First Aid Instructions

For advice, contact a Poisons Information Centre (Phone 13 1126) or a doctor.

If swallowed, do NOT induce vomiting.

4.1. Description of first aid measures

General information

NOTE! Keep affected person away from heat, sparks and flames!

Inhalation

Move the exposed person to fresh air at once. Get medical attention if any discomfort continues. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Perform artificial respiration if breathing has stopped. Keep the affected person warm and at rest. Get prompt medical attention.

Ingestion

Remove victim immediately from source of exposure. Rinse mouth thoroughly. DO NOT induce vomiting. Get medical attention immediately.

Skin contact

Remove affected person from source of contamination. Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.

Eye contact

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

4.2. Most important symptoms and effects, both acute and delayed

General information

The severity of the symptoms described will vary dependant of the concentration and the length of exposure.

Inhalation

In case of overexposure, organic solvents may depress the central nervous system causing dizziness and intoxication, and at very high concentrations unconsciousness and death.

Ingestion

May cause discomfort if swallowed. Dizziness. Nausea, vomiting. Fumes from the stomach contents may be inhaled resulting in the same symptoms as inhalation.

Skin contact

Prolonged contact may cause redness, irritation and dry skin.

Eye contact

May cause temporary eye irritation. Prolonged contact may cause redness and/or tearing.

(Aerosol) Express Wax**4.3. Indication of any immediate medical attention and special treatment needed**

No recommendation given, but first aid may still be required in case of accidental exposure, inhalation or ingestion of this chemical. If in doubt, GET MEDICAL ATTENTION PROMPTLY!

SECTION 5: FIREFIGHTING MEASURES**5.1. Extinguishing media****Extinguishing media**

Use: Powder. Alcohol resistant foam. Carbon dioxide or dry powder. Dry chemicals, sand, dolomite etc. Cool aerosol containers exposed to heat with water spray and remove container, if no risk is involved.

Unsuitable Extinguishing Media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture**Hazardous Combustion Products**

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

Unusual Fire & Explosion Hazards

Forms explosive mixtures with air. HIGHLY FLAMMABLE! May travel considerable distance to source of ignition and flash back. Aerosol cans may explode in a fire.

Specific hazards

Aerosol containers can explode when heated, due to excessive pressure build-up. Fire creates: Carbon dioxide (CO₂). Carbon monoxide (CO). Nitrous gases (NO_x).

5.3. Advice for firefighters**Special Fire Fighting Procedures**

Ventilate closed spaces before entering them. Move container from fire area if it can be done without risk. Use water to keep fire exposed containers cool and disperse vapours. Do not scatter spilled material with more water than needed to fight the fire. Be aware of danger for fire to re-start. Keep run-off water out of sewers and water sources. Dike for water control. Containers close to fire should be removed or cooled with water. Be aware of danger of explosion. Fight advanced or massive fires from safe distance or protected location.

Protective equipment for fire-fighters

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

Emergency Action Code 2(Y)

SECTION 6: ACCIDENTAL RELEASE MEASURES**6.1. Personal precautions, protective equipment and emergency procedures**

For personal protection, see section 8.

6.2. Environmental precautions

Do not discharge into drains, water courses or onto the ground. Spillages or uncontrolled discharges into watercourses must be IMMEDIATELY alerted to the Environmental Agency or other appropriate regulatory body.

6.3. Methods and material for containment and cleaning up

Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Absorb in vermiculite, dry sand or earth and place into containers. Let evaporate. Keep out of confined spaces because of explosion risk. Ensure that waste and contaminated materials are collected and removed from the work area as soon as possible in a suitably labelled container.

6.4. Reference to other sections

See section 11 for additional information on health hazards. For personal protection, see section 8. For waste disposal, see section 13.

SECTION 7: HANDLING AND STORAGE**7.1. Precautions for safe handling**

Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level. Read and follow manufacturer's recommendations. During application and drying, solvent vapours will be emitted. Risk of vapour concentration on the floor and in low-lying areas. Eliminate all sources of ignition. Static electricity and formation of sparks must be prevented.

7.2. Conditions for safe storage, including any incompatibilities

Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C. Keep away from heat, sparks and open flame. Pressurised container: Must not be exposed to temperatures above 50°C. Store at moderate temperatures in dry, well ventilated area. Store in a dry place.

Storage Class

Flammable compressed gas storage.

(Aerosol) Express Wax**7.3. Specific end use(s)**

The identified uses for this product are detailed in Section 1.2.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**8.1. Control parameters**

Name	STD	TWA - 8 Hrs		STEL - 15 Min		Notes
Anhydrous Aluminium Silicate	NOHSC		10 mg/m ³			
BUTANE	NOHSC	800 ppm	1900 mg/m ³			
PARAFFIN WAX	NOHSC		2 mg/m ³			
STODDARD SOLVENT; LOW BOILING POINT NAPHTHA - UNSPECIFIED	NOHSC		790 mg/m ³			

NOHSC = The National Occupational Health and Safety Commission.

Solvent naphtha (petroleum), medium aliph. (CAS: 64742-88-7)**Ingredient Comments**

No exposure limits noted for ingredient(s).

8.2. Exposure controls**Protective equipment****Process Conditions**

Provide eyewash station.

Engineering measures

Observe occupational exposure limits and minimize the risk of inhalation of vapours. No specific ventilation requirements noted, except this product must not be used in a confined space without good ventilation.

Respiratory equipment

No specific recommendation made, but respiratory protection must be used if the general level exceeds the recommended occupational exposure limit. Use chemical cartridge protection with appropriate cartridge.

Hand protection

Protective gloves must be used if there is a risk of direct contact or splash. The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material. Use protective gloves made of: Neoprene, nitrile, polyethylene or PVC. or Rubber (natural, latex). Be aware that the liquid may penetrate the gloves. Frequent change is advisable. Use thin cotton gloves inside the rubber gloves if allergy risk. Barrier cream applied before work may make it easier to clean the skin after exposure, but does not prevent absorption through the skin.

Eye protection

Wear approved chemical safety goggles where eye exposure is reasonably probable.

Other Protection

Wear appropriate clothing to prevent repeated or prolonged skin contact.

Hygiene measures

DO NOT SMOKE IN WORK AREA! When using do not eat, drink or smoke. Wash hands at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Wash promptly if skin becomes contaminated.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**9.1. Information on basic physical and chemical properties**

Appearance	Aerosol. Liquid
Colour	Brown.
Odour	Strong. Solvent.
Solubility	Soluble in: Organic solvents. Insoluble in water
Boiling Point (°C)	~ 100°C @ 760 mm Hg
Melting point (°C)	~ 0°C
Relative density	1.000 (20°C)
Vapour pressure	590 - 1760 kPa @ 45 °C

(Aerosol) Express Wax**Evaporation rate**

Not available.

pH-Value, Conc. Solution

Not applicable.

pH-Value, Diluted Solution

Not applicable.

Viscosity

Not determined.

Decomposition temperature (°C)

Not available.

Odour Threshold, Lower

Not available.

Odour Threshold, Upper

Not available.

Flash point (°C) < -20°C CC (Closed cup).**Auto Ignition Temperature (°C)** 365**Flammability Limit - Lower(%)** 1.8**Flammability Limit - Upper(%)** 9.5**Partition Coefficient
(N-Octanol/Water)** 2.3 - 2.8**Oxidising properties**

Not applicable.

Other Information

Information declared as "Not available" or "Not applicable" is not considered to be justified for enabling proper control measures to be taken.

9.2. Other information**Volatile Organic Compound (VOC)** 583 g/litre**SECTION 10: STABILITY AND REACTIVITY****10.1. Reactivity**

No specific reactivity hazards associated with this product.

10.2. Chemical stability

Stable under normal temperature conditions and recommended use. Avoid Heat, sparks, flames. Shocks and physical damage.

10.3. Possibility of hazardous reactions

Not applicable.

Hazardous Polymerisation

Will not polymerise.

10.4. Conditions to avoid

Avoid exposing aerosol containers to high temperatures or direct sunlight. Avoid heat, flames and other sources of ignition.

10.5. Incompatible materials**Materials To Avoid**

No specific, or groups of materials are likely to react to produce a hazardous situation.

10.6. Hazardous decomposition productsFire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO₂). Nitrous gases (NO_x).**SECTION 11: TOXICOLOGICAL INFORMATION****11.1. Information on toxicological effects****Toxicological information**

No significant health hazards when used for designed purpose and application and when used in accordance with instructions.

Other Health Effects

This substance has no evidence of carcinogenic properties. IARC Not Listed. OSHA Not Regulated. NTP Not Listed.

Skin Corrosion/Irritation

(Aerosol) Express Wax**Human Skin Model Test**

Scientifically unjustified.

Extreme pH

Scientifically unjustified.

General information

Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.

Inhalation

Vapours may cause headache, fatigue, dizziness and nausea. Vapour may affect central nervous system and cause headache, discomfort, vomiting or intoxication. High concentrations of vapours may irritate respiratory system and lead to headache, fatigue, nausea and vomiting. Vapour may irritate respiratory system or lungs.

Ingestion

May cause stomach pain or vomiting. Gastrointestinal symptoms, including upset stomach. May cause discomfort if swallowed. No harmful effects expected in amounts likely to be ingested by accident.

Skin contact

May cause defatting of the skin, but is not an irritant.

Eye contact

Spray and vapour in the eyes may cause irritation and smarting.

Health Warnings

Because of quantity and composition, the health hazard is small. No specific acute or chronic health impact noted, but this chemical may still have adverse impact on human health, either in general or on certain individuals with pre-existing or latent health problems.

Route of entry

Inhalation. Ingestion. Skin and/or eye contact.

Target Organs

Central nervous system Respiratory system, lungs

Medical Symptoms

No specific symptoms noted, but this chemical may still have adverse health impact, either in general or on certain individuals.

Medical Considerations

Skin disorders and allergies.

Toxicological Information on Ingredients:**PROPANE (CAS: 74-98-6)****Toxicological information**

No data recorded.

BUTANE (CAS: 106-97-8)**Toxicological information**

No data recorded.

Solvent naphtha (petroleum), medium aliph. (CAS: 64742-88-7)**Other Health Effects**

This substance has no evidence of carcinogenic properties.

Acute toxicity:**Acute Toxicity (Oral LD50)**

> 5050 mg/kg Rat

Acute Toxicity (Dermal LD50)

> 4 mg/kg Rabbit

Acute Toxicity (Inhalation LC50)

> 13 mg/l (vapours) Rat 4 hours

SECTION 12: ECOLOGICAL INFORMATION**Ecotoxicity**

The product contains a substance which is harmful to aquatic organisms.

(Aerosol) Express Wax**Ecological Information on Ingredients:****PROPANE (CAS: 74-98-6)****Ecotoxicity**

The product is not expected to be hazardous to the environment.

BUTANE (CAS: 106-97-8)**Ecotoxicity**

The product is not expected to be hazardous to the environment.

Solvent naphtha (petroleum), medium aliph. (CAS: 64742-88-7)**Ecotoxicity**

Dangerous for the environment: May cause long-term adverse effects in the aquatic environment.

12.1. Toxicity**Acute Toxicity - Fish**

Not determined.

Acute Toxicity Aquatic Invertebrates

Not determined.

Acute Toxicity - Aquatic Plants

Not determined.

Acute Toxicity - Microorganisms

Not determined.

Acute Toxicity - Terrestrial

Not determined.

12.2. Persistence and degradability**Degradability**

The product is biodegradable. Volatile substances are degraded in the atmosphere within a few days.

Ecological Information on Ingredients:**PROPANE (CAS: 74-98-6)****Degradability**

Volatile substances are degraded in the atmosphere within a few days.

BUTANE (CAS: 106-97-8)**Degradability**

Volatile substances are degraded in the atmosphere within a few days.

Solvent naphtha (petroleum), medium aliph. (CAS: 64742-88-7)**Degradability**

Volatile substances are degraded in the atmosphere within a few days.

12.3. Bioaccumulative potential**Bioaccumulative potential**

Bioaccumulation is unlikely to be significant because of the low water solubility of this product.

Partition coefficient 2.3 - 2.8

Ecological Information on Ingredients:**PROPANE (CAS: 74-98-6)****Bioaccumulative potential**

The product does not contain any substances expected to be bioaccumulating.

BUTANE (CAS: 106-97-8)**Bioaccumulative potential**

The product does not contain any substances expected to be bioaccumulating.

Solvent naphtha (petroleum), medium aliph. (CAS: 64742-88-7)**Bioaccumulative potential**

The product does not contain any substances expected to be bioaccumulating.

12.4. Mobility in soil**Mobility:**

The product contains volatile organic compounds (VOC) which will evaporate easily from all surfaces. The product is insoluble in water.

(Aerosol) Express Wax**Ecological Information on Ingredients:****PROPANE (CAS: 74-98-6)****Mobility:**

The product contains volatile organic compounds (VOC) which will evaporate easily from all surfaces.

BUTANE (CAS: 106-97-8)**Mobility:**

The product contains volatile organic compounds (VOC) which will evaporate easily from all surfaces.

Solvent naphtha (petroleum), medium aliph. (CAS: 64742-88-7)**Mobility:**

The product contains volatile organic compounds (VOC) which will evaporate easily from all surfaces. The product has poor water-solubility.

12.5. Results of PBT and vPvB assessment

This product does not contain any PBT or vPvB Substances.

12.6. Other adverse effects

Not applicable.

SECTION 13: DISPOSAL CONSIDERATIONS**General information**

Do not puncture or incinerate even when empty. Empty aerosols should be recycled where facilities exist. Full or part full aerosols should be disposed of as hazardous waste in accordance with local authority requirements.

13.1. Waste treatment methods

Empty containers must not be burned because of explosion hazard. Dispose of waste and residues in accordance with local authority requirements. Do not allow runoff to sewer, waterway or ground. Packaging: Recover and reclaim or recycle, if practical.

SECTION 14: TRANSPORT INFORMATION**14.1. UN number**

UN No. Road	1950
UN No. Sea	1950
UN No., Air	1950

14.2. UN proper shipping name

Proper Shipping Name	AEROSOLS
----------------------	----------

14.3. Transport hazard class(es)

ADR Class No.	2.1
ADR Class	Class 2: Gases
ADR Label No.	2.1
IMDG Class	2.1
ICAO Class	2.1

Transport Labels**14.4. Packing group**

Not applicable.

ADR Pack Group	#
IMDG Pack Gr.	#
Air Pack Gr.	#

(Aerosol) Express Wax**14.5. Environmental hazards****Environmentally Hazardous Substance/Marine Pollutant**

No.

14.6. Special precautions for user

EMS	F-D, S-U
Emergency Action Code	2(Y)
Tunnel Restriction Code	(D)

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not applicable.

SECTION 15: REGULATORY INFORMATION**Poisons Schedule Number** Allocated Poison Schedule Number - 5**National Regulations And References**

The Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP). National Code of Practice for the Preparation of Material Safety Data Sheets. Approved Criteria for Classifying Hazardous Substances. Exposure Standards for Atmospheric Contaminants in the Occupational Environment. Guidance Note on the Interpretation of Exposure Standards for Atmospheric Contaminants in the Occupational Environment. National Code of Practice for the Labelling of Workplace Substances. National Model Regulations for the Control of Workplace Hazardous Substances. National Code of Practice for the Control of Workplace Hazardous Substances. National Standard for the Storage and Handling of Workplace Dangerous Goods. National Code of Practice for the Storage and Handling of Workplace Dangerous Goods. Guidance Note for Placarding Stores for Dangerous Goods and Specified Hazardous Substances. Guidance Note for the Assessment of Health Risks Arising from Hazardous Substances in the Workplace. National Standard for the Control of Major Hazard Facilities. National Code of Practice for the Control of Major Hazard Facilities.

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**EU Legislation**

Dangerous Preparations Directive 1999/45/EC. Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments. Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 with amendments.

Health And Environmental Listings

Regulation EC 689/2008 concerning the export and import of dangerous chemicals.

Water hazard classification

WGK 1

15.2. Chemical Safety Assessment

No chemical safety assessment has been carried out.

SECTION 16: OTHER INFORMATION**General information**

Only trained personnel should use this material. This product has been manufactured under ISO 9001 and ISO 14001 Quality and Environmental Management Systems.

Revision Comments

NOTE: Lines within the margin indicate significant changes from the previous revision.

Issued By	Prepared by Autosmart International Ltd, Lynn Lane, Shenstone, Lichfield, Staffordshire, WS14 0DH, Great Britain. www.autosmartinternational.com rbutler@autosmart.co.uk Tel +44 (0)1543 481616
Revision Date	08/10/2013
Revision	2
Supersedes date	05/06/2013
Safety Data Sheet Status	Approved.

(Aerosol) Express Wax**Risk Phrases In Full**

R12	Extremely flammable.
R10	Flammable.
R52/53	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R65	Harmful: may cause lung damage if swallowed.
NC	Not classified.
R66	Repeated exposure may cause skin dryness or cracking.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R67	Vapours may cause drowsiness and dizziness.

Hazard Statements In Full

EUH066	Repeated exposure may cause skin dryness or cracking.
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Disclaimer

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.