



**MATERIAL SAFETY DATA SHEET**  
**(Aerosol) White Gloss**

**SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**

**1.1. Product identifier**

**Product Name** (Aerosol) White Gloss  
**Proper Shipping Name** AEROSOLS

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

**Application:** Car maintenance product. - Paint.  
**Uses Advised Against** For professional use only. This product is not recommended for any industrial, professional or consumer use other than the Identified uses above.

**1.3. Details of the supplier of the safety data sheet**

**Supplier** Autosmart Australia  
11 Darrambal Close  
Rathmines  
NSW 2283  
Australia  
www.autosmartinternational.com  
Tel: 02 49 75 14 88 (Mon to Fri, 08:00 - 16:00 AEST) (General Information. Transport Information. Mild Medical Information)  
autosmart@autosmartaustralia.com.au  
**Contact Person** Mr. Russell Butler

**1.4. Emergency telephone number**

Emergency No: +44 7808 971321 (24hrs) (Autosmart International, UK)  
General Information. Transport Information. Mild medical Information:-  
Tel: 02 49 75 14 88 (Mon to Fri, 08:00 - 16:00 AEST)

**SECTION 2: HAZARDS IDENTIFICATION**

**Risk Phrases**

R12	Extremely flammable.
R36	Irritating to eyes.
R66	Repeated exposure may cause skin dryness or cracking.
R67	Vapours may cause drowsiness and dizziness.

**Safety Phrases**

A1	Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.
A2	Do not spray on a naked flame or any incandescent material.
S2	Keep out of the reach of children.
S16	Keep away from sources of ignition - No smoking.
S23	Do not breathe vapour/spray.
S25	Avoid contact with eyes.
S26	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S51	Use only in well-ventilated areas.

**2.1. Classification of the substance or mixture**

**Human health**

When working extensively on big surfaces in small and badly ventilated rooms, vapours may develop in concentrations which may cause malaise such as headache, dizziness, nausea and irritation of the respiratory system.

**Physical and Chemical Hazards**

Aerosol containers can explode when heated, due to excessive pressure build-up. The product is extremely flammable, and explosive vapour/air mixtures may be formed even at normal room temperatures. When sprayed on a naked flame or any incandescent material the aerosol vapours can be ignited.

**(Aerosol) White Gloss****2.2. Label elements****Labelling**

Irritant



Extremely flammable

**Risk Phrases**

R12	Extremely flammable.
R36	Irritating to eyes.
R66	Repeated exposure may cause skin dryness or cracking.
R67	Vapours may cause drowsiness and dizziness.

**Safety Phrases**

A1	Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.
A2	Do not spray on a naked flame or any incandescent material.
S2	Keep out of the reach of children.
S16	Keep away from sources of ignition - No smoking.
S23	Do not breathe vapour/spray.
S25	Avoid contact with eyes.
S26	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S51	Use only in well-ventilated areas.

**2.3. Other hazards**

This product does not contain any PBT or vPvB Substances.

**Statement Of Hazardous Nature**

HAZARDOUS SUBSTANCE (According to criteria of NOHSC). DANGEROUS GOODS (According to ADG Code).

**ADR Class** Class 2: Gases

**ADR Pack Group** #

**UN No. Road** 1950

**Emergency Action Code** 2(Y)

### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

**3.2. Mixtures**

<b>ACETONE</b>	<b>30-60%</b>
<b>CAS-No.: 67-64-1</b>	<b>EC No.: 200-662-2</b>
<b>Registration Number: 01-2119471330-49-xxxx</b>	
Classification (EC 1272/2008) Flam. Liq. 2 - H225 EUH066 Eye Irrit. 2 - H319 STOT SE 3 - H336	Classification (67/548) F;R11 Xi;R36 R66 R67
<b>BUTANE</b>	<b>5-10%</b>
<b>CAS-No.: 106-97-8</b>	<b>EC No.: 203-448-7</b>
Classification (EC 1272/2008) Flam. Gas 1 - H220	Classification (67/548) F+;R12

**(Aerosol) White Gloss**

<b>TOLUENE</b>		<b>1-2%</b>
<b>CAS-No.: 108-88-3</b>	<b>EC No.: 203-625-9</b>	
Classification (EC 1272/2008) Flam. Liq. 2 - H225 Skin Irrit. 2 - H315 Repr. 2 - H361d STOT SE 3 - H336 STOT RE 2 - H373 Asp. Tox. 1 - H304	Classification (67/548) F;R11 Repr. Cat. 3;R63 Xn;R48/20,R65 Xi;R38 R67	
<b>XYLENE</b>		<b>1-2%</b>
<b>CAS-No.: 1330-20-7</b>	<b>EC No.: 215-535-7</b>	<b>Registration Number: 01-2119488216-32-xxxx</b>
Classification (EC 1272/2008) Flam. Liq. 3 - H226 Acute Tox. 4 - H312 Acute Tox. 4 - H332 Skin Irrit. 2 - H315	Classification (67/548) R10 Xn;R20/21 Xi;R38	
<b>BUTANONE</b>		<b>1-2%</b>
<b>CAS-No.: 78-93-3</b>	<b>EC No.: 201-159-0</b>	
Classification (EC 1272/2008) Flam. Liq. 2 - H225 EUH066 Eye Irrit. 2 - H319 STOT SE 3 - H336	Classification (67/548) F;R11 Xi;R36 R66 R67	
<b>ISOBUTANE</b>		<b>1-2%</b>
<b>CAS-No.: 75-28-5</b>	<b>EC No.: 200-857-2</b>	
Classification (EC 1272/2008) Flam. Gas 1 - H220	Classification (67/548) F+;R12	
<b>Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, &lt;2% aromatics</b>		<b>1-2%</b>
<b>CAS-No.: 64742-48-9</b>	<b>EC No.: 919-857-5</b>	<b>Registration Number: 01-2119463258-33-xxxx</b>
Classification (EC 1272/2008) Flam. Liq. 3 - H226 EUH066 STOT SE 3 - H336 Asp. Tox. 1 - H304	Classification (67/548) Xn;R65. R10,R66,R67.	
<b>ETHYLBENZENE</b>		<b>0.7-1.0%</b>
<b>CAS-No.: 100-41-4</b>	<b>EC No.: 202-849-4</b>	
Classification (EC 1272/2008) Flam. Liq. 2 - H225 Acute Tox. 4 - H332	Classification (67/548) F;R11 Xn;R20	

**(Aerosol) White Gloss**

The Full Text for all R-Phrases and Hazard Statements is Displayed in Section 16.

## SECTION 4: FIRST AID MEASURES

### Susdp First Aid Instructions

For advice, contact a Poisons Information Centre (Phone 13 1126) or a doctor at once.

If swallowed, do NOT induce vomiting.

### 4.1. Description of first aid measures

#### General information

Move the exposed person to fresh air at once.

#### Inhalation

In case of inhalation of spray mist: Move person into fresh air and keep at rest. Perform artificial respiration if breathing has stopped. Keep the affected person warm and at rest. Get prompt medical attention.

#### Ingestion

DO NOT INDUCE VOMITING! Rinse mouth thoroughly. Drink plenty of water. Get medical attention if any discomfort continues.

#### Skin contact

Promptly wash contaminated skin with soap or mild detergent and water. Promptly remove clothing if soaked through and wash as above. Get medical attention if any discomfort continues.

#### Eye contact

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

### 4.2. Most important symptoms and effects, both acute and delayed

#### General information

The severity of the symptoms described will vary dependant of the concentration and the length of exposure.

#### Inhalation

In case of overexposure, organic solvents may depress the central nervous system causing dizziness and intoxication, and at very high concentrations unconsciousness and death.

#### Ingestion

Due to the physical nature of this material it is unlikely that swallowing will occur. May cause nausea, headache, dizziness and intoxication.

#### Skin contact

Prolonged or repeated contact with skin may cause redness, itching, irritation and eczema/chapping.

#### Eye contact

Irritation of eyes and mucous membranes.

### 4.3. Indication of any immediate medical attention and special treatment needed

No recommendation given, but first aid may still be required in case of accidental exposure, inhalation or ingestion of this chemical. If in doubt, GET MEDICAL ATTENTION PROMPTLY!

## SECTION 5: FIREFIGHTING MEASURES

### 5.1. Extinguishing media

#### Extinguishing media

Use: Powder. Dry chemicals, sand, dolomite etc. Water spray, fog or mist.

### 5.2. Special hazards arising from the substance or mixture

#### Unusual Fire & Explosion Hazards

Forms explosive mixtures with air. HIGHLY FLAMMABLE! May travel considerable distance to source of ignition and flash back. Aerosol cans may explode in a fire.

#### Specific hazards

Aerosol containers can explode when heated, due to excessive pressure build-up. Fire creates: Carbon dioxide (CO<sub>2</sub>). Carbon monoxide (CO). Nitrous gases (NO<sub>x</sub>).

### 5.3. Advice for firefighters

#### Special Fire Fighting Procedures

Containers close to fire should be removed or cooled with water. Use water to keep fire exposed containers cool and disperse vapours. Be aware of danger of explosion.

#### Protective equipment for fire-fighters

Wear full protective clothing.

**Emergency Action Code** 2(Y)

**(Aerosol) White Gloss****SECTION 6: ACCIDENTAL RELEASE MEASURES****6.1. Personal precautions, protective equipment and emergency procedures**

For personal protection, see section 8.

**6.2. Environmental precautions**

Do not discharge into drains, water courses or onto the ground. Spillages or uncontrolled discharges into watercourses must be IMMEDIATELY alerted to the Environmental Agency or other appropriate regulatory body.

**6.3. Methods and material for containment and cleaning up**

Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Absorb in vermiculite, dry sand or earth and place into containers. Let evaporate. Keep out of confined spaces because of explosion risk.

**6.4. Reference to other sections**

For personal protection, see section 8. For waste disposal, see section 13. See section 11 for more detailed information on health effects and symptoms.

**SECTION 7: HANDLING AND STORAGE****7.1. Precautions for safe handling**

Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level. Read and follow manufacturer's recommendations. During application and drying, solvent vapours will be emitted. Eliminate all sources of ignition.

**7.2. Conditions for safe storage, including any incompatibilities**

Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C. Protect from light, including direct sunrays. Keep away from heat, sparks and open flame. Pressurised container: Must not be exposed to temperatures above 50°C. Store at moderate temperatures in dry, well ventilated area.

**Storage Class**

Flammable compressed gas storage.

**7.3. Specific end use(s)**

The identified uses for this product are detailed in Section 1.2.

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION****8.1. Control parameters**

Name	STD	TWA - 8 Hrs		STEL - 15 Min		Notes
ACETONE	NOHSC	500 ppm	1185 mg/m <sup>3</sup>	1000 ppm	2375 mg/m <sup>3</sup>	
BUTANE	NOHSC	800 ppm	1900 mg/m <sup>3</sup>			
BUTANONE	NOHSC	150 ppm	445 mg/m <sup>3</sup>	300 ppm	890 mg/m <sup>3</sup>	
ETHYLBENZENE	NOHSC	100 ppm	434 mg/m <sup>3</sup>	125 ppm	543 mg/m <sup>3</sup>	
TOLUENE	NOHSC	50 ppm	191 mg/m <sup>3</sup>	150 ppm	574 mg/m <sup>3</sup>	Sk
XYLENE	NOHSC	80 ppm	350 mg/m <sup>3</sup>	150 ppm	655 mg/m <sup>3</sup>	

NOHSC = The National Occupational Health and Safety Commission.

Sk = Absorption through the skin may be a significant source of exposure.

**(Aerosol) White Gloss****XYLENE (CAS: 1330-20-7)****DNEL**

Industry	Inhalation.	Short Term	442	mg/m <sup>3</sup>
Industry	Inhalation.	Long Term	221	mg/kg/day
Industry	Dermal	Long Term	3182	mg/m <sup>3</sup>
Consumer	Inhalation.	Short Term	260	mg/m <sup>3</sup>
Consumer	Inhalation.	Long Term	65.3	mg/m <sup>3</sup>
Consumer	Dermal	1872	mg/kg/day	
Consumer	Oral	Long Term	12.5	mg/kg/day

**PNEC**

Freshwater	0.327	mg/l
Marinewater	0.327	mg/l
Sediment (Freshwater)	12.46	mg/kg
Sediment (Marinewater)	12.46	mg/kg
Soil	2.31	mg/kg
STP	6.58	mg/l

**Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics (CAS: 64742-48-9)****Ingredient Comments**

No exposure limits noted for ingredient(s).

**DNEL**

Industry	Dermal	Long Term	208	mg/kg/day
Industry	Inhalation.	Long Term	871	mg/kg/day
Consumer	Dermal	Long Term	125	mg/kg/day
Consumer	Inhalation.	Long Term	185	mg/kg/day
Consumer	Oral	Long Term	125	mg/kg/day

**8.2. Exposure controls****Protective equipment****Process Conditions**

Provide eyewash station.

**Engineering measures**

Observe occupational exposure limits and minimize the risk of inhalation of vapours. No specific ventilation requirements noted, except this product must not be used in a confined space without good ventilation.

**Respiratory equipment**

If ventilation is insufficient, suitable respiratory protection must be provided. Wear mask supplied with: Gas cartridge suitable for organic substances.

**Hand protection**

Use protective gloves made of: Butyl rubber. Nitrile gloves are recommended, but be aware that the liquid may penetrate the gloves. Frequent change is advisable. The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material.

**Eye protection**

Wear approved chemical safety goggles where eye exposure is reasonably probable.

**Other Protection**

Wear appropriate clothing to prevent repeated or prolonged skin contact.

**Hygiene measures**

DO NOT SMOKE IN WORK AREA! When using do not eat, drink or smoke. Wash hands at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated.

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES****9.1. Information on basic physical and chemical properties**

<b>Appearance</b>	Aerosol. Liquid
<b>Colour</b>	White.
<b>Odour</b>	Organic solvents.
<b>Solubility</b>	Soluble in: Organic solvents Insoluble in water
<b>Boiling Point (°C)</b>	Not available.
<b>Relative density</b>	Not available.

**(Aerosol) White Gloss****Vapour density (air=1)**

Not available.

**Vapour pressure**

Not available.

**Evaporation rate**

Not available.

**Viscosity**

Not available.

**Decomposition temperature (°C)**

Not available.

**Odour Threshold, Lower**

Not available.

**Odour Threshold, Upper**

Not available.

**Flash point (°C)** < -40 CC (Closed cup).**Auto Ignition Temperature (°C)** 410 - 580**Flammability Limit - Lower(%)** 1.8**Flammability Limit - Upper(%)** 9.5**Partition Coefficient  
(N-Octanol/Water)**

Not available.

**Oxidising properties**

Not applicable.

**Other Information**

Information declared as "Not available" or "Not applicable" is not considered to be justified for enabling proper control measures to be taken.

**9.2. Other information****Volatile Organic Compound (VOC)** 640 g/litre**SECTION 10: STABILITY AND REACTIVITY****10.1. Reactivity**

No specific reactivity hazards associated with this product.

**10.2. Chemical stability**

Stable under normal temperature conditions and recommended use. Avoid Heat, sparks, flames. Shocks and physical damage.

**10.3. Possibility of hazardous reactions**

Not relevant.

**Hazardous Polymerisation**

Will not polymerise.

**10.4. Conditions to avoid**

Avoid exposing aerosol containers to high temperatures or direct sunlight. Avoid heat, flames and other sources of ignition. Avoid contact with: Strong oxidising agents. Strong alkalis. Strong mineral acids.

**10.5. Incompatible materials****Materials To Avoid**

Strong alkalis. Strong oxidising substances. Strong acids.

**10.6. Hazardous decomposition products**Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>). Nitrous gases (NO<sub>x</sub>).**SECTION 11: TOXICOLOGICAL INFORMATION****11.1. Information on toxicological effects****General information**

Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.

**(Aerosol) White Gloss****Inhalation**

High concentrations of vapours may irritate respiratory system and lead to headache, fatigue, nausea and vomiting. Vapours may cause drowsiness and dizziness.

**Ingestion**

May cause discomfort if swallowed.

**Skin contact**

Harmful in contact with skin. Repeated exposure may cause skin dryness or cracking.

**Eye contact**

Irritating to eyes. Spray and vapour in the eyes may cause irritation and smarting. Repeated exposure may cause chronic eye irritation.

**Health Warnings**

Because of quantity and composition, the health hazard is small.

**Route of entry**

Inhalation.

**Target Organs**

Central nervous system Respiratory system, lungs

## SECTION 12: ECOLOGICAL INFORMATION

**Ecotoxicity**

No negative effects on the aquatic environment are known. The product components are not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

**12.1. Toxicity****Acute Toxicity - Fish**

Not determined.

**Acute Toxicity Aquatic Invertebrates**

Not determined.

**Acute Toxicity - Aquatic Plants**

Not determined.

**Acute Toxicity - Microorganisms**

Not determined.

**Acute Toxicity - Terrestrial**

Not determined.

**12.2. Persistence and degradability****Degradability**

This product mainly consists of inorganic compounds which are not biodegradable. The remaining compounds of the product are expected to be easily biodegradable. Volatile substances are degraded in the atmosphere within a few days.

**12.3. Bioaccumulative potential****Bioaccumulative potential**

Bioaccumulation is unlikely to be significant because of the low water solubility of this product.

**Partition coefficient**

Not available.

**12.4. Mobility in soil****Mobility:**

The product contains volatile organic compounds (VOC) which will evaporate easily from all surfaces.

**12.5. Results of PBT and vPvB assessment**

This product does not contain any PBT or vPvB Substances.

**12.6. Other adverse effects**

Not applicable.

## SECTION 13: DISPOSAL CONSIDERATIONS



**(Aerosol) White Gloss****General information**

Do not puncture or incinerate even when empty. Empty aerosols should be recycled where facilities exist. Full or part full aerosols should be disposed of as hazardous waste in accordance with local authority requirements.

**13.1. Waste treatment methods**

Empty containers must not be burned because of explosion hazard. Dispose of waste and residues in accordance with local authority requirements. Do not allow runoff to sewer, waterway or ground. Recover and reclaim or recycle, if practical.

**SECTION 14: TRANSPORT INFORMATION****14.1. UN number**

UN No. Road	1950
UN No. Sea	1950
UN No., Air	1950

**14.2. UN proper shipping name**

Proper Shipping Name	AEROSOLS
----------------------	----------

**14.3. Transport hazard class(es)**

ADR Class No.	2.1
ADR Class	Class 2: Gases
ADR Label No.	2.1
IMDG Class	2.1
ICAO Class	2.1

Transport Labels

**14.4. Packing group**

ADR Pack Group	#
IMDG Pack Gr.	#
Air Pack Gr.	#

**14.5. Environmental hazards**

Environmentally Hazardous Substance/Marine Pollutant  
No.

**14.6. Special precautions for user**

EMS	F-D, S-U
Emergency Action Code	2(Y)
Tunnel Restriction Code	(D)

**14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

Not applicable.

**SECTION 15: REGULATORY INFORMATION**

Poisons Schedule Number	Allocated Poison Schedule Number - 5
-------------------------	--------------------------------------

## (Aerosol) White Gloss

### National Regulations And References

The Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP). National Code of Practice for the Preparation of Material Safety Data Sheets. Approved Criteria for Classifying Hazardous Substances. Exposure Standards for Atmospheric Contaminants in the Occupational Environment. Guidance Note on the Interpretation of Exposure Standards for Atmospheric Contaminants in the Occupational Environment. National Code of Practice for the Labelling of Workplace Substances. National Model Regulations for the Control of Workplace Hazardous Substances. National Code of Practice for the Control of Workplace Hazardous Substances. National Standard for the Storage and Handling of Workplace Dangerous Goods. National Code of Practice for the Storage and Handling of Workplace Dangerous Goods. Guidance Note for Placarding Stores for Dangerous Goods and Specified Hazardous Substances. Guidance Note for the Assessment of Health Risks Arising from Hazardous Substances in the Workplace. National Standard for the Control of Major Hazard Facilities. National Code of Practice for the Control of Major Hazard Facilities.

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU Legislation

Dangerous Preparations Directive 1999/45/EC. Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments. Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 with amendments.

#### Health And Environmental Listings

Regulation EC 689/2008 concerning the export and import of dangerous chemicals.

#### Water hazard classification

WGK 1

### 15.2. Chemical Safety Assessment

No chemical safety assessment has been carried out.

## SECTION 16: OTHER INFORMATION

#### General information

Only trained personnel should use this material.

#### Revision Comments

NOTE: Lines within the margin indicate significant changes from the previous revision. This is first issue.

<b>Revision Date</b>	08/10/2013
<b>Revision</b>	2
<b>Supersedes date</b>	08/09/2011

#### Risk Phrases In Full

R12	Extremely flammable.
R10	Flammable.
R20/21	Harmful by inhalation and in contact with skin.
R20	Harmful by inhalation.
R48/20	Harmful: danger of serious damage to health by prolonged exposure through inhalation.
R65	Harmful: may cause lung damage if swallowed.
R11	Highly flammable
R36	Irritating to eyes.
R38	Irritating to skin.
R63	Possible risk of harm to the unborn child.
R66	Repeated exposure may cause skin dryness or cracking.
R67	Vapours may cause drowsiness and dizziness.

**(Aerosol) White Gloss****Hazard Statements In Full**

EUH066	Repeated exposure may cause skin dryness or cracking.
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H361d	CLP only - Suspected of damaging the unborn child.
H373	May cause damage to organs <<Organs>> through prolonged or repeated exposure.

**Disclaimer**

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.