



Material Safety Data Sheet

Hazardous According To The Criteria Of NOHSC

1 IDENTIFICATION OF THE MATERIAL AND SUPPLIER

<u>Product Name:</u>	Coach Clean
<u>Other Name:</u>	None
<u>Manufacturer's Product Code:</u>	
<u>Recommended Use:</u>	Buffable floor cleaner. Product is used in diluted form.
<u>Supplier Name:</u>	AUTOSMART AUSTRALIA
<u>Supplier Address:</u>	AUTOSMART AUSTRALIA 11 DARRAMBAL CLOSE RATHMINES NSW 2283 www.autosmartaustralia.com.au www.autosmartinternational.com autosmart@autosmartaustralia.com.au
<u>Telephone No.:</u>	02 49 75 14 88 (Mon to Fri, 08:00 – 16:00 AEST) (General Information. Transport Information. Mild medical Information)
<u>Emergency No.:</u>	0011 44 7808 971 321 (24 Hrs) (Autosmart International) 13 11 26 (24 Hours) Poison Information Centre Australia

2 HAZARDS IDENTIFICATION

HAZARD DESIGNATION: Hazardous According To The Criteria Of NOHSC

Hazard Category:	Xi: IRRITANT N: DANGEROUS FOR THE ENVIRONMENT
Risk Phrases:	
R41	Risk of serious damage to eyes
R51/53	Toxic to aquatic organisms, may cause long term adverse effects in the aquatic environment
Safety Phrases:	
S1/2	Keep locked up and out of the reach of children.
S23	Do not breathe vapour/spray.
S24/25	Avoid contact with skin and eyes.
S26	In case of contact with eyes, rinse immediately with plenty of water and seek Medical advice.
S36/37/39	Wear suitable protective clothing, gloves and eye/face protection.
S45	In case of accident or if you feel unwell, seek medical advice immediately (show label where possible).
S46	If swallowed, seek medical advice immediately and show this container or label.
S51	use only in well-ventilated areas.
S57	Use appropriate containment to avoid environmental contamination

ADG CLASSIFICATION:

CLASS 8 "dangerous goods" for transport by road or rail according to the Australian Code for the Transport of Dangerous Good by Road and Rail.

SUSDP CLASSIFICATION:

None

3 COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENT	CAS NUMBER:	PROPORTION (% W/W)
Sodium Hydroxide	1310-73-2	1-5%
Orange Terpene	8028-48-6	10-30%
Fatty Alcohol Ethoxylate	68439-46-3	10-30%
Propan-2-ol	67-63-0	5-10%
Other ingredients determined not to be hazardous		To 100%

4 FIRST AID MEASURES

IF POISONING OCCURS, IMMEDIATELY CONTACT A DOCTOR OR POISONS INFORMATION CENTRE (TELEPHONE 13 11 26), AND FOLLOW THE ADVICE GIVEN. SHOW THIS MATERIAL SAFETY DATA SHEET TO A DOCTOR.

Inhalation: Remove person to fresh air. Rinse nose and mouth. Seek medical advice if symptoms persist.

Skin Contact: Remove all contaminated clothing. Wash the skin with plenty of water. Seek medical attention if discomfort continues. Launder clothing before re-use.

Eye contact: Immediately rinse eyes thoroughly, including under eyelids, with running water for at least 15 minutes. Seek immediate medical advice.

Ingestion: Do NOT induce vomiting. Seek immediate medical advice.

First Aid Facilities: Provide an eyewash station in the workplace.

Symptoms: Not available

Medical attention:**5 FIRE FIGHTING MEASURES**

Extinguishing media: Foam, dry chemical or water spray. Do not use a water jet from a fire hose.

Hazards from combustion products: No data available.

Precautions for fire fighters: Fire fighters should wear full protective clothing and self-contained breathing apparatus. Do not release contaminated water into the environment. Keep intact containers cool by water spray.

ADDITIONAL INFORMATION:

HAZCHEM CODE: 2R

6 ACCIDENTAL RELEASE MEASURES

Wear suitable protective clothing and boots. Prevent spill from entering drains, sewers or any body of water. Contain and absorb with sand, earth or inert absorbent. Scoop or shovel into sealable containers for disposal in accordance with applicable local, state and federal regulations.

Spillage's May Be Slippery.

7 HANDLING AND STORAGE

Handling:

Keep out of reach of children. Avoid contact with skin and eyes and do not inhale spray mist. Use only in a well-ventilated area. Do not apply in the presence of naked flames, hot surfaces or unprotected electrical equipment. Use proper grounding procedures.

Storage:

Store product in the closed, original container in a cool, well-ventilated area away from direct sunlight.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION



Exposure Standards:

Name	Std	TWA - 8 hrs	STEL - 15 min
Propan-2-ol	WEL	200 ppm 999 mg/m ³	500 ppm 1250 mg/m ³

SK – Skin

WEL – Workplace Exposure Limits

T.W.A – The time-weighted average airborne concentration over an eight-hour working day, for five-day working week over an entire working life

S.T.E.L. (Short term Exposure Limit) – the average airborne concentration over a fifteen minute period which should not be exceeded at any time during a normal eight hour working day. According to current knowledge this concentration should neither impair the health of, nor cause undue discomfort to, nearly all workers

Engineering Controls:

Ensure adequate ventilation. Keep container closed when not in use.

Personal Protective Equipment:

EYES:

Avoid contact with eyes. Wear safety goggles.

CLOTHING:

Wear suitable protective clothing.

Protective clothing must be stored separately from private clothing.

GLOVES:

Avoid contact with skin. Wear PVC gloves.

RESPIRATORY:

Wear an approved respirator to prevent inhalation, if other control measures are inadequate.

OTHER:

Do not eat, drink or smoke until after washing. Wash thoroughly after handling. After each day's use wash gloves, goggles and contaminated clothing.

9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Clear yellow gel
Odour:	Citrus
Vapour Pressure:	not relevant.
Vapour Density:	Not available
Boiling Point:	Not available
Freezing/melting point:	Not available
Solubility:	Soluble in Water.
Density:	1.000 @ 20 °C
pH Neat:	Approx. 9.0 (neat)
Flashpoint:	Not relevant
Flammability (explosive) limits:	
Auto-ignition temperature:	
Percent volatiles:	
Octanol/water partition coefficient:	Not available
Formulation:	Water based alkaline detergent cleaner.

10 STABILITY AND REACTIVITY

Chemical stability:	Normally stable
Hazardous polymerisation:	Not available
Conditions to avoid:	Avoid excessive heat for prolonged periods of time
Incompatible materials:	Incompatible with acids and
Hazardous decomposition products:	Not available
Hazardous reactions:	Not available

11 TOXICOLOGICAL INFORMATION

Inhalation: Do not breathe spray. Inhalation of spray may produce respiratory irritation and can result in headaches, dizziness, drowsiness, and possibly nausea.

Skin contact: Irritant to the skin. The material should not be allowed to come into contact with the skin.

Eye contact: Irritant to the eyes. The material should not be allowed to contact the eyes.

Ingestion: May cause discomfort if swallowed. Prolonged inhalation of alkaline mists may cause respiratory irritation resulting in sore throats.

Other: None ANIMAL TOXICITY DATA – PRODUCT: No data available for the product.
ANIMAL TOXICITY DATA – INDIVIDUAL INGREDIENTS:

Acute: Oral toxicity: LD50 rat: Not available

Dermal toxicity: LD50 rabbit: not available

Inhalation toxicity: Irritant

Skin irritation: Irritant

Eye irritation: Irritant

Sensitisation: Not available

Chronic: Chronic effects are not expected to occur with this product.

12 ECOLOGICAL INFORMATION

Fish toxicity:	Orange Terpene LC50 33mg/l
Daphnia toxicity:	Data not available
Toxicity to algae:	Data not available
Bird toxicity:	Data not available
Bee toxicity:	Data not available
Other:	NO data available
Environmental fate, persistence and degradation:	

Degrades rapidly in soil and water.

13 DISPOSAL CONSIDERATIONS

Do not discharge into drains. Do not incinerate. Dispose of waste material via a licensed waste disposal contractor to a regulated landfill.

14 TRANSPORT INFORMATION

UN number: UN 1719
Proper shipping name: CAUSTIC ALKALI LIQUID, N.O.S (Sodium Oleate)
Class and Subsidiary Risk: Class 8 – Corrosive liquid. “dangerous goods” for transport by road or rail according to the Australian Code for the Transport of Dangerous Goods by Road and Rail.
Packing Group: III
EPG: Not applicable
Hazchem code: 2R

15 REGULATORY INFORMATION

No Allocated Poison schedule number

16 OTHER INFORMATION

Preparation information:

Only trained personnel should use this material.

MSDS Issue

Issue	No.3
Prepared:	01/09/2013
Next review date:	01/09/2018
Reason for Update	Review & update

Prepared by Autosmart International, Lynn Lane, Shenstone, Lichfield, Staffordshire, WS14 0DH, Great Britain

www.autosmartinternational.com

rbutler@autosmart.co.uk

Tel: +44 1543 481616

Data Sources and References:

National Code of Practice for the preparation of Material Safety Data Sheets 2nd Edition [NOHSC:2011 (2003)].

Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP) No 23

National code of practice for the storage and handling of Workplace Dangerous Goods [NOHS:2017 (2001)]

National Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHS:21003 (1995)]

Disclaimer:

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.

END OF MSDS