

# Material Safety Data Sheet

Page: 1 of 3

Infosafe No. YSY3Q Issue Date : August 2007 APPROVED by PLESSJAL

Product Name : **MAX CUTTING COMPOUND**

Classified as hazardous according to criteria of NOHSC

## COMPANY DETAILS

**Company Name** Peerless Jal Pty Ltd (ABN 53 006 489 345)  
**Address** 10-12 Raglan Street Preston  
Victoria 3072 Australia  
**Tel/Fax** Tel: (03) 9416 6700 Fax: (03) 9416 8516  
**Other Information** The information in this MSDS was obtained from sources which we believe are reliable. However, the information is provided without warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the material are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising from or in any way connected with the handling, storage, use or disposal of the material.

## IDENTIFICATION

**Product Code** MP 06  
**Product Name** MAX CUTTING COMPOUND  
**Proper Shipping Name** None Allocated  
**UN Number** None Allocated  
**DG Class** None Allocated  
**Packing Group** None Allocated  
**Hazchem Code** None Allocated  
**Poisons Schedule** Not Scheduled  
**Product Use** To be used in conjunction with a buffing machine fitted with a lambswool buffing pad to rejuvenate faded duco and cut and polish acrylic automotive paints.

## Physical Data

**Appearance** Green solid paste with a mineral solvent odour.  
**Boiling Point** >100°C (@ 760mm Hg)  
**Vapour Pressure** Not know  
**Specific Gravity** 1.360 ± 0.005  
**Flash Point** Non-flammable  
**Flamm. Limit LEL** Not applicable  
**Flamm. Limit UEL** Not applicable  
**Solubility in Water** Partially soluble (earth insoluble)

## Other Properties

**Volatile Component** 40.0 - 41.0  
**pH Value** 8.5 - 9.5

## Ingredients

Ingredients	Name	CAS	Proportion	Hazard Symbol	Risk Phrase
	SILICAS	N/A	60-100 %		
	Pine Oil (85% turpine content)	8002-09-3	0-10 %		
	Paraffin oils & Emulsifiers	N/A	0-10 %		
	Water	N/A	To 100%		
	Hydrocarbons	8008-20-6	19.5%		

## HEALTH HAZARD INFORMATION

# Material Safety Data Sheet

Page: 2 of 3

Infosafe No. YSY3Q Issue Date : August 2007 APPROVED by PLESSJAL

Product Name : **MAX CUTTING COMPOUND**

Classified as hazardous according to criteria of NOHSC

## Health Effects

**Acute - Swallowed** Irritation of mouth and intestinal tract. Can result in nausea, vomiting and diarrhoea.  
**Acute - Eye** Possible irritant and abrasive. May cause eye injury.  
**Acute - Skin** Possible irritant. On prolonged or repeater contact may lead to dermatic effects.  
**Acute - Inhaled** Not a likely exposure route.

## First Aid

**Swallowed** Do NOT induce vomiting. Give a glass of water ad contact a doctor or the Poisons Information Centre. Phone 12 11 26.  
**Eye** Do NOT rub eye. Hold eyelids open and flood with water for at least 15 minutes and see a doctor.  
**Skin** Remove contaminated clothing, wash affected area with soap and water.  
**Inhaled** Not applicable

## Advice to Doctor

**Advice to Doctor** Treat symptomatically.

## Other Health Hazard Information

## PRECAUTIONS FOR USE

**Exposure Limits** Not determined for this product.  
**Eng. Controls** Ventilation: No special requirements when used in accordance with directions issued under 'Personal Protection'.

## Personal Protection

**Protective Equip.** Avoid contact with skin and eyes and avoid breathing dust. Dust masks and safety goggles must be worn when buffing off this product.

## Flammability

**Fire Hazards** Not Flammable. SELF EXTINGUISHING using sausage test.

## SAFE HANDLING INFORMATION

## Storage and Transport

**Storage and Transport** No special transporting requirements. Store between 5°C and 35°C.  
**Proper Shipping Name** None Allocated

## Spills and Disposal

**Spills & Disposal** Shovel up excess and rinse residue with water. Consul local authorities regarding disposal.

## Fire/Explosion Hazard

**Fire/Explos. Hazard** No known harmful decomposition products formed. Extinguish small fires with Foam, Dry Chemical or CO2. Fire fighters must use self-contained breathing apparatus on confined or poorly ventilated spaces. Cool intact drums with water spray.  
**Hazchem Code** None Allocated

## OTHER INFORMATION

**Other Information** ID No.: MP06-08

## CONTACT POINT

**Technical Contact Point** Peerless Jal Pty Ltd  
Ph: (03) 9416 6700

# Material Safety Data Sheet

Page: 3 of 3

Infosafe No.	YSY3Q	Issue Date : August 2007	APPROVED by PLESSJAL
--------------	-------	--------------------------	----------------------

Product Name : **MAX CUTTING COMPOUND**

Classified as hazardous according to criteria of NOHSC

---

...End Of MSDS...