



Material Safety Data Sheet

Hazardous According To The Criteria Of NOHSC

1 IDENTIFICATION OF THE MATERIAL AND SUPPLIER

| | |
|--------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <u>Product Name:</u> | Wax Attack |
| <u>Other Name:</u> | None |
| <u>Manufacturer's Product Code:</u> | |
| <u>Recommended Use:</u> | Wax Remover. |
| <u>Supplier Name:</u> | AUTOSMART AUSTRALIA |
| <u>Supplier Address:</u> | AUTOSMART AUSTRALIA 11 DARRAMBAL CLOSE RATHMINES NSW 2283 www.autosmartaustralia.com.au www.autosmartinternational.com autosmart@autosmartaustralia.com.au |
| <u>Telephone No.:</u> | 02 49 75 14 88 (Mon to Fri, 08:00 – 16:00 AEST) (General Information. Transport Information. Mild medical Information) |
| <u>Emergency No.:</u> | 0011 44 7808 971 321 (24 Hrs) (Autosmart International) 131126 (24hrs) Poisons Information Centre Australia |

2 HAZARDS IDENTIFICATION

HAZARD DESIGNATION: Hazardous According To The Criteria Of NOHSC

| | |
|-------------------------|---------------------------------------------------------------------------------------------------------|
| Hazard Category: | FLAMMABLE Xn - HARMFUL |
| Risk Phrases: | |
| R10 | Flammable |
| R36 | irritating to eyes |
| R65 | Harmful: may cause lung damage if swallowed |
| R66 | Repeated exposure may cause skin dryness or cracking |
| Safety Phrases: | |
| S1/2 | Keep locked up and out of the reach of children. |
| S23 | Do not breathe vapour/spray. |
| S24/25 | Avoid contact with skin and eyes. |
| S26 | In case of contact with eyes, rinse immediately with plenty of water and seek Medical advice. |
| S36/37/39 | Wear suitable protective clothing, gloves and eye/face protection. |
| S51 | use only in well-ventilated areas. |
| S45 | In case of accident or if you feel unwell, seek medical advice immediately (show label where possible). |
| S46 | If swallowed, seek medical advice immediately and show this container or label. |

S62 If swallowed, do not induce vomiting: Seek medical advice immediately and show this container or label.

ADG CLASSIFICATION: CLASS 3 “dangerous goods” for transport by road or rail according to the Australian Code for the Transport of Dangerous Good by Road and Rail.

SUSDP CLASSIFICATION: Schedule 5 (Standard for the Uniform Scheduling of Drugs and Poisons)

3 COMPOSITION/INFORMATION ON INGREDIENTS

| INGREDIENT | CAS NUMBER: | PROPORTION (% W/W) |
|--------------------------------------------------|-------------|--------------------|
| Coconut diethanolamide | 8051-30-7 | 1-5% |
| Fatty alcohol ethoxylate | 68439-46-3 | 1-5% |
| Isopropylamine dodecylbenzene sulphonate | 26264-05-1 | 1-5% |
| White spirit | 64742-48-9 | 60-100% |
| Xylene | 1330-20-7 | 5-10% |
| Other ingredients determined not to be hazardous | | To 100% |

4 FIRST AID MEASURES

IF POISONING OCCURS, IMMEDIATELY CONTACT A DOCTOR OR POISONS INFORMATION CENTRE (TELEPHONE 13 11 26), AND FOLLOW THE ADVICE GIVEN. SHOW THIS MATERIAL SAFETY DATA SHEET TO A DOCTOR.

Inhalation: Remove person to fresh air. Keep at rest. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. If breathing has stopped, apply artificial respiration immediately. Seek medical advice.

Skin Contact: If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. Seek medical attention if discomfort continues. Launder clothing before re-use.

Eye contact: Immediately rinse eyes thoroughly, including under eyelids, with running water for at least 15 minutes. Seek immediate medical advice.

Ingestion: Do NOT induce vomiting. Seek immediate medical advice.

First Aid Facilities: Provide an eyewash station in the workplace.

Symptoms: Not available

Medical attention: This product is a hydrocarbon solvent. Small amounts of liquid aspirated into the respiratory system during ingestion or from vomiting may cause bronchopneumonia or pulmonary oedema.

5 FIRE FIGHTING MEASURES

Extinguishing media: Foam, dry chemical or water spray. Do not use a water jet from a fire hose.

Hazards from combustion products: No data available.

Precautions for fire fighters: Extinguish all sources of ignition. This product is a combustible liquid. Fire fighters should wear full protective clothing and self-contained breathing apparatus. Do not release contaminated water into the environment. Keep intact containers cool by spraying with water.

ADDITIONAL INFORMATION:**HAZCHEM CODE:** 3YE**6 ACCIDENTAL RELEASE MEASURES**

Extinguish all sources of ignition. Wear suitable protective clothing and boots. Prevent spill from entering drains, sewers or any body of water. Contain and absorb with sand, earth or inert absorbent. Scoop or shovel into sealable containers for disposal in accordance with applicable local, state and federal regulations.



Spillage's May Be Slippery.

7 HANDLING AND STORAGE**Handling:**

Keep away from heat, sparks, open flame all other sources of ignition. Keep out of reach of children. Avoid contact with skin and eyes and do not inhale spray mist. Use only in a well-ventilated area. Do not apply in the presence of naked flames, hot surfaces or unprotected electrical equipment. Use proper grounding procedures.

Storage:

Store product in the closed, original container in a cool, well-ventilated area away from direct sunlight.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION**Exposure Standards:**

White Spirit LTEL 1000ppm.

Xylene LTEL 220ppm

Engineering Controls:

Ensure adequate ventilation. Keep container closed when not in use.

Personal Protective Equipment:

EYES: Avoid contact with eyes. Wear safety goggles.

CLOTHING: Wear suitable protective clothing. Protective clothing must be stored separately from private clothing.

GLOVES: Avoid contact with skin. Wear PVC gloves.

RESPIRATORY: Wear an approved respirator to prevent inhalation, if other control measures are inadequate.

OTHER: Do not eat, drink or smoke until after washing. Wash thoroughly after handling. After each day's use wash gloves, goggles and contaminated clothing.

9 PHYSICAL AND CHEMICAL PROPERTIES

| | |
|-----------------------------------|--------------------------|
| Appearance: | Liquid |
| Odour: | Solvent |
| Vapour Pressure: | not relevant. |
| Vapour Density: | Not available |
| Boiling Point: | 142 - 200°C |
| Freezing/melting point: | Not available |
| Solubility: | Miscible in Hydrocarbons |
| Density: | 0.800@ 20 °C |
| pH Neat: | Not relevant |
| Flashpoint: | Approx.30 deg/C |
| Flammability | |
| (explosive) limits: | |
| Auto-ignition temperature: | |
| Percent volatiles: | |

Octanol/water partition coefficient: Not available
Formulation: Solvent Degreaser

10 STABILITY AND REACTIVITY

Chemical stability: Normally stable
Hazardous polymerisation: Not available
Conditions to avoid: Avoid excessive heat
Incompatible materials: Incompatible with strong oxidising agents
Hazardous decomposition products: Carbon Monoxide
Hazardous reactions: Not available

11 TOXICOLOGICAL INFORMATION

Inhalation:

Harmful: may cause lung damage if swallowed. Do not breathe vapour / spray / fumes. Inhalation of spray may produce respiratory irritation and can result in headaches, dizziness, drowsiness, and possibly nausea.

Skin contact:

Mild irritant and drying to the skin. The material should not be allowed to come into contact with the skin.

Eye contact:

The material should not be allowed to contact the eyes.

Ingestion:

Aspiration of product into the lungs can cause fatal chemical pneumonitis.

Other: None ANIMAL TOXICITY DATA – PRODUCT: No data available for the product. ANIMAL TOXICITY DATA – INDIVIDUAL INGREDIENTS:

Acute: Oral toxicity: LD50 rat: White Spirit >2000mg/kg
 Xylene 4300mg/kg

Dermal toxicity: LD50 rabbit: White Spirit >2000mg/kg

Inhalation toxicity: White Spirit > 5000mg/m³

Skin irritation: Mild irritant

Eye irritation: Mild irritant

Sensitisation: Moderate skin sensitiser

Chronic:

12 ECOLOGICAL INFORMATION

Fish toxicity: White Spirit LC50 >100mg/l
 Xylene LC50 (96hr) 2.6-8.4mg/l

Daphnia toxicity: Xylene EC50 (24hr) 1.0-4.7mg/l

Toxicity to algae: Data not available

Bird toxicity: Data not available

Bee toxicity: Data not available

Other: No data available

Environmental fate, persistence and degradation:

Degrades rapidly in soil, air and water.

13 DISPOSAL CONSIDERATIONS

Do not discharge into drains. Do not incinerate. Dispose of waste material via a licensed waste disposal contractor.

14 TRANSPORT INFORMATION

UN number: 1993
Proper shipping name: FLAMMABLE LIQUIDS, N.O.S (White Spirit, Xylene)
Class and Subsidiary Risk: CLASS 3 “dangerous goods” for transport by road or rail according to the Australian Code for the Transport of Dangerous Goods by Road and Rail.
Packing Group: III
EPG: Not applicable
Hazchem code: 3YE

15 REGULATORY INFORMATION

Allocated Poison schedule number 5.

16 OTHER INFORMATION**Preparation information:**

Only trained personnel should use this material.

MSDS Issue

| | |
|-------------------|-----------------|
| Issue | No.3 |
| Prepared: | 01/09/2013 |
| Next review date: | 01/09/2018 |
| Reason for Update | Review & update |

Prepared by Autosmart International, Lynn Lane, Shenstone, Lichfield, Staffordshire, WS14 0DH, Great Britain

www.autosmartinternational.com

rbutler@autosmart.co.uk

Tel: +44 1543 481616

Data Sources and References:

National Code of Practice for the preparation of Material Safety Data Sheets 2nd Edition [NOHSC:2011 (2003)].
 Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP) No 23
 National code of practice for the storage and handling of Workplace Dangerous Goods [NOHS:2017 (2001)]
 National Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHS:21003 (1995)]

Disclaimer:

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.

END OF MSDS