



## SAFETY DATA SHEET

### Aquaseal SiO2

According to Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice, February 2016

#### SECTION 1: Identification: Product identifier and chemical identity

##### Product identifier

**Product name** Aquaseal SiO2

##### Relevant identified uses of the substance or mixture and uses advised against

**Application** Car maintenance product.

**Uses advised against** For professional use only. This product is not recommended for any industrial, professional or consumer use other than the Identified uses above.

##### Details of the supplier of the safety data sheet

**Supplier** Autosmart Australia  
11 Darrambal Close  
Rathmines  
NSW 2283  
Australia  
www.autosmartaustralia.com.au  
Tel: 02 49 75 14 88 (Mon to Fri, 08:00 - 16:00 AEST) (General Information. Transport Information. Mild Medical Information)  
autosmart@autosmartaustralia.com.au

**Contact Person** Mr. Russell Butler

##### Emergency telephone number

**Emergency telephone** Emergency No: +44 7808 971321 (24hrs) (Autosmart International, UK)  
General Information. Transport Information. Mild medical Information:-  
Tel: 02 49 75 14 88 (Mon to Fri, 08:00 - 16:00 AEST)

**National emergency telephone number** Poison Information Hotline: 13 11 26

#### SECTION 2: Hazard(s) identification

##### Classification of the substance or mixture

**Physical hazards** Not Classified

**Health hazards** Skin Corr. 1B - H314 Eye Dam. 1 - H318 STOT SE 3 - H336

**Environmental hazards** Not Classified

##### Label elements

##### Hazard pictograms



**Signal word** DANGER

## Aquaseal SiO<sub>2</sub>

<b>Hazard statements</b>	H314 Causes severe skin burns and eye damage. H336 May cause drowsiness or dizziness.
<b>Precautionary statements</b>	P260 Do not breathe vapour/ spray. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P363 Wash contaminated clothing before reuse. P501 Dispose of contents/ container in accordance with national regulations.
<b>Contains</b>	Isopropyl alcohol, Siloxanes and Silicones, 3-[(2-aminoethyl)amino]propyl Me, di-Me

### Other hazards

This product does not contain any substances classified as PBT (persistent, bioaccumulative and toxic) or vPvB (very persistent and very bioaccumulative).

## SECTION 3: Composition and information on ingredients

### Mixtures

<b>Isopropyl alcohol</b> <span style="float: right;"><b>20&lt;30%</b></span>
CAS number: 67-63-0 Substance with a Community workplace exposure limit.
<b>Classification</b> Flam. Liq. 2 - H225 Eye Irrit. 2A - H319 STOT SE 3 - H336
<b>Siloxanes and Silicones, 3-[(2-aminoethyl)amino]propyl Me, di-Me</b> <span style="float: right;"><b>5&lt;10%</b></span>
CAS number: —
<b>Classification</b> Skin Corr. 1B - H314 Eye Dam. 1 - H318

The full text for all hazard statements is displayed in Section 16.

## SECTION 4: First aid measures

### Description of first aid measures

<b>General information</b>	Get medical attention immediately. Show this Safety Data Sheet to the medical personnel. Chemical burns must be treated by a physician.
<b>Inhalation</b>	Remove affected person from source of contamination. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Maintain an open airway. Loosen tight clothing such as collar, tie or belt. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Place unconscious person on their side in the recovery position and ensure breathing can take place.

## Aquaseal SiO<sub>2</sub>

<b>Ingestion</b>	Rinse mouth thoroughly with water. Remove any dentures. Give a few small glasses of water or milk to drink. Stop if the affected person feels sick as vomiting may be dangerous. Do not induce vomiting unless under the direction of medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Place unconscious person on their side in the recovery position and ensure breathing can take place. Maintain an open airway. Loosen tight clothing such as collar, tie or belt.
<b>Skin Contact</b>	It is important to remove the substance from the skin immediately. Take off immediately all contaminated clothing. Rinse immediately with plenty of water. Continue to rinse for at least 15 minutes and get medical attention. Chemical burns must be treated by a physician.
<b>Eye contact</b>	Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 10 minutes.
<b>Protection of first aiders</b>	First aid personnel should wear appropriate protective equipment during any rescue. If it is suspected that volatile contaminants are still present around the affected person, first aid personnel should wear an appropriate respirator or self-contained breathing apparatus. Wash contaminated clothing thoroughly with water before removing it from the affected person, or wear gloves. It may be dangerous for first aid personnel to carry out mouth-to-mouth resuscitation.

### Most important symptoms and effects, both acute and delayed

<b>General information</b>	See Section 11 for additional information on health hazards. The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
<b>Inhalation</b>	A single exposure may cause the following adverse effects: Severe irritation of nose and throat. Symptoms following overexposure may include the following: Corrosive to the respiratory tract.
<b>Ingestion</b>	May cause chemical burns in mouth, oesophagus and stomach. Symptoms following overexposure may include the following: Severe stomach pain. Nausea, vomiting.
<b>Skin contact</b>	Causes severe burns. Symptoms following overexposure may include the following: Pain or irritation. Redness. Blistering may occur.
<b>Eye contact</b>	Causes serious eye damage. Symptoms following overexposure may include the following: Pain. Profuse watering of the eyes. Redness.

### Indication of any immediate medical attention and special treatment needed

<b>Notes for the doctor</b>	Treat symptomatically.
-----------------------------	------------------------

### **SECTION 5: Firefighting measures**

#### Extinguishing media

<b>Suitable extinguishing media</b>	The product is not flammable. Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire-extinguishing media suitable for the surrounding fire.
<b>Unsuitable extinguishing media</b>	Do not use water jet as an extinguisher, as this will spread the fire.

#### Special hazards arising from the substance or mixture

<b>Specific hazards</b>	Containers can burst violently or explode when heated, due to excessive pressure build-up. Severe corrosive hazard. Water used for fire extinguishing, which has been in contact with the product, may be corrosive.
<b>Hazardous combustion products</b>	Thermal decomposition or combustion products may include the following substances: Very toxic or corrosive gases or vapours.

## Aquaseal SiO<sub>2</sub>

### Advice for firefighters

#### **Protective actions during firefighting**

Avoid breathing fire gases or vapours. Evacuate area. Keep upwind to avoid inhalation of gases, vapours, fumes and smoke. Ventilate closed spaces before entering them. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapours and protect men stopping the leak. Avoid discharge to the aquatic environment. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.

#### **Special protective equipment for firefighters**

Regular protection may not be safe. Wear chemical protective suit. Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing conforming to Australia/New Zealand Standards AS/NZS 4967 (for clothing) AS/NZS 1801 (for helmets), AS/NZS 4821 (for protective boots), AS/NZS 1801 (for protective gloves) will provide a basic level of protection for chemical incidents.

#### **Hazchem Code**

2X

### **SECTION 6: Accidental release measures**

#### **Personal precautions, protective equipment and emergency procedures**

##### **Personal precautions**

No action shall be taken without appropriate training or involving any personal risk. Keep unnecessary and unprotected personnel away from the spillage. Wear protective clothing as described in Section 8 of this safety data sheet. Follow precautions for safe handling described in this safety data sheet. Wash thoroughly after dealing with a spillage. Ensure procedures and training for emergency decontamination and disposal are in place. Do not touch or walk into spilled material. Avoid inhalation of vapours and spray/mists. Use suitable respiratory protection if ventilation is inadequate. Avoid contact with skin and eyes. Avoid contact with contaminated tools and objects.

#### **Environmental precautions**

##### **Environmental precautions**

The product may affect the acidity (pH) of water which may have hazardous effects on aquatic organisms. Avoid discharge to the aquatic environment. Large Spillages: Inform the relevant authorities if environmental pollution occurs (sewers, waterways, soil or air).

#### **Methods and material for containment and cleaning up**

##### **Methods for cleaning up**

Wear protective clothing as described in Section 8 of this safety data sheet. Clear up spills immediately and dispose of waste safely. This product is corrosive. Approach the spillage from upwind. Small Spillages: If the product is soluble in water, dilute the spillage with water and mop it up. Alternatively, or if it is not water-soluble, absorb the spillage with an inert, dry material and place it in a suitable waste disposal container. Large Spillages: If leakage cannot be stopped, evacuate area. Flush spilled material into an effluent treatment plant, or proceed as follows. Contain and absorb spillage with sand, earth or other non-combustible material. Place waste in labelled, sealed containers. Clean contaminated objects and areas thoroughly, observing environmental regulations. The contaminated absorbent may pose the same hazard as the spilled material. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage. Neutralise with alkali. Caution. May generate heat. Following dilution and neutralisation, discharge to the sewer with plenty of water may be permitted. The requirements of the local water authority must be complied with if contaminated water is flushed directly to the sewer. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

#### **Reference to other sections**

##### **Reference to other sections**

For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

## Aquaseal SiO<sub>2</sub>

### SECTION 7: Handling and storage, including how the chemical may be safely used

#### Precautions for safe handling

##### **Usage precautions**

Read and follow manufacturer's recommendations. Wear protective clothing as described in Section 8 of this safety data sheet. Keep away from food, drink and animal feeding stuffs. Handle all packages and containers carefully to minimise spills. Keep container tightly sealed when not in use. Avoid the formation of mists. This product is corrosive. Immediate first aid is imperative. Do not handle until all safety precautions have been read and understood. Do not handle broken packages without protective equipment. Do not reuse empty containers.

##### **Advice on general occupational hygiene**

Wash promptly if skin becomes contaminated. Take off contaminated clothing and wash before reuse. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Wash at the end of each work shift and before eating, smoking and using the toilet. Change work clothing daily before leaving workplace.

#### Conditions for safe storage, including any incompatibilities

##### **Storage precautions**

Store away from incompatible materials (see Section 10). Store in accordance with local regulations. Store away from the following materials: Alkalis. Keep only in the original container. Keep container tightly closed, in a cool, well ventilated place. Keep containers upright. Protect containers from damage. Bund storage facilities to prevent soil and water pollution in the event of spillage. The storage area floor should be leak-tight, jointless and not absorbent.

##### **Storage class**

Corrosive storage.

##### **Specific end use(s)**

##### **Specific end use(s)**

The identified uses for this product are detailed in Section 1.

### SECTION 8: Exposure controls and personal protection

#### Control parameters

#### Occupational exposure limits

##### **Isopropyl alcohol**

Long-term exposure limit (8-hour TWA): 400 ppm 983 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): 500 ppm 1230 mg/m<sup>3</sup>

#### Exposure controls

##### **Protective equipment**



##### **Appropriate engineering controls**

Provide adequate ventilation. Personal, workplace environment or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Use process enclosures, local exhaust ventilation or other engineering controls as the primary means to minimise worker exposure. Personal protective equipment should only be used if worker exposure cannot be controlled adequately by the engineering control measures. Ensure control measures are regularly inspected and maintained. Ensure operatives are trained to minimise exposure.

##### **Eye/face protection**

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Personal protective equipment for eye and face protection should comply with Australia/New Zealand Standard AS/NZS 1337. Wear tight-fitting, chemical splash goggles or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

## Aquaseal SiO<sub>2</sub>

<b>Hand protection</b>	Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. To protect hands from chemicals, gloves should comply with Australia/New Zealand Standard AS/NZS 2161. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. Frequent changes are recommended.
<b>Other skin and body protection</b>	Appropriate footwear and additional protective clothing complying with an approved standard should be worn if a risk assessment indicates skin contamination is possible.
<b>Hygiene measures</b>	Provide eyewash station and safety shower. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Clean equipment and the work area every day. Good personal hygiene procedures should be implemented. Wash at the end of each work shift and before eating, smoking and using the toilet. When using do not eat, drink or smoke. Preventive industrial medical examinations should be carried out. Warn cleaning personnel of any hazardous properties of the product.
<b>Respiratory protection</b>	Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible. Ensure all respiratory protective equipment is suitable for its intended use and complies with Australia/New Zealand Standard AS/NZS 1716. Check that the respirator fits tightly and the filter is changed regularly. Gas and combination filter cartridges should comply with Australia/New Zealand Standard AS/NZS 1716. Full face mask respirators with replaceable filter cartridges should comply with Australia/New Zealand Standard AS/NZS 1716. Half mask and quarter mask respirators with replaceable filter cartridges should comply with Australia/New Zealand Standard AS/NZS 1716.
<b>Environmental exposure controls</b>	Keep container tightly sealed when not in use. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels. Store in a demarcated bunded area to prevent release to drains and/or watercourses.

### SECTION 9: Physical and chemical properties

#### Information on basic physical and chemical properties

<b>Appearance</b>	Liquid.
<b>Colour</b>	Blue.
<b>Odour</b>	Apple.
<b>pH</b>	pH (concentrated solution): 5.5 - 6.5
<b>Initial boiling point and range</b>	98-103°C
<b>Flash point</b>	~ 71°C Closed cup.
<b>Relative density</b>	~ 0.995
<b>Solubility(ies)</b>	Miscible with water.
<b>Comments</b>	Information declared as "Not available" or "Not applicable" is not considered to be relevant to the implementation of the proper control measures.
<b>Other information</b>	No information required.

### SECTION 10: Stability and reactivity

## Aquaseal SiO2

<b>Reactivity</b>	See the other subsections of this section for further details.
<b>Stability</b>	Stable at normal ambient temperatures and when used as recommended. Stable under the prescribed storage conditions.
<b>Possibility of hazardous reactions</b>	No potentially hazardous reactions known.
<b>Conditions to avoid</b>	There are no known conditions that are likely to result in a hazardous situation.
<b>Materials to avoid</b>	Alkalis. Amines.
<b>Hazardous decomposition products</b>	Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Corrosive gases or vapours.

### SECTION 11: Toxicological information

#### Information on toxicological effects

##### Acute toxicity - oral

**Notes (oral LD<sub>50</sub>)** Based on available data the classification criteria are not met.

##### Acute toxicity - dermal

**Notes (dermal LD<sub>50</sub>)** Based on available data the classification criteria are not met.

##### Acute toxicity - inhalation

**Notes (inhalation LC<sub>50</sub>)** Based on available data the classification criteria are not met.

##### Skin corrosion/irritation

**Animal data** Skin Corr. 1B - H314 Causes severe burns.

##### Serious eye damage/irritation

**Serious eye damage/irritation** Eye Dam. 1 - H318 Corrosive to skin. Corrosivity to eyes is assumed.

##### Respiratory sensitisation

**Respiratory sensitisation** Based on available data the classification criteria are not met.

##### Skin sensitisation

**Skin sensitisation** Based on available data the classification criteria are not met.

##### Germ cell mutagenicity

**Genotoxicity - in vitro** Based on available data the classification criteria are not met.

##### Carcinogenicity

**Carcinogenicity** Based on available data the classification criteria are not met.

##### **IARC carcinogenicity**

IARC Group 3 Not classifiable as to its carcinogenicity to humans.

##### Reproductive toxicity

**Reproductive toxicity - fertility** Based on available data the classification criteria are not met.

**Reproductive toxicity - development**

Based on available data the classification criteria are not met.

##### Specific target organ toxicity - single exposure

**STOT - single exposure** STOT SE 3 - H336 May cause drowsiness or dizziness.

**Target organs**

Central nervous system

##### Specific target organ toxicity - repeated exposure

## Aquaseal SiO<sub>2</sub>

<b>STOT - repeated exposure</b>	Not classified as a specific target organ toxicant after repeated exposure.
<b><u>Aspiration hazard</u></b>	
<b>Aspiration hazard</b>	Based on available data the classification criteria are not met.
<b>General information</b>	
	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
<b>Inhalation</b>	Corrosive to the respiratory tract. Symptoms following overexposure may include the following: Severe irritation of nose and throat.
<b>Ingestion</b>	May cause chemical burns in mouth, oesophagus and stomach. Symptoms following overexposure may include the following: Severe stomach pain. Nausea, vomiting.
<b>Skin Contact</b>	Causes severe burns. Symptoms following overexposure may include the following: Pain or irritation. Redness. Blistering may occur.
<b>Eye contact</b>	Causes serious eye damage. Symptoms following overexposure may include the following: Pain. Profuse watering of the eyes. Redness.
<b>Route of exposure</b>	Ingestion Inhalation Skin and/or eye contact
<b>Target Organs</b>	Central nervous system

### Toxicological information on ingredients.

#### Isopropyl alcohol

##### Acute toxicity - oral

**Acute toxicity oral (LD<sub>50</sub> mg/kg)** 5,840.0

**Species** Rat

**Notes (oral LD<sub>50</sub>)** Based on available data the classification criteria are not met.

##### Acute toxicity - dermal

**Acute toxicity dermal (LD<sub>50</sub> mg/kg)** 16.4

**Species** Rabbit

**Notes (dermal LD<sub>50</sub>)** Based on available data the classification criteria are not met.

##### Acute toxicity - inhalation

**Notes (inhalation LC<sub>50</sub>)** Based on available data the classification criteria are not met.

##### Skin corrosion/irritation

**Animal data** Based on available data the classification criteria are not met.

##### Serious eye damage/irritation

**Serious eye damage/irritation** Causes serious eye irritation.

##### Respiratory sensitisation

**Respiratory sensitisation** Based on available data the classification criteria are not met.

##### Skin sensitisation

**Skin sensitisation** Based on available data the classification criteria are not met.



## Aquaseal SiO<sub>2</sub>

### Germ cell mutagenicity

**Genotoxicity - in vitro** Based on available data the classification criteria are not met.

### Carcinogenicity

**Carcinogenicity** Based on available data the classification criteria are not met.

**IARC carcinogenicity** IARC Group 3 Not classifiable as to its carcinogenicity to humans.

### Reproductive toxicity

**Reproductive toxicity - fertility** Based on available data the classification criteria are not met.

**Reproductive toxicity - development** Based on available data the classification criteria are not met.

### Specific target organ toxicity - single exposure

**STOT - single exposure** STOT SE 3 - H336 May cause drowsiness or dizziness.

**Target organs** Central nervous system

### Specific target organ toxicity - repeated exposure

**STOT - repeated exposure** Not classified as a specific target organ toxicant after repeated exposure.

### Aspiration hazard

**Aspiration hazard** Based on available data the classification criteria are not met. Entry into the lungs following ingestion or vomiting may cause chemical pneumonitis.

### **General information**

The severity of the symptoms described will vary dependent on the concentration and the length of exposure.

### **Inhalation**

A single exposure may cause the following adverse effects: Headache. Nausea, vomiting. Central nervous system depression. Drowsiness, dizziness, disorientation, vertigo. Narcotic effect.

### **Ingestion**

A single exposure may cause the following adverse effects: Confusion, agitation and/or excitation. Symptoms following overexposure may include the following: May cause nausea, headache, dizziness and intoxication. Unconsciousness.

### **Skin Contact**

A single exposure may cause the following adverse effects: Temporary irritation. Prolonged contact may cause dryness of the skin.

### **Eye contact**

Irritating to eyes.

### **Route of exposure**

Ingestion Inhalation Skin and/or eye contact

### **Target Organs**

Central nervous system

### Siloxanes and Silicones, 3-[(2-aminoethyl)amino]propyl Me, di-Me

### Acute toxicity - oral

**Acute toxicity oral (LD<sub>50</sub> mg/kg)** 2,001.0

**Species** Rat

**ATE oral (mg/kg)** 2,001.0

### Acute toxicity - dermal

## Aquaseal SiO<sub>2</sub>

**Summary** Based on available data the classification criteria are not met.

### Acute toxicity - inhalation

**Summary** Based on available data the classification criteria are not met.

### Skin corrosion/irritation

**Skin corrosion/irritation** Corrosive to skin.

### Serious eye damage/irritation

**Serious eye damage/irritation** Corrosivity to eyes is assumed.

### Respiratory sensitisation

**Respiratory sensitisation** Not sensitising.

### Skin sensitisation

**Skin sensitisation** Not sensitising.

### Germ cell mutagenicity

**Summary** Based on available data the classification criteria are not met.

### Carcinogenicity

**Carcinogenicity** Based on available data the classification criteria are not met.

### Reproductive toxicity

**Summary** Based on available data the classification criteria are not met.

### Specific target organ toxicity - single exposure

**STOT - single exposure** Based on available data the classification criteria are not met.

### Specific target organ toxicity - repeated exposure

**STOT - repeated exposure** Based on available data the classification criteria are not met.

### Aspiration hazard

**Aspiration hazard** Based on available data the classification criteria are not met.

## SECTION 12: Ecological information

**Ecotoxicity** Not regarded as dangerous for the environment. However, large or frequent spills may have hazardous effects on the environment.

### Ecological information on ingredients.

#### Isopropyl alcohol

**Ecotoxicity** Not regarded as dangerous for the environment. However, large or frequent spills may have hazardous effects on the environment.

#### Siloxanes and Silicones, 3-[(2-aminoethyl)amino]propyl Me, di-Me

**Ecotoxicity** The product does not contain organically bound halogen.

**Toxicity** Based on available data the classification criteria are not met.

### Ecological information on ingredients.

#### Isopropyl alcohol

## Aquaseal SiO2

<b>Toxicity</b>	Based on available data the classification criteria are not met.
<b><u>Acute aquatic toxicity</u></b>	
<b>Acute toxicity - fish</b>	LC50, 96 hours: ~ 9640 mg/l, Pimephales promelas (Fat-head Minnow)
<b>Acute toxicity - aquatic invertebrates</b>	EC <sub>50</sub> , >: > 1000 mg/l, Daphnia magna
<b>Acute toxicity - aquatic plants</b>	EC <sub>50</sub> , 72 hours: > 1000 mg/l, Scenedesmus subspicatus
<b>Acute toxicity - microorganisms</b>	EC <sub>50</sub> , >: > 1000 mg/l, Activated sludge

### Siloxanes and Silicones, 3-[(2-aminoethyl)amino]propyl Me, di-Me

<b><u>Acute aquatic toxicity</u></b>	
<b>Acute toxicity - fish</b>	Not available.

### Persistence and degradability

**Persistence and degradability** The degradability of the product is not known.

### Ecological information on ingredients.

#### Isopropyl alcohol

<b>Persistence and degradability</b>	The product is readily biodegradable.
<b>Biodegradation</b>	Degradation (%) - 95: 21 days
<b>Biological oxygen demand</b>	~ 1171 g O <sub>2</sub> /g substance
<b>Chemical oxygen demand</b>	~ 2294 g O <sub>2</sub> /g substance

### Siloxanes and Silicones, 3-[(2-aminoethyl)amino]propyl Me, di-Me

<b>Persistence and degradability</b>	There are no data on the degradability of this product.
--------------------------------------	---

### Bioaccumulative potential

**Bioaccumulative Potential** No data available on bioaccumulation.

### Ecological information on ingredients.

#### Isopropyl alcohol

<b>Bioaccumulative Potential</b>	No data available on bioaccumulation.
<b>Partition coefficient</b>	log Pow: 0.05

### Siloxanes and Silicones, 3-[(2-aminoethyl)amino]propyl Me, di-Me

**Bioaccumulative Potential** No data available on bioaccumulation.

### Mobility in soil

**Mobility** The product is water-soluble and may spread in water systems. The product is non-volatile.

### Ecological information on ingredients.

## Aquaseal SiO<sub>2</sub>

### Isopropyl alcohol

<b>Mobility</b>	The product is water-soluble and may spread in water systems. Volatile liquid. The product contains organic solvents which will evaporate easily from all surfaces.
<b>Adsorption/desorption coefficient</b>	Water - Koc: ~ 1.1 @ °C
<b>Henry's law constant</b>	0.00000338 atm m <sup>3</sup> /mol @ 25°C

### Siloxanes and Silicones, 3-[(2-aminoethyl)amino]propyl Me, di-Me

<b>Mobility</b>	No data available.
-----------------	--------------------

#### Other adverse effects

<b>Other adverse effects</b>	None known.
------------------------------	-------------

#### Ecological information on ingredients.

### Isopropyl alcohol

<b>Other adverse effects</b>	None known.
------------------------------	-------------

### Siloxanes and Silicones, 3-[(2-aminoethyl)amino]propyl Me, di-Me

<b>Other adverse effects</b>	None known.
------------------------------	-------------

## SECTION 13: Disposal considerations

### Waste treatment methods

<b>General information</b>	The generation of waste should be minimised or avoided wherever possible. Reuse or recycle products wherever possible. This material and its container must be disposed of in a safe way. Disposal of this product, process solutions, residues and by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements. When handling waste, the safety precautions applying to handling of the product should be considered. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out. Empty containers or liners may retain some product residues and hence be potentially hazardous.
----------------------------	--

<b>Disposal methods</b>	Do not empty into drains. Dispose of surplus products and those that cannot be recycled via a licensed waste disposal contractor. Waste, residues, empty containers, discarded work clothes and contaminated cleaning materials should be collected in designated containers, labelled with their contents. Incineration or landfill should only be considered when recycling is not feasible.
-------------------------	--

## SECTION 14: Transport information

<b>General</b>	For limited quantity packaging/limited load information, consult the relevant modal documentation using the data shown in this section.
----------------	---

### UN number

<b>UN No. (ADG)</b>	1760
<b>UN No. (IMDG)</b>	1760
<b>UN No. (ICAO)</b>	1760

### UN proper shipping name

## Aquaseal SiO2

**Proper shipping name (ADG)** CORROSIVE LIQUID, N.O.S. (CONTAINS Siloxanes and Silicones, 3-[(2-aminoethyl)amino]propyl Me, di-Me)

**Proper shipping name (IMDG)** CORROSIVE LIQUID, N.O.S. (CONTAINS Siloxanes and Silicones, 3-[(2-aminoethyl)amino]propyl Me, di-Me)

**Proper shipping name (ICAO)** CORROSIVE LIQUID, N.O.S. (CONTAINS Siloxanes and Silicones, 3-[(2-aminoethyl)amino]propyl Me, di-Me)

### Transport hazard class(es)

<b>ADG class</b>	8
<b>ADG classification code</b>	C9
<b>ADG label</b>	8
<b>IMDG class</b>	8
<b>ICAO class/division</b>	8

### Transport labels



### Packing group

<b>ADG packing group</b>	II
<b>IMDG packing group</b>	II
<b>ICAO packing group</b>	II

### Environmental hazards

**Environmentally hazardous substance/marine pollutant**

No.

### Special precautions for user

Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**EmS** F-A, S-B

**Hazchem Code** 2X

**Transport in bulk according to** Not applicable.

**Annex II of MARPOL 73/78  
and the IBC Code**

## SECTION 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

## Aquaseal SiO2

<b>National regulations</b>	<p>The Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).          National Code of Practice for the Preparation of Material Safety Data Sheets.          Approved Criteria for Classifying Hazardous Substances.          Exposure Standards for Atmospheric Contaminants in the Occupational Environment.          Guidance Note on the Interpretation of Exposure Standards for Atmospheric Contaminants in the Occupational Environment.          National Code of Practice for the Labelling of Workplace Substances.          National Model Regulations for the Control of Workplace Hazardous Substances.          National Code of Practice for the Control of Workplace Hazardous Substances.          National Standard for the Storage and Handling of Workplace Dangerous Goods.          National Code of Practice for the Storage and Handling of Workplace Dangerous Goods.          Guidance Note for Placarding Stores for Dangerous Goods and Specified Hazardous Substances. Guidance Note for the Assessment of Health Risks Arising from Hazardous Substances in the Workplace.          National Standard for the Control of Major Hazard Facilities. National Code of Practice for the Control of Major Hazard Facilities.</p>
-----------------------------	---

**Schedule (SUSMP)** No Poison Schedule number allocated

### Inventories

#### **Australia - AICS**

All the ingredients are listed or exempt.

<b>SECTION 16: Any other relevant information</b>
---

**Abbreviations and acronyms used in the safety data sheet** ADG: Australian dangerous goods code

IATA: International air transport association.  
 ICAO: Technical instructions for the safe transport of dangerous goods by air.  
 IMDG: International maritime dangerous goods.  
 CAS: Chemical abstracts service.  
 ATE: Acute toxicity estimate.  
 LC<sub>50</sub>: Lethal concentration to 50 % of a test population.  
 LD<sub>50</sub>: Lethal dose to 50% of a test population (median lethal dose).  
 EC<sub>50</sub>: 50% of maximal effective concentration.  
 PBT: Persistent, bioaccumulative and toxic substance.  
 vPvB: Very persistent and very bioaccumulative.

**Classification abbreviations and acronyms** Eye Dam. = Serious eye damage  
 Skin Corr. = Skin corrosion  
 STOT SE = Specific target organ toxicity-single exposure

**Training advice** Read and follow manufacturer's recommendations. Only trained personnel should use this material.

**Revision comments** NOTE: Lines within the margin indicate significant changes from the previous revision.

**Issued by** Prepared by Autosmart International Ltd, Lynn Lane, Shenstone, Lichfield, Staffordshire, WS14 0DH, Great Britain.  
 www.autosmartinternational.com  
 rbutler@autosmart.co.uk  
 Tel +44 (0)1543 481616

**Revision date** 1/07/2021

**Revision** 1

## Aquaseal SiO2

<b>SDS No.</b>	22107
<b>SDS status</b>	Approved.
<b>Hazard statements in full</b>	H225 Highly flammable liquid and vapour. H314 Causes severe skin burns and eye damage. H318 Causes serious eye damage. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.