



## SAFETY DATA SHEET (Aerosol) Silver Seal Paint Protector

According to the Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practise, 2021.

### SECTION 1: Identification: Product identifier and chemical identity

#### Product identifier

**Product name** (Aerosol) Silver Seal Paint Protector

**Product No.** A83-11

#### Relevant identified uses of the substance or mixture and uses advised against

**Application** Car maintenance product. - Paint protector

**Uses advised against** For professional use only. This product is not recommended for any industrial, professional or consumer use other than the Identified uses above.

#### Details of the supplier of the safety data sheet

**Supplier** Autosmart Australia  
11 Darrambal Close  
Rathmines  
NSW 2283  
Australia  
[www.autosmartaustralia.com.au](http://www.autosmartaustralia.com.au)  
Tel: 02 49 75 14 88 (Mon to Fri, 08:00 - 16:00 AEST) (General Information. Transport Information. Mild Medical Information)  
[autosmart@autosmartaustralia.com.au](mailto:autosmart@autosmartaustralia.com.au)

**Contact Person** Mr. Russell Butler

**Manufacturer** Autosmart International Ltd..  
Lynn Lane  
Shenstone, nr Lichfield  
Staffordshire WS14 0DH  
Great Britain  
[www.autosmartinternational.com](http://www.autosmartinternational.com)  
Tel: +44 (0) 1543 481616 (09:00 - 17:00)  
Fax: +44 (0) 1543 481549 (09:00 - 17:00)  
[info@autosmartinternational.com](mailto:info@autosmartinternational.com)

#### Emergency telephone number

**Emergency telephone** NCEC - For Chemical Emergency Support ONLY (spill, leak, fire, exposure or accident), Call NCEC at 18000 74234 (toll free 24Hrs) - when calling please quote "AUTOSMART 29003-NCEC"  
Local number +61 2 8 014 4558  
General Information. Transport Information. Mild medical Information:-  
Tel: 02 49 75 14 88 (Mon to Fri, 08:00 - 16:00 AEST)

**National emergency telephone number** Poison Information Hotline: 13 11 26

### SECTION 2: Hazard(s) identification

#### Classification of the substance or mixture

**(Aerosol) Silver Seal Paint Protector****Physical hazards** Aerosol 1 - H222, H229 Press. Gas, Compressed - H280**Health hazards** STOT SE 3 - H336**Environmental hazards** Aquatic Acute 3 - H402 Aquatic Chronic 3 - H412**Label elements****Hazard pictograms****Signal word** DANGER

**Hazard statements**

H229 Pressurised container: may burst if heated.  
 H280 Contains gas under pressure; may explode if heated.  
 H336 May cause drowsiness or dizziness.  
 H412 Harmful to aquatic life with long lasting effects.

**Precautionary statements**

P210 Keep away from heat/ sparks/ open flames/ hot surfaces. - No smoking.  
 P211 Do not spray on an open flame or other ignition source.  
 P251 Pressurized container: Do not pierce or burn, even after use.  
 P261 Avoid breathing vapour/ spray.  
 P280 Wear protective gloves.  
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

**Supplemental label information**

EUH066 Repeated exposure may cause skin dryness or cracking.  
 For professional users only.  
 AUH066 Repeated exposure may cause skin dryness or cracking.

**Contains** Naphtha (petroleum), hydrotreated heavy**Other hazards**

This product does not contain any substances classified as PBT (persistent, bioaccumulative and toxic) or vPvB (very persistent and very bioaccumulative).

**SECTION 3: Composition and information on ingredients****Mixtures**

<b>PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS</b>	<b>60-100%</b>
CAS number: 68476-85-7	
Substance with a Community workplace exposure limit.	
<b>Classification</b>	
Flam. Gas 1 - H220	
Press. Gas, Liquefied - H280	
<b>Naphtha (petroleum), hydrotreated heavy</b>	<b>20&lt;30%</b>
CAS number: 64742-48-9	
<b>Classification</b>	
Flam. Liq. 3 - H226	
STOT SE 3 - H336	
Asp. Tox. 1 - H304	

**(Aerosol) Silver Seal Paint Protector**

<b>Dimethyl Siloxane, ho term rxn methyltrimethoxysilane &amp; amionethylaninopropyltrimethoxysilane</b>	<b>0.2&lt;0.5%</b>
CAS number: 69430-37-1 M factor (Acute) = 1                      M factor (Chronic) = 1	
<b>Classification</b> Flam. Liq. 2 - H225 Skin Irrit. 2 - H315 Eye Irrit. 2A - H319 Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410	
<b>Isopropyl alcohol</b>	<b>0.1&lt;0.2%</b>
CAS number: 67-63-0 Substance with a Community workplace exposure limit.	
<b>Classification</b> Flam. Liq. 2 - H225 Eye Irrit. 2A - H319 STOT SE 3 - H336	
<b>(R)-p-mentha-1,8-diene</b>	<b>0.1&lt;0.2%</b>
CAS number: 5989-27-5 M factor (Acute) = 1                      M factor (Chronic) = 1	
<b>Classification</b> Flam. Liq. 3 - H226 Skin Irrit. 2 - H315 Skin Sens. 1B - H317 Asp. Tox. 1 - H304 Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410	

The full text for all hazard statements is displayed in Section 16.

#### **SECTION 4: First aid measures**

##### Description of first aid measures

###### **General information**

Get medical attention immediately. Show this Safety Data Sheet to the medical personnel.

###### **Inhalation**

Remove affected person from source of contamination. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Maintain an open airway. Loosen tight clothing such as collar, tie or belt. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Place unconscious person on their side in the recovery position and ensure breathing can take place.

## (Aerosol) Silver Seal Paint Protector

<b>Ingestion</b>	Rinse mouth thoroughly with water. Remove any dentures. Give a few small glasses of water or milk to drink. Stop if the affected person feels sick as vomiting may be dangerous. Do not induce vomiting unless under the direction of medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Place unconscious person on their side in the recovery position and ensure breathing can take place. Maintain an open airway. Loosen tight clothing such as collar, tie or belt.
<b>Skin Contact</b>	Rinse with water.
<b>Eye contact</b>	Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 10 minutes.
<b>Protection of first aiders</b>	First aid personnel should wear appropriate protective equipment during any rescue. Wash contaminated clothing thoroughly with water before removing it from the affected person, or wear gloves. It may be dangerous for first aid personnel to carry out mouth-to-mouth resuscitation.

### Most important symptoms and effects, both acute and delayed

<b>General information</b>	See Section 11 for additional information on health hazards. The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
<b>Inhalation</b>	A single exposure may cause the following adverse effects: Headache. Nausea, vomiting. Central nervous system depression. Drowsiness, dizziness, disorientation, vertigo. Narcotic effect.
<b>Ingestion</b>	Due to the physical nature of this product, it is unlikely that ingestion will occur.
<b>Skin contact</b>	Repeated exposure may cause skin dryness or cracking.
<b>Eye contact</b>	May be slightly irritating to eyes. May cause discomfort.

### Indication of any immediate medical attention and special treatment needed

<b>Notes for the doctor</b>	Treat symptomatically.
-----------------------------	------------------------

## **SECTION 5: Firefighting measures**

### Extinguishing media

<b>Suitable extinguishing media</b>	The product is flammable. Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire-extinguishing media suitable for the surrounding fire.
<b>Unsuitable extinguishing media</b>	Do not use water jet as an extinguisher, as this will spread the fire.

### Special hazards arising from the substance or mixture

<b>Specific hazards</b>	Containers can burst violently or explode when heated, due to excessive pressure build-up. Bursting aerosol containers may be propelled from a fire at high speed. If aerosol cans are ruptured, care should be taken due to the rapid escape of the pressurised contents and propellant. Vapours may form explosive mixtures with air.
<b>Hazardous combustion products</b>	Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours.

### Advice for firefighters

## (Aerosol) Silver Seal Paint Protector

<b>Protective actions during firefighting</b>	Avoid breathing fire gases or vapours. Evacuate area. Keep upwind to avoid inhalation of gases, vapours, fumes and smoke. Ventilate closed spaces before entering them. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapours and protect men stopping the leak. Avoid discharge to the aquatic environment. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.
<b>Special protective equipment for firefighters</b>	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing conforming to Australia/New Zealand Standards AS/NZS 4967 (for clothing) AS/NZS 1801 (for helmets), AS/NZS 4821 (for protective boots), AS/NZS 1801 (for protective gloves) will provide a basic level of protection for chemical incidents.

### SECTION 6: Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

<b>Personal precautions</b>	No action shall be taken without appropriate training or involving any personal risk. Keep unnecessary and unprotected personnel away from the spillage. Wear protective clothing as described in Section 8 of this safety data sheet. Follow precautions for safe handling described in this safety data sheet. Wash thoroughly after dealing with a spillage. Ensure procedures and training for emergency decontamination and disposal are in place. Do not touch or walk into spilled material. Evacuate area. Risk of explosion. Provide adequate ventilation. No smoking, sparks, flames or other sources of ignition near spillage. Promptly remove any clothing that becomes contaminated.
-----------------------------	--

#### Environmental precautions

<b>Environmental precautions</b>	Avoid discharge into drains or watercourses or onto the ground. Avoid discharge to the aquatic environment. Large Spillages: Inform the relevant authorities if environmental pollution occurs (sewers, waterways, soil or air).
----------------------------------	--

#### Methods and material for containment and cleaning up

<b>Methods for cleaning up</b>	Wear protective clothing as described in Section 8 of this safety data sheet. Clear up spills immediately and dispose of waste safely. Eliminate all ignition sources if safe to do so. No smoking, sparks, flames or other sources of ignition near spillage. Approach the spillage from upwind. Under normal conditions of handling and storage, spillages from aerosol containers are unlikely. If aerosol cans are ruptured, care should be taken due to the rapid escape of the pressurised contents and propellant. Small Spillages: Wipe up with an absorbent cloth and dispose of waste safely. Large Spillages: If the product is soluble in water, dilute the spillage with water and mop it up. Alternatively, or if it is not water-soluble, absorb the spillage with an inert, dry material and place it in a suitable waste disposal container. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage. Dangerous for the environment. Do not empty into drains. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.
--------------------------------	---

#### Reference to other sections

<b>Reference to other sections</b>	For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.
------------------------------------	---

### SECTION 7: Handling and storage, including how the chemical may be safely used

#### Precautions for safe handling

## (Aerosol) Silver Seal Paint Protector

<b>Usage precautions</b>	Read and follow manufacturer's recommendations. Wear protective clothing as described in Section 8 of this safety data sheet. Keep away from food, drink and animal feeding stuffs. Avoid exposing aerosol containers to high temperatures or direct sunlight. The product is flammable. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not handle until all safety precautions have been read and understood. Do not handle broken packages without protective equipment. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Spray will evaporate and cool rapidly and may cause frostbite or cold burns if in contact with skin. Avoid contact with eyes. Avoid inhalation of vapours and spray/mists.
<b>Advice on general occupational hygiene</b>	Wash promptly if skin becomes contaminated. Take off contaminated clothing and wash before reuse. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Wash at the end of each work shift and before eating, smoking and using the toilet. Change work clothing daily before leaving workplace.

### Conditions for safe storage, including any incompatibilities

<b>Storage precautions</b>	Store away from incompatible materials (see Section 10). Store in accordance with local regulations. Keep away from oxidising materials, heat and flames. Keep only in the original container. Keep container tightly closed, in a cool, well ventilated place. Keep containers upright. Protect containers from damage. Protect from sunlight. Do not store near heat sources or expose to high temperatures. Do not expose to temperatures exceeding 50 °C/ 122 °F. Bund storage facilities to prevent soil and water pollution in the event of spillage. The storage area floor should be leak-tight, jointless and not absorbent.
<b>Storage class</b>	Miscellaneous hazardous material storage.

### Specific end use(s)

**Specific end use(s)** The identified uses for this product are detailed in Section 1.

## **SECTION 8: Exposure controls and personal protection**

### Control parameters

#### Occupational exposure limits

#### **PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS**

Long-term exposure limit (8-hour TWA): 1000 ppm 1800 mg/m<sup>3</sup>

#### **Isopropyl alcohol**

Long-term exposure limit (8-hour TWA): 400 ppm 983 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): 500 ppm 1230 mg/m<sup>3</sup>

#### **Naphtha (petroleum), hydrotreated heavy (CAS: 64742-48-9)**

**Ingredient comments** No exposure limits known for ingredient(s).

#### **Thixcin R**

**Ingredient comments** No exposure limits known for ingredient(s).

#### **(R)-p-mentha-1,8-diene (CAS: 5989-27-5)**

**Ingredient comments** No exposure limits known for ingredient(s).

### Exposure controls

## (Aerosol) Silver Seal Paint Protector

### Protective equipment



### Appropriate engineering controls

Provide adequate ventilation. Personal, workplace environment or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Use process enclosures, local exhaust ventilation or other engineering controls as the primary means to minimise worker exposure. Personal protective equipment should only be used if worker exposure cannot be controlled adequately by the engineering control measures. Ensure control measures are regularly inspected and maintained. Ensure operatives are trained to minimise exposure.

### Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Personal protective equipment for eye and face protection should comply with Australia/New Zealand Standard AS/NZS 1337. Unless the assessment indicates a higher degree of protection is required, the following protection should be worn: Tight-fitting safety glasses.

### Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. The breakthrough time for any glove material may be different for different glove manufacturers. To protect hands from chemicals, gloves should comply with Australia/New Zealand Standard AS/NZS 2161. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. Frequent changes are recommended. The choice of protective gloves depends upon the chemicals being handled, and the conditions of work and use. When used with mixtures, the protection time of gloves cannot be accurately estimated. Gloves made from the following material may provide suitable chemical protection: Nitrile rubber. Thickness: >0.2mm The selected gloves should have a breakthrough time of at least 0.5 hours. Glove thickness is not necessarily a good measure of glove resistance as the permeation rate will depend on the exact glove composition. Repeated exposure to chemicals will degrade the ability of the glove to provide resistance to chemicals. Specific work environments and material handling practices may vary, therefore safety procedures should be developed for each intended application. Use thin cotton gloves inside natural rubber gloves if there is an allergy risk to natural rubber.

### Other skin and body protection

Appropriate footwear and additional protective clothing complying with an approved standard should be worn if a risk assessment indicates skin contamination is possible.

### Hygiene measures

Provide eyewash station and safety shower. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Clean equipment and the work area every day. Good personal hygiene procedures should be implemented. Wash at the end of each work shift and before eating, smoking and using the toilet. When using do not eat, drink or smoke. Preventive industrial medical examinations should be carried out. Warn cleaning personnel of any hazardous properties of the product.

### Respiratory protection

Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible. Ensure all respiratory protective equipment is suitable for its intended use and complies with Australia/New Zealand Standard AS/NZS 1716. Check that the respirator fits tightly and the filter is changed regularly. Gas and combination filter cartridges should comply with Australia/New Zealand Standard AS/NZS 1716. Full face mask respirators with replaceable filter cartridges should comply with Australia/New Zealand Standard AS/NZS 1716. Half mask and quarter mask respirators with replaceable filter cartridges should comply with Australia/New Zealand Standard AS/NZS 1716.

## (Aerosol) Silver Seal Paint Protector

<b>Environmental exposure controls</b>	Keep container tightly sealed when not in use. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
--	---

### SECTION 9: Physical and chemical properties

#### Information on basic physical and chemical properties

<b>Appearance</b>	Aerosol. Liquid.
<b>Colour</b>	Brown.
<b>Odour</b>	Strong. Solvent.
<b>Odour threshold</b>	Not available.
<b>pH</b>	Not applicable.
<b>Melting point</b>	Not determined.
<b>Initial boiling point and range</b>	-40 ~ -2°C @ 1013 hPa
<b>Flash point</b>	-60°C Closed cup.
<b>Evaporation rate</b>	Not available.
<b>Flammability Limit - Lower(%)</b>	Lower flammable/explosive limit: 1.4 % Upper flammable/explosive limit: 10.9 %
<b>Vapour pressure</b>	590 - 1760 kPa @ °C
<b>Vapour density</b>	~ 1.5 @ 15°C
<b>Relative density</b>	~ 0.510 @ 15°C
<b>Solubility(ies)</b>	Soluble in the following materials: Organic solvents. Insoluble in water.
<b>Partition coefficient</b>	log Pow: 2.3 - 2.8
<b>Auto-ignition temperature</b>	365°C
<b>Decomposition Temperature</b>	Not available.
<b>Viscosity</b>	Not determined.
<b>Oxidising properties</b>	Not applicable.
<b>Comments</b>	Information declared as "Not available" or "Not applicable" is not considered to be relevant to the implementation of the proper control measures. Information given is applicable to the major ingredient.
<b>Volatile organic compound</b>	This product contains a maximum VOC content of 583 g/litre.

### SECTION 10: Stability and reactivity

<b>Reactivity</b>	See the other subsections of this section for further details.
<b>Stability</b>	Stable at normal ambient temperatures and when used as recommended. Stable under the prescribed storage conditions.
<b>Possibility of hazardous reactions</b>	The following materials may react strongly with the product: Oxidising agents.
<b>Conditions to avoid</b>	Avoid exposing aerosol containers to high temperatures or direct sunlight. Pressurised container: may burst if heated



## (Aerosol) Silver Seal Paint Protector

**Materials to avoid** No specific material or group of materials is likely to react with the product to produce a hazardous situation.

**Hazardous decomposition products** Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours.

### SECTION 11: Toxicological information

#### Information on toxicological effects

**Other health effects** There is no evidence that the product can cause cancer.

#### Acute toxicity - oral

**Notes (oral LD<sub>50</sub>)** Based on available data the classification criteria are not met.

#### Acute toxicity - dermal

**Notes (dermal LD<sub>50</sub>)** Based on available data the classification criteria are not met.

#### Acute toxicity - inhalation

**Notes (inhalation LC<sub>50</sub>)** Based on available data the classification criteria are not met.

#### Skin corrosion/irritation

**Animal data** Repeated exposure may cause skin dryness or cracking.

**Human skin model test** Scientifically unjustified.

**Extreme pH** Scientifically unjustified.

#### Serious eye damage/irritation

**Serious eye damage/irritation** Based on available data the classification criteria are not met.

#### Respiratory sensitisation

**Respiratory sensitisation** Based on available data the classification criteria are not met.

#### Skin sensitisation

**Skin sensitisation** Based on available data the classification criteria are not met.

#### Germ cell mutagenicity

**Genotoxicity - in vitro** Based on available data the classification criteria are not met.

#### Carcinogenicity

**Carcinogenicity** Based on available data the classification criteria are not met.

**IARC carcinogenicity** Contains a substance which may be potentially carcinogenic. IARC Group 3 Not classifiable as to its carcinogenicity to humans.

#### Reproductive toxicity

**Reproductive toxicity - fertility** Based on available data the classification criteria are not met.

**Reproductive toxicity - development** Based on available data the classification criteria are not met.

#### Specific target organ toxicity - single exposure

**STOT - single exposure** STOT SE 3 - H336 May cause drowsiness or dizziness.

**Target organs** Central nervous system

#### Specific target organ toxicity - repeated exposure

**STOT - repeated exposure** Not classified as a specific target organ toxicant after repeated exposure.

#### Aspiration hazard

## (Aerosol) Silver Seal Paint Protector

<b>Aspiration hazard</b>	Based on available data the classification criteria are not met.
<b>General information</b>	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
<b>Inhalation</b>	A single exposure may cause the following adverse effects: Headache. Nausea, vomiting. Central nervous system depression. Drowsiness, dizziness, disorientation, vertigo. Narcotic effect.
<b>Ingestion</b>	Due to the physical nature of this product, it is unlikely that ingestion will occur.
<b>Skin Contact</b>	Repeated exposure may cause skin dryness or cracking.
<b>Eye contact</b>	May be slightly irritating to eyes. May cause discomfort.
<b>Acute and chronic health hazards</b>	Because of the product's quantity and composition, the health hazard is regarded as low.
<b>Route of exposure</b>	Ingestion Inhalation Skin and/or eye contact
<b>Target Organs</b>	Central nervous system
<b>Medical Symptoms</b>	No specific symptoms noted, but this chemical may still have adverse health impact, either in general or on certain individuals.
<b>Medical considerations</b>	Skin disorders and allergies.

### SECTION 12: Ecological information

<b>Ecotoxicity</b>	The product contains a substance which is harmful to aquatic organisms.
<b>Toxicity</b>	Aquatic Chronic 3 - H412 Harmful to aquatic life with long lasting effects.
<b><u>Acute aquatic toxicity</u></b>	
<b>Acute toxicity - fish</b>	Not determined.
<b>Acute toxicity - aquatic invertebrates</b>	Not determined.
<b>Acute toxicity - aquatic plants</b>	Not determined.
<b>Acute toxicity - microorganisms</b>	Not determined.
<b>Acute toxicity - terrestrial</b>	Not determined.
<b><u>Persistence and degradability</u></b>	
<b>Persistence and degradability</b>	The degradability of the product is not known.
<b><u>Bioaccumulative potential</u></b>	
<b>Bioaccumulative Potential</b>	No data available on bioaccumulation.
<b>Partition coefficient</b>	log Pow: 2.3 - 2.8
<b><u>Mobility in soil</u></b>	
<b>Mobility</b>	The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces.
<b><u>Other adverse effects</u></b>	
<b>Other adverse effects</b>	None known.

## (Aerosol) Silver Seal Paint Protector

### SECTION 13: Disposal considerations

#### Waste treatment methods

##### **General information**

The generation of waste should be minimised or avoided wherever possible. Reuse or recycle products wherever possible. This material and its container must be disposed of in a safe way. Disposal of this product, process solutions, residues and by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements. When handling waste, the safety precautions applying to handling of the product should be considered. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out. Empty containers or liners may retain some product residues and hence be potentially hazardous.

##### **Disposal methods**

Do not empty into drains. Empty containers must not be punctured or incinerated because of the risk of an explosion. Dispose of surplus products and those that cannot be recycled via a licensed waste disposal contractor. Waste, residues, empty containers, discarded work clothes and contaminated cleaning materials should be collected in designated containers, labelled with their contents.

### SECTION 14: Transport information

##### **General**

For limited quantity packaging/limited load information, consult the relevant modal documentation using the data shown in this section.

##### UN number

UN No. (ADG) 1950

UN No. (IMDG) 1950

UN No. (ICAO) 1950

##### UN proper shipping name

Proper shipping name (ADG) AEROSOLS

Proper shipping name (IMDG) AEROSOLS

Proper shipping name (ICAO) AEROSOLS

##### Transport hazard class(es)

ADG class 2.1

ADG classification code 5F

ADG label 2.1

IMDG class 2.1

ICAO class/division 2.1

##### **Transport labels**



##### Packing group

ADG packing group None

IMDG packing group None

ICAO packing group None

## (Aerosol) Silver Seal Paint Protector

### Environmental hazards

#### Environmentally hazardous substance/marine pollutant

No.

### Special precautions for user

Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

EmS F-D, S-U

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78  
and the IBC Code

### SECTION 15: Regulatory information

#### Safety, health and environmental regulations/legislation specific for the substance or mixture

##### National regulations

The Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).  
National Code of Practice for the Preparation of Material Safety Data Sheets.  
Approved Criteria for Classifying Hazardous Substances.  
Exposure Standards for Atmospheric Contaminants in the Occupational Environment.  
Guidance Note on the Interpretation of Exposure Standards for Atmospheric Contaminants in the Occupational Environment.  
National Code of Practice for the Labelling of Workplace Substances.  
National Model Regulations for the Control of Workplace Hazardous Substances.  
National Code of Practice for the Control of Workplace Hazardous Substances.  
National Standard for the Storage and Handling of Workplace Dangerous Goods.  
National Code of Practice for the Storage and Handling of Workplace Dangerous Goods.  
Guidance Note for Placarding Stores for Dangerous Goods and Specified Hazardous Substances. Guidance Note for the Assessment of Health Risks Arising from Hazardous Substances in the Workplace.  
National Standard for the Control of Major Hazard Facilities. National Code of Practice for the Control of Major Hazard Facilities.

Schedule (SUSMP) Schedule 5. Caution.

### Inventories

#### EU - EINECS/ELINCS

All the ingredients are listed or exempt.

#### Australia - AIC

All the ingredients are listed or exempt.

### SECTION 16: Any other relevant information

## (Aerosol) Silver Seal Paint Protector

<b>Abbreviations and acronyms used in the safety data sheet</b>	<p>ADG: Australian dangerous goods code</p> <p>IATA: International air transport association.</p> <p>ICAO: Technical instructions for the safe transport of dangerous goods by air.</p> <p>IMDG: International maritime dangerous goods.</p> <p>CAS: Chemical abstracts service.</p> <p>ATE: Acute toxicity estimate.</p> <p>LC<sub>50</sub>: Lethal concentration to 50 % of a test population.</p> <p>LD<sub>50</sub>: Lethal dose to 50% of a test population (median lethal dose).</p> <p>EC<sub>50</sub>: 50% of maximal effective concentration.</p> <p>PBT: Persistent, bioaccumulative and toxic substance.</p> <p>vPvB: Very persistent and very bioaccumulative.</p>
<b>Classification abbreviations and acronyms</b>	<p>Aerosol = Aerosol</p> <p>STOT SE = Specific target organ toxicity-single exposure</p> <p>Aquatic Chronic = Hazardous to the aquatic environment (chronic)</p>
<b>General information</b>	<p>This product has been manufactured under ISO 9001 and ISO 14001 Quality and Environmental Management Systems.</p>
<b>Training advice</b>	<p>Read and follow manufacturer's recommendations. Only trained personnel should use this material.</p>
<b>Revision comments</b>	<p>NOTE: Lines within the margin indicate significant changes from the previous revision.</p>
<b>Issued by</b>	<p>Prepared by Autosmart International Ltd, Lynn Lane, Shenstone, Lichfield, Staffordshire, WS14 0DH, Great Britain.</p> <p><a href="http://www.autosmartinternational.com">www.autosmartinternational.com</a></p> <p><a href="mailto:rbutler@autosmart.co.uk">rbutler@autosmart.co.uk</a></p> <p>Tel +44 (0)1543 481616</p>
<b>Revision date</b>	12/05/2022
<b>Revision</b>	11
<b>Supersedes date</b>	3/03/2020
<b>SDS No.</b>	10318
<b>SDS status</b>	Approved.
<b>Hazard statements in full</b>	<p>H220 Extremely flammable gas.</p> <p>H225 Highly flammable liquid and vapour.</p> <p>H226 Flammable liquid and vapour.</p> <p>H229 Pressurised container: may burst if heated.</p> <p>H280 Contains gas under pressure; may explode if heated.</p> <p>H304 May be fatal if swallowed and enters airways.</p> <p>H315 Causes skin irritation.</p> <p>H317 May cause an allergic skin reaction.</p> <p>H319 Causes serious eye irritation.</p> <p>H336 May cause drowsiness or dizziness.</p> <p>H400 Very toxic to aquatic life.</p> <p>H402 Harmful to aquatic life.</p> <p>H410 Very toxic to aquatic life with long lasting effects.</p> <p>H412 Harmful to aquatic life with long lasting effects.</p>

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.