



SAFETY DATA SHEET

WashSmart - Foaming Wheel and Engine Scrub

According to Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice, February 2016

SECTION 1: Identification: Product identifier and chemical identity

Product identifier

Product name WashSmart - Foaming Wheel and Engine Scrub

Relevant identified uses of the substance or mixture and uses advised against

Application Car maintenance product. - Degreaser

Uses advised against For professional use only. This product is not recommended for any industrial, professional or consumer use other than the Identified uses above.

Details of the supplier of the safety data sheet

Supplier Autosmart Australia
11 Darrambal Close
Rathmines
NSW 2283
Australia
www.autosmartaustralia.com.au
Tel: 02 49 75 14 88 (Mon to Fri, 08:00 - 16:00 AEST) (General Information. Transport Information. Mild Medical Information)
autosmart@autosmartaustralia.com.au

Contact Person Mr. Russell Butler

Emergency telephone number

Emergency telephone Emergency No: +44 7808 971321 (24hrs) (Autosmart International, UK)
General Information. Transport Information. Mild medical Information:-
Tel: 02 49 75 14 88 (Mon to Fri, 08:00 - 16:00 AEST)

National emergency telephone number Poison Information Hotline: 13 11 26

SECTION 2: Hazard(s) identification

Classification of the substance or mixture

Physical hazards Met. Corr. 1 - H290
Health hazards Skin Corr. 1C - H314 Eye Dam. 1 - H318
Environmental hazards Not Classified

Label elements

Hazard pictograms



Signal word DANGER

WashSmart - Foaming Wheel and Engine Scrub

Hazard statements	H290 May be corrosive to metals. H314 Causes severe skin burns and eye damage.
Precautionary statements	P264 Wash contaminated skin thoroughly after handling. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P362+P364 Take off contaminated clothing and wash before reuse. P501 Dispose of contents/ container in accordance with national regulations. P280 Wear protective clothing, gloves, eye and face protection.
Supplemental label information	For professional users only.
Contains	Trisodium Nitritotriacetate

Other hazards

This product does not contain any substances classified as PBT (persistent, bioaccumulative and toxic) or vPvB (very persistent and very bioaccumulative).

SECTION 3: Composition and information on ingredients

Mixtures

Trisodium Nitritotriacetate CAS number: 5064-31-3	3<5%
Classification Acute Tox. 4 - H302 Eye Irrit. 2A - H319 Carc. 2 - H351	
Alcohols, C12-14, ethoxylated CAS number: 68439-50-9	1<1.25%
Classification Skin Irrit. 2 - H315 Eye Dam. 1 - H318	
sodium hydroxide CAS number: 1310-73-2 Substance with a Community workplace exposure limit.	0.5<0.7%
Classification Met. Corr. 1 - H290 Skin Corr. 1A - H314 Eye Dam. 1 - H318	

WashSmart - Foaming Wheel and Engine Scrub

POTASSIUM HYDROXIDE	0.5<0.7%
CAS number: 1310-58-3	
Classification	
Met. Corr. 1 - H290	
Acute Tox. 4 - H302	
Skin Corr. 1A - H314	
Eye Dam. 1 - H318	

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

Description of first aid measures

General information	Get medical attention immediately. Show this Safety Data Sheet to the medical personnel.
Inhalation	Remove affected person from source of contamination. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Maintain an open airway. Loosen tight clothing such as collar, tie or belt. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Place unconscious person on their side in the recovery position and ensure breathing can take place.
Ingestion	Rinse mouth thoroughly with water. Remove any dentures. Give a few small glasses of water or milk to drink. Stop if the affected person feels sick as vomiting may be dangerous. Do not induce vomiting unless under the direction of medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Place unconscious person on their side in the recovery position and ensure breathing can take place. Maintain an open airway. Loosen tight clothing such as collar, tie or belt.
Skin Contact	Rinse with water.
Eye contact	Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 10 minutes.
Protection of first aiders	First aid personnel should wear appropriate protective equipment during any rescue. Wash contaminated clothing thoroughly with water before removing it from the affected person, or wear gloves. It may be dangerous for first aid personnel to carry out mouth-to-mouth resuscitation.

Most important symptoms and effects, both acute and delayed

General information	See Section 11 for additional information on health hazards. The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	Prolonged inhalation of high concentrations may damage respiratory system.
Ingestion	Corrosive. Ingestion may cause severe irritation of the mouth, the oesophagus and the gastrointestinal tract.
Skin contact	Corrosive.
Eye contact	Corrosive to skin and eyes.

Indication of any immediate medical attention and special treatment needed

Notes for the doctor	Treat symptomatically.
-----------------------------	------------------------

SECTION 5: Firefighting measures

WashSmart - Foaming Wheel and Engine Scrub

Extinguishing media

Suitable extinguishing media The product is not flammable. Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire-extinguishing media suitable for the surrounding fire.

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

Special hazards arising from the substance or mixture

Specific hazards Containers can burst violently or explode when heated, due to excessive pressure build-up.

Hazardous combustion products Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours.

Advice for firefighters

Protective actions during firefighting Avoid breathing fire gases or vapours. Evacuate area. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapours and protect men stopping the leak. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing conforming to Australia/New Zealand Standards AS/NZS 4967 (for clothing) AS/NZS 1801 (for helmets), AS/NZS 4821 (for protective boots), AS/NZS 1801 (for protective gloves) will provide a basic level of protection for chemical incidents.

Hazchem Code 2R

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions No action shall be taken without appropriate training or involving any personal risk. Keep unnecessary and unprotected personnel away from the spillage. Wear protective clothing as described in Section 8 of this safety data sheet. Follow precautions for safe handling described in this safety data sheet. Wash thoroughly after dealing with a spillage. Ensure procedures and training for emergency decontamination and disposal are in place. Do not touch or walk into spilled material.

Environmental precautions

Environmental precautions Large Spillages: Inform the relevant authorities if environmental pollution occurs (sewers, waterways, soil or air).

Methods and material for containment and cleaning up

WashSmart - Foaming Wheel and Engine Scrub

Methods for cleaning up

Wear protective clothing as described in Section 8 of this safety data sheet. Clear up spills immediately and dispose of waste safely. Approach the spillage from upwind. Small Spillages: If the product is soluble in water, dilute the spillage with water and mop it up. Alternatively, or if it is not water-soluble, absorb the spillage with an inert, dry material and place it in a suitable waste disposal container. Large Spillages: If leakage cannot be stopped, evacuate area. Flush spilled material into an effluent treatment plant, or proceed as follows. Contain and absorb spillage with sand, earth or other non-combustible material. Place waste in labelled, sealed containers. Clean contaminated objects and areas thoroughly, observing environmental regulations. The contaminated absorbent may pose the same hazard as the spilled material. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage. Neutralise with acid. Caution. May generate heat. Following dilution and neutralisation, discharge to the sewer with plenty of water may be permitted. The requirements of the local water authority must be complied with if contaminated water is flushed directly to the sewer. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

Reference to other sections

Reference to other sections

For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

SECTION 7: Handling and storage, including how the chemical may be safely used

Precautions for safe handling

Usage precautions

Read and follow manufacturer's recommendations. Wear protective clothing as described in Section 8 of this safety data sheet. Keep away from food, drink and animal feeding stuffs. Handle all packages and containers carefully to minimise spills. Keep container tightly sealed when not in use. Avoid the formation of mists. Do not handle until all safety precautions have been read and understood. Do not handle broken packages without protective equipment. Do not reuse empty containers.

Advice on general occupational hygiene

Wash promptly if skin becomes contaminated. Take off contaminated clothing and wash before reuse. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Wash at the end of each work shift and before eating, smoking and using the toilet. Change work clothing daily before leaving workplace.

Conditions for safe storage, including any incompatibilities

Storage precautions

Store away from incompatible materials (see Section 10). Store in accordance with local regulations. Store away from the following materials: Acids. Keep only in the original container. Keep container tightly closed, in a cool, well ventilated place. Keep containers upright. Protect containers from damage. Store in corrosive resistant container with a resistant inner liner. Bund storage facilities to prevent soil and water pollution in the event of spillage. The storage area floor should be leak-tight, jointless and not absorbent.

Storage class

Acid-reactive storage.

Specific end use(s)

Specific end use(s)

The identified uses for this product are detailed in Section 1.

SECTION 8: Exposure controls and personal protection

Control parameters

Occupational exposure limits

sodium hydroxide

Ceiling value: 2 mg/m³

POTASSIUM HYDROXIDE

WashSmart - Foaming Wheel and Engine Scrub

Long-term exposure limit (8-hour TWA): NOHSC

Short-term exposure limit (15-minute): NOHSC 2 mg/m³

NOHSC = The National Occupational Health and Safety Commission.

Trisodium Nitrotriacetate (CAS: 5064-31-3)

Ingredient comments No exposure limits known for ingredient(s).

Alcohols, C12-14, ethoxylated (CAS: 68439-50-9)

Ingredient comments No exposure limits known for ingredient(s).

Alcohols C9-11, ethoxylated (CAS: 68439-46-3)

Ingredient comments No exposure limits known for ingredient(s).

Quaternary ammonium compounds, coco alkylbis(hydroxyethyl)methyl, ethoxylated, chlorides (CAS: 61791-10-4)

Ingredient comments No exposure limits known for ingredient(s).

Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate ventilation. Personal, workplace environment or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Use process enclosures, local exhaust ventilation or other engineering controls as the primary means to minimise worker exposure. Personal protective equipment should only be used if worker exposure cannot be controlled adequately by the engineering control measures. Ensure control measures are regularly inspected and maintained. Ensure operatives are trained to minimise exposure.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Personal protective equipment for eye and face protection should comply with Australia/New Zealand Standard AS/NZS 1337. Wear tight-fitting, chemical splash goggles or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. To protect hands from chemicals, gloves should comply with Australia/New Zealand Standard AS/NZS 2161. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. Frequent changes are recommended.

Other skin and body protection

Appropriate footwear and additional protective clothing complying with an approved standard should be worn if a risk assessment indicates skin contamination is possible.

WashSmart - Foaming Wheel and Engine Scrub

Hygiene measures	Provide eyewash station and safety shower. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Clean equipment and the work area every day. Good personal hygiene procedures should be implemented. Wash at the end of each work shift and before eating, smoking and using the toilet. When using do not eat, drink or smoke. Preventive industrial medical examinations should be carried out. Warn cleaning personnel of any hazardous properties of the product.
Respiratory protection	Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible. Ensure all respiratory protective equipment is suitable for its intended use and complies with Australia/New Zealand Standard AS/NZS 1716. Check that the respirator fits tightly and the filter is changed regularly. Gas and combination filter cartridges should comply with Australia/New Zealand Standard AS/NZS 1716. Full face mask respirators with replaceable filter cartridges should comply with Australia/New Zealand Standard AS/NZS 1716. Half mask and quarter mask respirators with replaceable filter cartridges should comply with Australia/New Zealand Standard AS/NZS 1716.
Environmental exposure controls	Store in a demarcated bunded area to prevent release to drains and/or watercourses.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Liquid.
Colour	Light (or pale). Straw.
Odour	Pine.
Odour threshold	Not available.
pH	pH (concentrated solution): ~ 13.2 pH (diluted solution): ~ 11.0 @ 1%
Melting point	~ 0°C
Initial boiling point and range	~ 100 @°C @ 760 mm Hg
Flash point	Not applicable.
Evaporation rate	Not available.
Flammability Limit - Lower(%)	Not applicable.
Vapour pressure	Not applicable.
Vapour density	Not applicable.
Relative density	~ 1.094 @ (20°C)°C
Solubility(ies)	Soluble in water. Miscible with water.
Partition coefficient	Not available.
Auto-ignition temperature	Not applicable.
Decomposition Temperature	Not available.
Viscosity	~ 1 cSt @ °C
Oxidising properties	Not applicable.
Comments	Information declared as "Not available" or "Not applicable" is not considered to be relevant to the implementation of the proper control measures.
Volatile organic compound	This product contains a maximum VOC content of 0 g/litre.

WashSmart - Foaming Wheel and Engine Scrub

SECTION 10: Stability and reactivity

Reactivity	May be corrosive to metals.
Stability	Stable at normal ambient temperatures and when used as recommended. Stable under the prescribed storage conditions.
Possibility of hazardous reactions	No potentially hazardous reactions known.
Conditions to avoid	There are no known conditions that are likely to result in a hazardous situation.
Materials to avoid	Acid anhydrides. Acids. Phenols, cresols. Mild steel. Stainless steel. Aluminium. May be corrosive to metals.
Hazardous decomposition products	Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours.

SECTION 11: Toxicological information

Information on toxicological effects

Acute toxicity - oral

Notes (oral LD₅₀) Based on available data the classification criteria are not met.

ATE oral (mg/kg) 13,020.83

Acute toxicity - dermal

Notes (dermal LD₅₀) Based on available data the classification criteria are not met.

Acute toxicity - inhalation

Notes (inhalation LC₅₀) Based on available data the classification criteria are not met.

Skin corrosion/irritation

Extreme pH ≥ 11.5 Corrosive.

Serious eye damage/irritation

Serious eye damage/irritation Causes serious eye irritation.

Respiratory sensitisation

Respiratory sensitisation Based on available data the classification criteria are not met.

Skin sensitisation

Skin sensitisation Based on available data the classification criteria are not met.

Germ cell mutagenicity

Genotoxicity - in vitro Based on available data the classification criteria are not met.

Carcinogenicity

Carcinogenicity Based on available data the classification criteria are not met.

IARC carcinogenicity

None of the ingredients are listed or exempt.

Reproductive toxicity

Reproductive toxicity - fertility Based on available data the classification criteria are not met.

Reproductive toxicity - development

Based on available data the classification criteria are not met.

Specific target organ toxicity - single exposure

WashSmart - Foaming Wheel and Engine Scrub

STOT - single exposure Not classified as a specific target organ toxicant after a single exposure.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Not classified as a specific target organ toxicant after repeated exposure.

Aspiration hazard

Aspiration hazard Based on available data the classification criteria are not met.

General information

The severity of the symptoms described will vary dependent on the concentration and the length of exposure.

Inhalation

Prolonged inhalation of high concentrations may damage respiratory system.

Ingestion

Corrosive. Ingestion may cause severe irritation of the mouth, the oesophagus and the gastrointestinal tract.

Skin Contact

Corrosive.

Eye contact

Corrosive to skin and eyes.

Route of exposure

Ingestion Inhalation Skin and/or eye contact

Target Organs

No specific target organs known.

Toxicological information on ingredients.

Trisodium Nitrioltriacetate

Toxicological effects Nitrioltriacetic acid, trisodium salt (NTA) has caused kidney tumours in rats and mice when administered orally in high concentrations. The tumours are based on organ damage that can only occur when extremely high threshold limit concentrations, as compared with possible human exposure, are exceeded. In view of the potential degree of exposure, there should be no cancer risk to humans.

Acute toxicity - oral

ATE oral (mg/kg) 500.0

Carcinogenicity

Carcinogenicity Limited evidence of a carcinogenic effect.

Alcohols, C12-14, ethoxylated

Acute toxicity - oral

Notes (oral LD₅₀) Based on available data the classification criteria are not met.

Acute toxicity - dermal

Notes (dermal LD₅₀) Based on available data the classification criteria are not met.

Acute toxicity - inhalation

Notes (inhalation LC₅₀) Based on available data the classification criteria are not met.

Skin corrosion/irritation

Animal data Irritating.

Serious eye damage/irritation

Serious eye damage/irritation Eye Dam. 1 - H318 Causes serious eye damage.

Respiratory sensitisation

WashSmart - Foaming Wheel and Engine Scrub

Respiratory sensitisation	Based on available data the classification criteria are not met.
<u>Skin sensitisation</u>	
Skin sensitisation	Based on available data the classification criteria are not met.
<u>Germ cell mutagenicity</u>	
Genotoxicity - in vitro	Based on available data the classification criteria are not met.
<u>Carcinogenicity</u>	
Carcinogenicity	Based on available data the classification criteria are not met.
IARC carcinogenicity	None of the ingredients are listed or exempt.
<u>Reproductive toxicity</u>	
Reproductive toxicity - fertility	Based on available data the classification criteria are not met.
Reproductive toxicity - development	Based on available data the classification criteria are not met.
<u>Specific target organ toxicity - single exposure</u>	
STOT - single exposure	Not classified as a specific target organ toxicant after a single exposure.
<u>Specific target organ toxicity - repeated exposure</u>	
STOT - repeated exposure	Not classified as a specific target organ toxicant after repeated exposure.
<u>Aspiration hazard</u>	
Aspiration hazard	Based on available data the classification criteria are not met.
<u>General information</u>	
General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	Prolonged inhalation of high concentrations may damage respiratory system.
Ingestion	May cause irritation.
Skin Contact	Redness. Irritating to skin.
Eye contact	Causes serious eye damage. Symptoms following overexposure may include the following: Pain. Profuse watering of the eyes. Redness.
Route of exposure	Ingestion Inhalation Skin and/or eye contact
Target Organs	No specific target organs known.
	<u>sodium hydroxide</u>
Other health effects	There is no evidence that the product can cause cancer.
<u>Specific target organ toxicity - single exposure</u>	
STOT - single exposure	Not classified as a specific target organ toxicant after a single exposure.
<u>Specific target organ toxicity - repeated exposure</u>	
STOT - repeated exposure	Not classified as a specific target organ toxicant after repeated exposure.
<u>Aspiration hazard</u>	
Aspiration hazard	Not anticipated to present an aspiration hazard, based on chemical structure.

WashSmart - Foaming Wheel and Engine Scrub

Route of exposure Skin absorption Ingestion Skin and/or eye contact

Target Organs No specific target organs known.

POTASSIUM HYDROXIDE

Other health effects There is no evidence that the product can cause cancer.

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 273.0

Species Rat

Skin sensitisation

Skin sensitisation Guinea pig maximization test (GPMT) - : Not sensitising.

Specific target organ toxicity - single exposure

STOT - single exposure Not classified as a specific target organ toxicant after a single exposure.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Not classified as a specific target organ toxicant after repeated exposure.

SECTION 12: Ecological information

Ecotoxicity The product may affect the acidity (pH) of water which may have hazardous effects on aquatic organisms.

Ecological information on ingredients.

Alcohols, C12-14, ethoxylated

Ecotoxicity Not regarded as dangerous for the environment. However, large or frequent spills may have hazardous effects on the environment.

sodium hydroxide

Ecotoxicity The product may affect the acidity (pH) of water which may have hazardous effects on aquatic organisms.

POTASSIUM HYDROXIDE

Ecotoxicity The product components are not classified as environmentally hazardous. However, large or frequent spills may have hazardous effects on the environment.

Toxicity Based on available data the classification criteria are not met.

Ecological information on ingredients.

Trisodium Nitriacetate

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hours: 114-470 mg/l, Fish

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: 560-1,000 mg/l, Daphnia magna

WashSmart - Foaming Wheel and Engine Scrub

Acute toxicity - aquatic plants IC₅₀, 72 hours: 180-320 mg/l, Algae

Alcohols, C12-14, ethoxylated

Toxicity Based on available data the classification criteria are not met.

sodium hydroxide

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 48 hours: ~ 189 mg/l, Leuciscus idus (Golden orfe)
LC₅₀, 96 hours: 125 mg/l, Fish

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: > 100 mg/l, Daphnia magna
EC₅₀, 48 hours: 40-240 mg/l, Daphnia magna

Acute toxicity - aquatic plants Not known.

POTASSIUM HYDROXIDE

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hours: 80 mg/l, Freshwater fish

Persistence and degradability

Ecological information on ingredients.

Trisodium Nitriacetate

Persistence and degradability The product is biodegradable.

Alcohols, C12-14, ethoxylated

Persistence and degradability The product is readily biodegradable.

sodium hydroxide

Persistence and degradability The product contains only inorganic substances which are not biodegradable. The product is potentially degradable.

Stability (hydrolysis) Not applicable.

Biological oxygen demand ~ 0 g O₂/g substance

POTASSIUM HYDROXIDE

Persistence and degradability The product contains inorganic substances which are not biodegradable. The product is potentially degradable.

Bioaccumulative potential

Bioaccumulative Potential No data available on bioaccumulation.

Partition coefficient Not available.

Ecological information on ingredients.

WashSmart - Foaming Wheel and Engine Scrub

Trisodium Nitriacetate

Bioaccumulative Potential The product does not contain any substances expected to be bioaccumulating.

Alcohols, C12-14, ethoxylated

Bioaccumulative Potential No data available on bioaccumulation.

Partition coefficient Not available.

sodium hydroxide

Bioaccumulative Potential The product is not bioaccumulating.

POTASSIUM HYDROXIDE

Bioaccumulative Potential The product does not contain any substances expected to be bioaccumulating.

Mobility in soil

Mobility The product is water-soluble and may spread in water systems. The product is non-volatile.

Ecological information on ingredients.

Trisodium Nitriacetate

Mobility The product is soluble in water.

Alcohols, C12-14, ethoxylated

Mobility The product is water-soluble and may spread in water systems. The product is non-volatile.

sodium hydroxide

Mobility The product is soluble in water.

Henry's law constant The product contains mainly inorganic substances which are not biodegradable.

POTASSIUM HYDROXIDE

Mobility The product is soluble in water.

Other adverse effects

Other adverse effects None known.

Ecological information on ingredients.

Alcohols, C12-14, ethoxylated

Other adverse effects None known.

SECTION 13: Disposal considerations

Waste treatment methods

WashSmart - Foaming Wheel and Engine Scrub

General information

The generation of waste should be minimised or avoided wherever possible. Reuse or recycle products wherever possible. This material and its container must be disposed of in a safe way. Disposal of this product, process solutions, residues and by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements. When handling waste, the safety precautions applying to handling of the product should be considered. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out. Empty containers or liners may retain some product residues and hence be potentially hazardous.

Disposal methods

Dispose of surplus products and those that cannot be recycled via a licensed waste disposal contractor. Waste, residues, empty containers, discarded work clothes and contaminated cleaning materials should be collected in designated containers, labelled with their contents. Incineration or landfill should only be considered when recycling is not feasible.

SECTION 14: Transport information

General

For limited quantity packaging/limited load information, consult the relevant modal documentation using the data shown in this section.

UN number

UN No. (ADG) 1824

UN No. (IMDG) 1824

UN No. (ICAO) 1824

UN proper shipping name

Proper shipping name (ADG) SODIUM HYDROXIDE SOLUTION

Proper shipping name (IMDG) SODIUM HYDROXIDE SOLUTION

Proper shipping name (ICAO) SODIUM HYDROXIDE SOLUTION

Transport hazard class(es)

ADG class 8

ADG label 8

IMDG class 8

ICAO class/division 8

Transport labels



Packing group

ADG packing group III

IMDG packing group III

ICAO packing group III

Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

Special precautions for user

WashSmart - Foaming Wheel and Engine Scrub

Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

IMDG Code segregation group 18. Alkalis

EmS F-A, S-B

Hazchem Code 2R

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

SECTION 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

Schedule (SUSMP) Schedule 5. Caution.

Inventories

Australia - AICS

All the ingredients are listed or exempt.

SECTION 16: Any other relevant information

Abbreviations and acronyms used in the safety data sheet ADG: Australian dangerous goods code

IATA: International air transport association.

ICAO: Technical instructions for the safe transport of dangerous goods by air.

IMDG: International maritime dangerous goods.

CAS: Chemical abstracts service.

ATE: Acute toxicity estimate.

LC₅₀: Lethal concentration to 50 % of a test population.

LD₅₀: Lethal dose to 50% of a test population (median lethal dose).

EC₅₀: 50% of maximal effective concentration.

PBT: Persistent, bioaccumulative and toxic substance.

vPvB: Very persistent and very bioaccumulative.

Classification abbreviations and acronyms Met. Corr. = Corrosive to metals
Eye Irrit. = Eye irritation
Skin Irrit. = Skin irritation

Training advice Read and follow manufacturer's recommendations. Only trained personnel should use this material.

Revision comments NOTE: Lines within the margin indicate significant changes from the previous revision.

Issued by Prepared by Autosmart International Ltd, Lynn Lane, Shenstone, Lichfield, Staffordshire, WS14 0DH, Great Britain.
www.autosmartinternational.com
rbutler@autosmart.co.uk
Tel +44 (0)1543 481616

Revision date 15/10/2020

Revision 2

Supersedes date 4/02/2019

WashSmart - Foaming Wheel and Engine Scrub

SDS No.	21671
SDS status	Approved.
Hazard statements in full	H290 May be corrosive to metals. H302 Harmful if swallowed. H314 Causes severe skin burns and eye damage. H315 Causes skin irritation. H318 Causes serious eye damage. H319 Causes serious eye irritation. H351 Suspected of causing cancer.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.